View NSN Online: https://aerobasegroup.com/nsn/5330-00-479-2847

## FEL-PRO CHEMICAL PRODUCTS, L.P. -- 7 M 7260,51313 -- 5330-00-479-2847

============ Product Identification ==============

Product ID:7 M 7260,51313 MSDS Date:02/14/1995

FSC:5330

NIIN:00-479-2847

MSDS Number: CFRDN === Responsible Party ===

Company Name: FEL-PRO CHEMICAL PRODUCTS, L.P.

Address:3412 WEST TOUHY AVENUE

City:SKOKIE State:IL ZIP:60076 Country:US

Info Phone Num:303-289-5651 Emergency Phone Num:303-289-56 51/800-424-9300(CHEMTREC)

Preparer's Name: CATHY GRIFFITH

CAGE:GO402

=== Contractor Identification ===

Company Name: FEL-PRO CHEMICAL PRODUCTS DIV OF FELT PRODUCTS

Address:7450 N MCCORMICK

Box:1205 City:SKOKIE State:IL

ZIP:60076-8205 Country:US

Phone:303-289-5651

CAGE:GO402

Company Name: FEL-PRO CHEMICAL PRODUCTS LP

Address:3412 WEST TOUHY AVE

Box:City:LINCOLNWOOD

State:IL ZIP:60645 Country:US

Phone:303-289-5651

CAGE:05VH4

Company Name: FEL-PRO CHEMICAL PRODUCTS LP

Address:6120 EAST 58TH AVE

Box:Cit

y:COMMERCE CITY State:CO ZIP:80022 Country:US Phone:303-289-5651 CAGE:FELPR Company Name: PHILLIPS GASKET INC **Box:UNKNOW** CAGE:41962 Company Name: RP DIR-SET-PHILLIPS GASKET **Box:UNKNOW** CAGE:9S754 ======= Composition/Information on Ingredients ======== Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 60% Other REC Limits: NONE RECOMMENDED OSHA PEL:200 PPM ACGIH TLV:200 PPM/300STEL;9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty: 5000 LBS Ingred Name: N-HEPTANE CAS:142-82-5 RTECS #:MI7700000 Fraction by Wt: 20% Other REC Limits: NONE RECOMMENDED **OSHA PEL:500 PPM** ACGIH TLV:400 PPM/500STEL;9596 Ingred Name:TALC (ENCAPSULATED) CAS:14807-96-6 RTECS #:WW2710000 Fraction by Wt: 5% Other REC Limits: NONE RECOMMENDED OSHA PEL:20 MPPCF Z-3 ACGIH TLV:2 MG/M3 RDUST; 9596 Ingred Name: ACRYLONITRILE BUTADIENE POLYMER (NON-HAZARDOUS)

CAS:9003-18-3 Fraction by Wt: >3%

Other REC Limits: NONE RECOMMENDED

====== Hazards Ide

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS,

RESPIRATORY & GI TRACTS. ACUTE- MAY CAUSE SEVERE EYE IRRITATION. MAY CAUSE MILD SKIN IRRITATION. INHALATION MAY CAUSE INJURY TO LUNGS. LIVER. KIDNEYS & CNS EFFECTS. HARMF UL/FATAL IF INGESTED.

MAY CAUSE MOUTH, THROAT, STOMACH IRRI

TATION. CHRONIC- MAY CAUSE

CNS, LUNGS, LIVER, KIDNEY EFFECTS.

**Explanation of Carcinogenicity:NONE** 

Effects of Overexposure: SEVERE IRRITATION, HEADACHE, DIZZINESS, NAUSEA, VOMITING, DROWSINESS, FATIGUE, BLURRED VISION, DIARRHEA, PAIN. COUGHING. SHORTNESS OF BREATH

Medical Cond Aggravated by Exposure: INDIVIDUALS WITH PRE-EXISTING DISEASES OF THE EYE, SKIN, RESPIRATORY TRACT, CNS, LIVER, KIDNEY MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

======		
	First Aid Measures	

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES, HOLD EYELIDS OPEN, SKIN: WASH WITH SOAP & WATER. INHALED: MOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NECESSARY. ORAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, WASH OUT MOUTH WITH WATER, DRINK A GLASS OF WATER OR MILK, CALL PHYSICIAN.

============= Fire Fighting Measures ========================

Flash Point Method:SC

Flash Point:22.0F,-5.6C

Lower Limits: 1.0% Upper Limits:11.5%

Extinguishing Media: USE CARBON DIOXIDE (CO2), ALCOHOL FOAM OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures: WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED.

Unusual Fire/Explosion Hazard: VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CONTAI

======== Accidental Release Measures =========
Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH, VERMICULITE. TRANSFER TO A SUITABLE CONTAINER FOR DISPOSAL. PR EVENT LIQUID FROM ENTERING SEWERS OR WATERWAYS.
Neutralizing Agent:NOT RELEVANT
======== Handling and Storage ====================================
Handling and Storage Precautions:STORE IN COOL, VENTILATED AREA, AWAY FROM FLAMES, SPARKS & INCOMPATIBLES. Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. FOLLOW ALL LABEL INSTRUCTIONS. KEEP OUT OF REACH OF CHILDREN. DO NOT INGEST. DO NOT GET IN EYES OR ON SKIN. DO NOT BREATHE VAPOR OR MIST. FOR IN DUSTRIAL USE ONLY.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF TLV IS EXCEEDED OR FOR SYMPTOMS O F OVER EXPOSURE, WEAR NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR OR AIR-PURIFYING RESPIRATOR. IN EMERGENCY, WEAR A NIOSH-APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREA THING APPARATUS. Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S). Protective Gloves:NEOPRENE, BUTYL Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES Other Protective Equipment:WEAR PROTECTIVE CLOTHING IN CASE OF REPEATED OR PROLONGED CONTACT . PROVIDE EYE WASH & SAFETY SHOWER. Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING, DRINKING/SMOKING.
Supplemental Safety and Health
======================================
HCC:F3 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:175F - 210F Vapor Density:>1 Spec Gravity:0.7905 Evaporation Rate & Description of the state of the st

NERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.