View NSN Online: https://aerobasegroup.com/nsn/9130-01-031-5816

Product ID:JP-8, CPS243791 MSDS Date:03/06/1994

FSC:9130

NIIN:01-031-5816

MSDS Number: CFTYR === Responsible Party ===

Company Name: CHEVRON USA PRODUCTS CO

Address:575 MARKET ST City:SAN FRANCISCO

State:CA

ZIP:94105-2856 Country:US

Info Phone Num:415-894-1899;510-242-5357

Emergency Phone Num:800-231-0623;800-424-9300(CHEMTREC)

CAGE:81230

=== Contractor Identification ===

Company Name: CHEVRON ENVIRONMENTAL HEALTH CENTER INC

Address:15299 SAN PABLO AVE

Box:4054

City:RICHMOND

State:CA ZIP:94804 Country:US

Phone:800-582-3835

CAGE:0AHD1

Company Name: CHEVRON PRODUCTS COMPANY LUBRICANTS AND SPECIALTY PRODUCTS

Address:6001 BOLLINGER CANYON RD

Box:City:SAN RAMON

State:CA ZIP:94583 Country:US

Phone:800-414-6737 / 800-582-3835

CAGE:81230

====== Composition/Information on Ingredients ======

=====

Ingred Name: JET FUELS CONTAINING INGS 2,3,4 & 5

RTECS #:9999999ZZ Fraction by Wt: 100%

OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name: KEROSENE; (ALIPHATIC PETROLEUM SOLVENT)

CAS:8008-20-6

RTECS #:OA5500000

OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name: KEROSENE, HYDRODESULFURIZED

CAS:64742-81-0

RTECS #:OA5510000

OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name:DISTILLATES (PETROLEUM), HYDRODESULFURIZED MIDDLE;

(DISTILLATES, HYDRODESULFURIZED MIDDLE)

CAS:64742-80-9 RTECS #:JN9202000 OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name: GAS OIL, BLEND; (DISTILLATES, STRAIGHT RUN MIDDLE)

CAS:64741-44-2

RTECS #:LX3296000

OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name: SUPDAT: INHAL: PRLNGD BRTHG OF VAPS CAN CAUSE CNS EFTS. SIGNS

& SYMPS OF EXPOS: SKIN: MAY INCL PAIN/FEELING OF (ING 7)

RTECS #:9999999ZZ

Ingred Name: ING 6:HEAT, DISCOLORATION, SWELLING, AND BLISTERING. INHAL:

CNS EFTS MAY INCL 1 OR MORE OF FOLLOWING:HDCH, DIZZ, (ING 8)

RTECS #:9999999ZZ

Ingred Name: ING 7:LOSS OF APPETITE, WEAK AND LOSS OF CO

ORDINATION.

CHRONIC: RPTS IN LITERATURE CONCLUDE THAT LONG-TERM EXPOS (ING 9) RTECS #:9999999ZZ

Ingred Name:ING 8:TO JET FUELS MAY RSLT IN CHANGES IN 1)INCIDENCE & PREVALENCE OF PSYCHIATRIC SYMPS 2)PSYCHOLOGICAL TESTS (ING 10) RTECS #:9999999ZZ

Ingred Name:ING 9:AND 3)EEGS. THESE STUDIES WERE CONDUCTED IN SPECIFIC WORK SITUATIONS WHERE THERE WERE EXPOS TO JET FUELS.(ING 11) RTECS #:9999999ZZ

Ingred Name:ING 10:STUDIES HAVE BEEN REVIEWED & IT IS MFR OPINION THAT WORK SITUATIONS

ARE TOO COMPLEX & ANALYTICAL METHS (ING 12)

RTECS #:9999999ZZ

Ingred Name:ING 11:THAT DEFINE BRAIN DMG ARE TOO IMPRECISE TO STATE W/SCIENTIFIC CERTAINTY THAT EITHER CNDTNS OCCURS/IT WAS (ING 13) RTECS #:9999999ZZ

Ingred Name:ING 12:DUE TO TYPE OF MATL DISCUSSED IN DOCUMENT.

CARCIN:PROD CONTAINS MIX OF PETRO HYDROCARBS CALLED MIDDLE (ING 14)

RTECS #:9999992Z

Ingred Name:ING 13:DISTIL (WHICH MEANS THEY BOIL BETWEEN APPROXIMATELY 350F & 750F). BECAUSE OF BROAD DESCRIPTION, MANY PRO D(ING 15)

RTECS #:9999999ZZ

Ingred Name:ING 14:ARE CONSIDERED MIDDLE DISTIL YET THEY ARE PRDCED BY VARIETY OF DIFFERENT PETROL REFINING PROCESSES. TOX (ING 16) RTECS #:9999999ZZ

Ingred Name:ING 15:DATA DEVELOPED ON SOME MIDDLE DISTIL FOUND THAT THEY CAUSE POS RESPONSES IN SOME MUTAGENICITY TESTS & (ING 17) RTECS #:9999992Z

Ingred Name:ING 16:CAUSED SKIN CANCER WHEN RPTDLY APPLIED TO MICE OVER THEIR LIFETIME. PROD MAY CONTAIN SOME MIDDLE DISTIL(ING 18) RTECS #:9999992Z

Ingred Na

me:ING 17:FOUND TO CAUSE THOSE ADVERSE EFFECTS. RTECS #:9999992Z

Ingred Name:FIRST AID PROC:PERS. IF MED ADVICE CANNOT BE OBTAINED, TAKE PERSON & PROD CNTNR TO NEAREST MED EMER TREATMENT (ING 20) RTECS #:9999999ZZ

Ingred Name:ING 19:CTR/HOSPITAL. IF ANY SIGNS/SYMPS AS DESCRIBED OCCUR, MOVE PERSON TO FRESH AIR. IF ANY OF THESE EFTS (ING 21) RTECS #:9999992Z

Ingred Name:ING 20:CONTINUE, SEE MD. NOTE TO PHYS:INGEST OF PROD/SUSSEQUENT VOMIT CAN RSLT IN ASPIR OF LIGHT HYDROCARB LIQ (ING

22)

RTECS #:9999999ZZ

Ingred Name: ING 21: WHICH CAN CAUSE PNEUMONITIS. RTECS #:9999992Z

Ingred Name:SPILL PROC:SOIL & WATER & FROM ENTERING DRAINAGE & SEWAGE SYS. CLEAN UP SM SPILLS USING APPROP TECHNIQUES SUCH (ING 24) RTECS #:9999999ZZ

Ingred Name:ING 23:AS SORBENT MATLS/PUMPING. WHERE FEASIBLE & APPROP, REMOVE CONTAMINATE SOIL. FOR MORE INFO CONT NEHC. RTECS #:9999999ZZ

Ingred Name:OTHER PREC:AVIATION FUELS SHOULD BE FILTERED DURING TRANSFER INTO FUEL TANKS.

RTECS #:9 999999ZZ

=========== Hazards Identification ================

LD50 LC50 Mixture:LD50:(ORAL,RAT) >5 ML/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:EYE:NOT EXPECTED TO CAUSE PRLNGD/SIGNIFICANT IRRITATION. SKIN:MOD IRRITANT SO CONT W/SKIN COULD CAUSE PRLNGD(DAYS) INJURY TO AFFECTED AREA. DEGREE OF INJURY WILL DEPEND ON AMT OF MATL THAT GETS ON SKIN & SPEED &

THOROUGHNESS OF FIRSTAID TREATMENT. IF ABSORBED THRU SKIN, SUBSTANCE IS CONSIDERED (EFTS OF OVEREXP)

Explanation of Carcinogenicity: NOT RELEVANT.

Effects of Overexposure:HLTH HAZ:PRACTICALLY NON-TOX TO INTERNAL ORGANS. INGEST:CONSIDERED PRACTICALLY NON-TOX TO INTERNAL ORGANS. BECAUSE OF LOW VISCOSITY OF SUBSTANCE, IT CAN DIRECTLY ENTER LUNGS IF IT IS SWALLOWED(THIS IS CALLED ASPIR). THIS CAN OCCUR DURING ACT OF SWALLOWING/WHEN VOMIT SUBSTANCE. ONCE IN LUNGS, SUBSTANCE IS

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:EYE:NOT REQD. HOWEVER, AS PREC FLUSH W/FRESH WATER FOR @ LST 15 MINS. REMOVE CONT LENSES IF WORN. SKIN:REMOVE CONTAMD CLTHG. WASH THORO W/SOAP & WATER. SEE MD IF ANY SIGNS/SYMPS DESCRIBED IN DOCUMENT OCCUR. DISCARD CONTAMD NON-WATERPROOF SHOES & BOOTS. WASH CONTAMD CLTHG. INGEST:GIVE WATER/MILK TO DRINK & TELEPHONE FO R MED

ADVICE. DO NOT MAKE PERSON VOMIT UNLESS DIRECTED TO DO SO BY MED (ING 19)

========= Fire Fighting Measures ================

Flash Point Method:TCC Flash Point:100F,38C Lower Limits:0.6% Upper Limits:4.7%

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM & WATER FOG.

Fire Fighting Procedures:NIOSH APPRVD SCBA & FULL PROT EQUIP . LIQ EVAP & FORMS VAP(FUMES) WHICH CAN CATCH FIRE & BURN W/EXPLO VIOLENCE. INVISIBLE VAP SPREADS EASILY & CAN(SUPDAT)

Unusual Fire/Ex

plosion Hazard: NORMAL COMBUSTION FORMS CARBON DIOXIDE

AND WATER VAPOR; INCOMPLETE COMBUSTION CAN PRODUCE CARBON MONOXIDE.

======== Accidental Release Measures ============

Spill Release Procedures:ELIM ALL SOURCES OF IGNIT IN VICIN OF SPILL/RELEASED VAP. CLEAN UP SPILLS IMMED, OBSERVING PREC IN EXPOS CTLS/PERSONAL PROT SECTION. THIS MATL IS CONSIDERED TO BE WATER POLLUTANT & RELEASES OF THIS PR OD SHOULD BE PVNTD FROM CONTAMINATING (ING 23)

Neutralizing Ag

======================================
Handling and Storage Precautions:DO NOT USE/STORE NEAR FLAME, SPARKS/HOT SURFS. USE ONLY IN WELL VENTILATED AREA. KEEP CNTNR CLSD. DO NOT WELD, HEAT/DRILL CONTAINER. Other Precautions:REPLACE CAP/BUNG. EMPTIED CNTNR STILL CONTAINS HAZ/EXPLO VAP/LIQ. CAUTION! DO NOT USE PRESS TO EMPTY DRUM/DRUM MAY RUPTURE W/EXPLO FORCE. WARNING! NOT FOR USE AS PORTABLE HEATER/APPLIANCE FU EL. TOX FU MES MAY ACCUM & CAUSE DEATH. (ING 25)
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NO SPECIAL RESPIRATORY PROTECTION IS NORMALLY REQUIRED. HOWEVER, IF OPERATING CONDITIONS CREATE HIGH AIRBORNE CONCENTRATIONS, THE USE OF AN NIOSH APPROVED RESPIRATOR IS RECOMMENDED. Ventilation:USE THIS MATERIAL ONLY IN WELL VENTILATED AREAS. Protective Gloves:IMPERVIOUS GLOVES. Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES. Other Protectiv e Equipment:ANSI APPRVD EYE WASH & DELUGE SHOWER. Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health FIRE FIGHT PROC:BE SET ON FIRE BY MANY SOURCES SUCH AS PILOT LIGHTS,
WELDING EQUIPMENT, & ELECTRICAL MOTORS AND SWTICHES. FIRE HAZ IS GREATER AS LIQUID TEMPERATURE RISES ABOVE 85F. READ ENTIRE DOCUMEN T. EFTS OF OVEREXP:DIFFICULT TO REMOVE & CAN CAUSE SEVERE INJURY TO LUNGS & DEATH. (ING 6)
======================================
Boiling Pt:B.P. Text:>320F,>160C Melt/Freeze Pt:M.P/F.P Text:-40F,-40C Vapor Pres:0.1 PSIA Vapor Density:5.7 Spec Gravity:0.81 Evaporation Rate & DATA AVAILABLE Solubility in Water:INSOLUBLE Appearance and Odor:PALE YELLOW LIQUID WITH PETROLEUM ODOR. Percent Volatiles by Volume:100
======================================
Stability Indicator/Materials to Avoid:YES MAY REACT WITH STRONG OXIDIZING AGENTS, SUCH AS CHLORATES, NITRATES,

ent:NONE SPECIFIED BY MANUFACTURER.

PEROXIDES, ETC.
Stability Condition to Avoid:NO DATA AVAILABLE.
Hazardous Decomposition Products:NORMAL COMBUSTION FORMS CARBON DIOXIDE

AND WATER VAPOR; INCOMPLETE COMBUSTION CAN PRODUCE CARBON MONOXIDE.

====== Disposal Considerations ===========

Waste Disposal Methods:PLACE CONTAMD MATLS IN DISPOSABLE CNTNRS & DISPOSE IF IN MANNER CONSISTENT W/APPLIC REGS. CONTACT FEDERAL, STATE, AND LOCAL ENVIRONMENTAL/HEALTH AUTHORITIES FOR APPRVD DISPOSAL OF THIS MATERIAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their partic ular situation.