View NSN Online: https://aerobasegroup.com/nsn/5970-01-274-5305

COURTAULDS COATINGS INC -- INTERSHIELD 89 FIRE RESISTANT SEALING PUTTY, GMA 080 -- 5970-01-274-5305

Product ID: INTERSHIELD 89 FIRE RESISTANT SEALING PUTTY, GMA 080 MSDS Date:12/17/1996 FSC:5970 NIIN:01-274-5305 MSDS Number: CFVXZ === Responsible Party === Company Name: COURTAULDS COATINGS INC Address:6001 ANTOINE DRIVE **City:HOUSTON** State:TX ZIP:77091 Country:US Inf o Phone Num:713-684-1227/1563/908-964-2206 Emergency Phone Num:800-854-6813/800-424-9300(CHEMTREC) CAGE:50411 === Contractor Identification === Company Name: COURTAULDS COATINGS INC Address:400 S 13TH STREET Box:City:LOUISVILLE State:KY ZIP:40203-1714 Country:US Phone:502-588-9651 CAGE:50411 Company Name: INTERNATIONAL PAINT CO INC (804-543-1225) **Box:UNKNOW** CAGE:7Z197 Company Name: INTERNATIONAL PAINT INC Address:6001 ANTOINE DRIVE Box:City:HOUSTON State:TX ZIP:77091 Country:US Phone:713-684-1244 CA

GE:028S6 Company Name:INTERPLASTIC CORP Address:1225 WOLTER BLVD City:VADNAIS HEIGHTS State:MN ZIP:55110-5145 Country:US Phone:800-424-9300 CAGE:INTER

Ingred Name:POLYBUTENE CAS:9003-29-6 RTECS #:EM9032000 Fraction by Wt: 10 - 25% Other REC Limits:NONE RECOMMENDED

Ingred Name:TRADE SECRET COMPONENT/TS 14 Fraction by Wt: 1 - 10% Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS INGREDIENTS Fraction by Wt: BALANCE O

ther REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION, NAUSEA, VOMITING, TEARING Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS SUCH AS ALLERGIES, ECZEMA MAY BE MORE SUSCEPTIBLE TO THE E

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH PLENTY OF SOAP & WATE R. ORAL:DO NOT INDUCE VOMITING. KEEP ATREST. SEEK IMMEDIATE MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSO

N.			

Flash Point:450F,232C Extinguishing Media:CARBON DIOXIDE, FOAM OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED.

Unusual Fire/Explosion Hazard:MAY FORM TOXIC PRODUCTS.

Spill R

elease Procedures:WEAR PROTECTIVE EQUIPMENT. VENTILATE AREA. ABSORB ON SAND, VERMICULITE OR SIMILAR MATERIAL. SWEEP UP AND PLACE IN AN APPROPRIATE CONTAINER FOR DISPOSAL. Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE IN COOL, VENTILATED AREA, AWAY FROM FLAMES & STRONG OXIDIZING AGENTS. KEEP CONTAINER TIGHTLY CLOSED.

Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE. FOLLOW ALL LABEL

INSTRUCTIONS. KEEP OUT OF REACH OF CHILDREN. AVOID BREATHING VAPORS. DO NOT GET IN EYE, ON SKIN OR ON CLOTHING. AVOID DIRECT SUNLIGHT.

Respiratory Protection: IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS TO AN ACCEPTABLE LEVEL, A NIOSH-APPROVED ORGANIC VAPOR/AMINE RESPIRATOR MUST BE WORN. A PROGRAM SHOULD BE INSTITUTED TO ASSURE COMPLIANC E WITH OSHA STANDARD 29 CFR 1910.134.

Ventilatio

n:GENERAL MECHANICAL VENTILATION IS ADEQUATE FOR NORMAL USE.

LOCAL EXHAUST IS RECOMMENDED FOR CONFINED AREAS.

Protective Gloves:LATEX FOR REPEATED/PROLONGED CONTACT

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment: EYE WASH STATION, SAFETY SHOWER, PROTECTIVE CLOTHING

Work Hygienic Practices: OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

=====

HCC:N1 NRC/State Lic Num:NOT RELEVANT Vapor Density:>1 Spec Gravity:1.806 Evaporation Rate & amp; Reference: