

M. D. C. INDUSTRIES, INC. -- LAPPING & GRINDING COMPOUND -- 5350-00-193-1348

=====
Product Identification
=====

Product ID:LAPPING & GRINDING COMPOUND

MSDS Date:01/08/1997

FSC:5350

NIIN:00-193-1348

MSDS Number: CFWVJ

=== Responsible Party ===

Company Name:M. D. C. INDUSTRIES, INC.

Address:COLLINS & WILLARD STS

City:PHILADELPHIA

State:PA

ZIP:19134

Country:US

Info Phone Num:215-426-5925

Emergency P

hone Num:215-426-5925

CAGE:KO563

=== Contractor Identification ===

Company Name:M. D. C. INDUSTRIES, INC.

Address:COLLINS & WILLARD STS

Box:City:PHILADELPHIA

State:PA

ZIP:19134

Country:US

Phone:215-426-5925

CAGE:KO563

Company Name:MCD INDUSTRIES

Address:COLLINS & WILLARD STS

Box:City:PHILADELPHIA

State:PA

ZIP:19134

Country:US

CAGE:34274

=====
Composition/Information on Ingredients
=====

Ingred Name:ALUMINUM OXIDE (SARA 313)

CAS:7429-90-5

RTECS #:BD0330000

Other REC Limits:NON

E RECOMMENDED
ACGIH TLV:10 MG/M3

Ingred Name:HYDROTREATED HEAVY NAPHTHENIC DISTILLATE
CAS:64742-52-5
RTECS #:PY8035000
Other REC Limits:NONE RECOMMENDED

Ingred Name:SOLVENT, DEWAXED RESIDUAL OIL (PETROLEUM)
CAS:64742-62-7
Other REC Limits:NONE RECOMMENDED

Ingred Name:LITHIUM SALT SOAPS OF PLANT & ANIMAL DERIVED FATTY OILS
Other REC Limits:NONE RECOMMENDED

Ingred Name:SOLVENT-DEWAXED HEAVY PARRAFINIC DISTILLATE
CAS:64742-65-0
RTECS #:PY8038500
Other REC Limits:NONE RECOMMENDED

Ingred Name:CH
LORINATED PARAFFIN HYDROCARBONS
CAS:63449-39-8
RTECS #:RV0450000
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: IRRITATION, REDNESS, PAIN. SKIN:
IRRITATION. INHAL: RESPIRATORY TRACT IRRITATION. INGEST: GI
IRRITATION, (NAUSEA, VOMIT, DIARRHEA).

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, LIFT LIDS. SKIN: REMOVE BY
WIPING. WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES, WASH BEFORE
REUSE. INHAL: GET FRESH AIR. INGEST: DRINK WATER. INDUCE VOMIT. IN
ALL CASES, GET MED AID.

=====
===== Fire Fighting Measures =====

Flash Point:540F,282C
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:DRY CHEMICAL, CO2, FOAM, WATER FOG.
Fire Fighting Procedures:USE SCBA & PROTECTIVE GEAR

R. COOL TANK &
CONTAINERS W/WATER. IMPROPER USE OF WATER MAY CAUSE FROTHING &
SPREAD FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW OR SPILL IF SAFE. ONCE SOLIDIFIED
SHOVEL MATERIAL INTO CONTAINERS. KEEP OUT OF ALL BODIES OF WATER.
CLEANUP PERSONNEL SHOULD USE PROTECTIVE CLOTHING.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM INCOMPATIBLE
MA
TERIALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR.
Ventilation:(MECHANICAL) LOCAL EXHAUST.
Protective Gloves:RECOMMENDED.
Eye Protection:SAFETY GLASSES/GOGGLES.
Other Protective Equipment:FACE SHIELDS & PROTECTIVE CLOTHING.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:600F,316C
Vapor Pres:70F
Evaporation Rate & Reference: