

DURANT PAINT -- TT-E-2784A -- 8010-01-336-0528

===== Product Identification =====

Product ID:TT-E-2784A  
MSDS Date:09/15/1997  
FSC:8010  
NIIN:01-336-0528  
MSDS Number: CFXGK  
=== Responsible Party ===  
Company Name:DURANT PAINT  
Address:960 BROADWAY  
City:REVERE  
State:MA  
ZIP:02051  
Country:US  
Info Phone Num:617-289-1400  
Emergency Phone Num:617-289-1400  
CAGE:NO367

=== Contractor Identification ===

Company  
Name:DURANT PAINT  
Address:950 BROADWAY  
Box:City:REVERE  
State:MA  
ZIP:02051  
Country:US  
Phone:617-289-1400  
CAGE:NO367  
Company Name:DURANT PAINTS INC  
Address:112 RAILROAD ST  
Box:City:REVERE  
State:MA  
ZIP:02151-4007  
Country:US  
Phone:781-289-8415  
CAGE:3F338

===== Composition/Information on Ingredients =====

Ingred Name:GLYCOL ETHER (VAPOR PRESSURE 25%)  
CAS:111-77-3  
RTECS #:KL6125000  
Fraction by Wt: 7.20%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:GLYCOL ETHER (VAPOR PRESSURE 0.1

%)  
CAS:770-35-4  
Fraction by Wt: 1.30%  
Other REC Limits:NONE RECOMMENDED

Ingrid Name:VOC = 1.46 G/L, NON-EXEMPT SOLVENT PER ADJUSTED GALLON.  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE: IRRITATION. SKIN: IRRITATION.  
INHAL: IRRITATING TO NOSE/THROAT. INGEST:TOXIC.

Effect  
s of Overexposure:INHAL: HEADACHE, NAUSEA, VOMITING, DROWSINESS.  
Medical Cond Aggravated by Exposure:HEART CONDITIONS, ASTHMA.

=====  
First Aid Measures  
=====

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, GET MED AID. SKIN: WASH  
W/SOAP & WATER. REMOVE CONTAIN CLOTHES. INHAL: GET FRESH AIR. OXGEN  
IF NEEDED. INGEST: GIVE TWO GLASSES OF WATER. INDUCE VOMIT.

=====  
Fire Fighting Measures  
=====

Flash Point:NONFLAMMBLE  
Ex  
tinguishing Media:CO2, FOAM.  
Fire Fighting Procedures:USE FULL PROTECTIVE GEAR.  
Unusual Fire/Explosion Hazard:COOL CONTAINERS W/WATER STEAM IN EVENT OF  
A FIRE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:DIKE & CONTAIN. SOAK UP RESIDUE W/ABSORBENT  
MATERIAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. PROTECT  
FROM FREEZING.

=====  
Exposure  
=====

Controls/Personal Protection =====

Respiratory Protection:REQUIRED.  
Ventilation:REQUIRED.  
Protective Gloves:REQUIRED.  
Eye Protection:REQUIRED.  
Other Protective Equipment:APRON.  
Work Hygienic Practices:WASH AFTER HANDLING.  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,156C  
Vapor Density:>AIR  
Evaporation Rate & Reference:VALUE NOT STATED  
Solubility in Water:100%  
Percent Volatiles by Volume:58.9

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
OXIDIZING MATERIALS.  
Stability Condition to Avoid:HEAT, SPARKS & OPEN FLAME.  
Hazardous Decomposition Products:CARBON MONOXIDE & UNIDENTIFIED ORGANIC  
COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN RECKA APPROVED FACILITY.

Disclaimer (provided with this information by the compiling agencies):  
This information is fo  
rmulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.