View NSN Online: https://aerobasegroup.com/nsn/8010-01-418-7176

DURANT PAINT -- TT-E-2784A -- 8010-01-418-7176

Product ID:TT-E-2784A MSDS Date:09/15/1997

FSC:8010

NIIN:01-418-7176

MSDS Number: CFXPK
=== Responsible Party ===
Company Name: DURANT PAINT

Address:960 BROADWAY

City:REVERE State:MA ZIP:02051 Country:US

Info Phone Num:617-289-1400

Emergency Phone Num:617-289-1400

CAGE:NO367

=== Contractor Identification ===

Company

Name:DURANT PAINT Address:950 BROADWAY

Box:City:REVERE

State:MA ZIP:02051 Country:US

Phone:617-289-1400

CAGE:NO367

Company Name: DURANT PAINTS INC

Address:112 RAILROAD ST

Box:City:REVERE

State:MA

ZIP:02151-4007

Country:US

Phone:781-289-8415

CAGE:3F338

====== Composition/Information on Ingredients ========

Ingred Name: GLYCOL ETHER (VAPOR PRESSURE 25%)

CAS:111-77-3

RTECS #:KL6125000 Fraction by Wt: 7.20%

Other REC Limits: NONE RECOMMENDED

Ingred Name: GLYCOL ETHER (VAPOR PRESSURE 0.1

%) CAS:770-35-4 Fraction by Wt: 1.30% Other REC Limits:NONE RECOMMENDED
Ingred Name:VOC = 1.46 G/L, NON-EXEMPT SOLVENT PER ADJUSTED GALLON. RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRITATION. SKIN: IRRITATION. INHAL: IRRITATING TO NOSE/THROAT. INGEST:TOXIC. Effect
s of Overexposure:INHAL: HEADACHE, NAUSEA, VOMITING, DROWSINESS. Medical Cond Aggravated by Exposure:HEART CONDITIONS, ASTHMA.
======================================
First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, GET MED AID. SKIN: WASH W/SOAP & WATER. REMOVE CONTAIM CLOTHES. INHAL: GET FRESH AIR. OXGEN IF NEEDED. INGEST: GIVE TWO GLASSES OF WATER. INDUCE VOMIT.
======================================
Flash Point:NONFLAMMBLE Ex
tinguishing Media:CO2, FOAM. Fire Fighting Procedures:USE FULL PROTECTIVE GEAR. Unusual Fire/Explosion Hazard:COOL CONTAINERS W/WATER STEAM IN EVENT OF A FIRE.
========= Accidental Release Measures ==========
Spill Release Procedures:DIKE & CONTAIN. SOAK UP RESIDUE W/ABSORBENT MATERIAL.
============= Handling and Storage =============
Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. PROTECT FROM FREEZING.
====== Exposure

Respiratory Protection:REQUIRED. Ventilation:REQUIRED. Protective Gloves:REQUIRED. Eye Protection:REQUIRED. Other Protective Equipment:APRON. Work Hygienic Practices:WASH AFTER HANDLING. Supplemental Safety and Health NK
======== Physical/Chemical Properties =========
Boiling Pt:B.P. Text:212F,156C Vapor Density:>AIR Evaporation Rate & Description and Solubility in Water:100% Percent Volatiles by Volume:58.9
==== ========= Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS. Stability Condition to Avoid:HEAT, SPARKS & OPEN FLAME. Hazardous Decomposition Products:CARBON MONOXIDE & UNIDENTIFIED ORGANIC COMPOUNDS.
======== Disposal Considerations ==========
Waste Disposal Methods:DISPOSE OF IN RECKA APPROVED FACILITY.
Disclaimer (provided with this information by the compiling agencies): This information is fo rmulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

Controls/Personal Protection =======

particular situation.