

CARTRIDGE EXPRESS -- EP-L,75 A -- 6850-01-321-0640

=====
Product Identification
=====

Product ID:EP-L,75 A

MSDS Date:02/12/1991

FSC:6850

NIIN:01-321-0640

MSDS Number: CFYGQ

=== Responsible Party ===

Company Name:CARTRIDGE EXPRESS

Address:2700 WEST STREET

City:FALLS CHURCH

State:VA

ZIP:22046-3701

Country:US

Info Phone Num:703-573-6343

Emergency Phone Num:703-573-6343

CAGE:CAREX

=== Contractor Iden

tification ===

Company Name:CARTRIDGE EXPRESS

Address:2700 WEST STREET

Box:City:FALLS CHURCH

State:VA

ZIP:22046-3701

Country:US

Phone:703-573-6343

CAGE:CAREX

=====
Composition/Information on Ingredients
=====

Ingred Name:STYRENE ACRYLATE COPOLYMER

CAS:25153-46-2

Fraction by Wt: 40 - 50%

Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON OXIDE

CAS:1317-61-9

Fraction by Wt: 25 - 45%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 MG/M3

ACGIH TLV:5 MG/M3

Ingred Name:CARBON BLACK

CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 248F,>120C
Spec Gravity:1.5 - 1.7
Viscosity:NOT RELEVANT
Evaporation Rate & Reference:NOT RELEVANT
Solubility in Water:INSOLUBLE
Appearance and Odor:FINE BLACK POWDER - RESIN ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations ==

=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. RECYCLING IS RECOMMENDED. DO NOT INCINERATE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing t
his
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.