

P-T TECHNOLOGIES INC -- REMOVE-HP -- 6850-01-446-8061

=====  
Product Identification  
=====

Product ID:REMOVE-HP

MSDS Date:04/29/1997

FSC:6850

NIIN:01-446-8061

MSDS Number: CFYJV

=== Responsible Party ===

Company Name:P-T TECHNOLOGIES INC

Address:108 4TH AVENUE, SOUTH

City:SAFETY HARBOR

State:FL

ZIP:34695

Country:US

Info Phone Num:800-441-7874 / 813-726-4644

Emergency Phone Num:800-441-7874 / 813-726-4644

CAGE:0JVH6

=== Contractor Identification ===

Company Name:P-T TECHNOLOGIES INC

Address:108 4TH AVENUE, SOUTH

Box:City:SAFETY HARBOR

State:FL

ZIP:34695

Country:US

Phone:813-726-4644

CAGE:0JVH6

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HEAVY AROMATIC NAPHTHA (SOLVENT NAPHTHA)

CAS:64742-94-5

RTECS #:WF3100000

Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYL LACTATE

CAS:97-64-3

RTECS #:OD5075000

Other REC Limits:NONE RECOMMENDED

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE-MAY CAUSE IRRITATION. SKIN-MAY  
CAUSE DEFATTING OR DRYNESS OF SKIN. CONTINUED DRYNESS MAY CAUSE  
DERMATITIS. INHALATION-CAN CAUSE IRRITATION OF THE RESPIRATORY  
TRACT. INGESTION-MAY CAUSE GASTROINTESTINAL IRRITATION.  
Explanation of Carcinogenicity:NOT CARCINOGENIC.  
Effects of Overexposure:E  
EYE-TEARING AND REDNESS. INHALATION-NAUSEA,  
DIZZINESS OR HEADACHE. INGESTION-NAUSEA AND VOMITING.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:EYE-FLUSH WITH WATER FOR 15 MIN. IF IRRITATION PERSISTS,  
CONTACT PHYSICIAN. SKIN-WASH THOROUGHLY WITH SOAP AND WATER. REMOVE  
CONTAMINATED CLOTHING. INHALATION-IF AFFECTED BY VAPOR, GET TO  
FRESH AIR. IF BREATHING IS DIFFICULT, SEE PHYSICIAN.  
AN.INGESTION-DO  
NOT INDUCE VOMITING. PRODUCT CONTAINS HYDROCARBONS. CONSULT  
PHYSICIAN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:133F,56C  
Autoignition Temp:Autoignition Temp Text:410F  
Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY  
CHEMICAL. CLASS B FIRE PROCEDURES.  
Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM COMBUSTIBLE  
MIXTURES AT OR ABOVE FLASH POINT.  
Unusual Fire/Explosion Hazard:NONE KNOWN.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. CONTAIN THE SPILL.  
RECOVER FREE PRODUCT. ABSORB WITH SUITABLE CHEMICAL ABSORBENT FOR  
DISPOSAL VIA INCINERATION OR BURIAL IN APPROVED LANDFILL.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:AMBIENT.  
Other Precautions:KEEP AWAY FROM HEAT SOURCES, OPEN FLAMES, A

ND OTHER  
IGNITION SOURCES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.  
Ventilation:NORMAL ROOM VENTILATION IS USUALLY ADEQUATE. USE FANS OR  
OTHER MECHANICAL VENTILATION IN ENCLOSED AREAS.  
Protective Gloves:SOLVENT RESISTANT GLOVES RECOMMENDED.  
Eye Protection:SAFETY GLASSES RECOMMENDED.  
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.  
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.  
Supplemen  
tal Safety and Health

===== Physical/Chemical Properties =====

HCC:F4  
Vapor Pres:1  
Spec Gravity:.9631  
Solubility in Water: