View NSN Online: https://aerobasegroup.com/nsn/6520-01-328-2307

Product ID:543899 FLUOROSHIELD MSDS Date:09/20/1995 FSC:6520 NIIN:01-328-2307 MSDS Number: CFYQK === Responsible Party === Company Name: CAULK/DENTSPLY Address:LAKEVIEW AND CLARKE AVE Box:359 City:MILFORD State:DE ZIP:19963-0359 Country:US Info Phone Num:302-422-4511/800-532-2855 Emergency Phone Num:302-42 2-4511/800-424-9300(CHEMTREC) CAGE:11107 === Contractor Identification === Company Name: CAULK/DENTSPLY Address:38 W CLARKE AVE Box:359 City:MILFORD State:DE ZIP:19963-0359 Country:US Phone:302-422-4511/703-451-1900 CAGE:11107

Ingred Name:METHACRYLATE MONOMER AND ELASTOMER Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYE CONTACT: MAY CAUSE IRRIT & POSSIBLE CORNEAL DMG.INDIVIDUALS SENSITIVE TO ACRYLICS MAY DEVELOP ALLERGIC RESPONSE.POSSIBLE NAUSEA ON PROLONGED EXPOSURE. Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY:NTP/IARC/OSHA:NO. Effects of Overexposure: EYE CONTACT: IRRITATION OR POSSIBLE CORNEAL DMG.DERMAL IRRIT OR POSSIBLE ALLERGIC RESPONSE Medical Cond Aggravated by Exposure: OPEN SORES OR WOUNDS ON SKIN. KNOWN SENSITIZATION TO ACRYLICS. First Aid:EYE OR SKIN CONTACT:FLUSH W/WATER FOR @LEAST 15MINS AND CONSULT PHYSICIAN IF IRRIT IS APPARENT. Flash Point:NE Autoignition Temp:Autoignition Temp Text:NP Lower Limits:NE Upper Limits:NE Extinguishing Media:CO2, DRY CHEMICAL, FOAM. Fire Fig hting Procedures:WEAR FULL PROTECTIVE CLOTHING INCLUDING SELF CONTAINED RESPIRATOR. Unusual Fire/Explosion Hazard: DURING FIRE IRRITATING DECOMPOSITION PRODUCTS MAY FORM. Spill Release Procedures: ABSORB W/INERT MATLS SUCH AS SAND, VERMICULITE, & TRANSFER TO A CONTAINER FOR DISPOSAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Sto

rage Precautions: STORE AT AMBIENT TEMPERATURES OUT OF SUNLIGHT AND HEAT. Other Precautions: KEEP AWAY FROM FOODSTUFFS. KEEP AWAY FROM FLAME & SPARKS. Respiratory Protection:NOT REQUIRED FOR THE INTENDED USE OF THIS PRODUCT. Ventilation: LOCAL EXHAUST USING EXPLOSION-PROOF MOTORS IS RECOMMENDED. Protective Gloves:LATEX OR VINYL **Eve Protection: GOGGLES** Other Protective Equipment: WEAR GLVOES FOR CLEANUP OPERATIONS. Work H vgienic Practices: OBSERVE NORMAL CARE WHEN WORKING W/CHEMICALS. Supplemental Safety and Health HCC:N1 Boiling Pt:B.P. Text:NA Melt/Freeze Pt:M.P/F.P Text:NA Decomp Temp:Decomp Text:NP Vapor Pres:NE Vapor Density:NE Spec Gravity:1.3 G/CM3 pH:NP Viscosity:NP Evaporation Rate & amp; Reference:NE Solubility in Water: INSOLUBLE Appearance and Odor:CREAMY PASTE W/LIGHT ACRYLIC ODOR Percent Volatiles by Volume:NP Corrosion Rate:NP == Stability Indicator/Materials to Avoid:YES OXIDIZERS. Stability Condition to Avoid: PROLONGED HEAT ABOVE 50C OR DAYLIGHT. Hazardous Decomposition Products:CO, CO2. Conditions to Avoid Polymerization: EXPOSURE TO DAYLIGHT, OPEN FLAME, OR PROLONGED HEAT ABOVE 50C.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

D

isclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation