

CAULK/DENTSPLY -- 543899 FLUOROSHIELD -- 6520-01-328-2307

===== Product Identification =====

Product ID:543899 FLUOROSHIELD
MSDS Date:09/20/1995
FSC:6520
NIIN:01-328-2307
MSDS Number: CFYQK
=== Responsible Party ===
Company Name:CAULK/DENTSPLY
Address:LAKEVIEW AND CLARKE AVE
Box:359
City:MILFORD
State:DE
ZIP:19963-0359
Country:US
Info Phone Num:302-422-4511/800-532-2855
Emergency Phone Num:302-42
2-4511/800-424-9300(CHEMTREC)
CAGE:11107
=== Contractor Identification ===
Company Name:CAULK/DENTSPLY
Address:38 W CLARKE AVE
Box:359
City:MILFORD
State:DE
ZIP:19963-0359
Country:US
Phone:302-422-4511/ 703-451-1900
CAGE:11107

===== Composition/Information on Ingredients =====

Ingred Name:METHACRYLATE MONOMER AND ELASTOMER
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE CONTACT:MAY CAUSE IRRIT & POSSIBLE CORNEAL DMG.INDIVIDUALS SENSITIVE TO ACRYLICS MAY DEVELOP ALLERGIC RESPONSE.POSSIBLE NAUSEA ON PROLONGED EXPOSURE.
Explanation of Carcinogenicity:PER
MSDS:CARCINOGENICITY:NTP/IARC/OSHA:NO.
Effects of Overexposure:EYE CONTACT:IRRITATION OR POSSIBLE CORNEAL DMG.DERMAL IRRIT OR POSSIBLE ALLERGIC RESPONSE
. Medical Cond Aggravated by Exposure:OPEN SORES OR WOUNDS ON SKIN.KNOWN SENSITIZATION TO ACRYLICS.

=====
===== First Aid Measures =====

First Aid:EYE OR SKIN CONTACT:FLUSH W/WATER FOR @LEAST 15MINS AND CONSULT PHYSICIAN IF IRRIT IS APPARENT.

=====
===== Fire Fighting Measures =====

Flash Point:NE
Autoignition Temp:Autoignition Temp Text:NP
Lower Limits:NE
Upper Limits:NE
Extinguishing Media:CO2, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING INCLUDING SELF CONTAINED RESPIRATOR.
Unusual Fire/Explosion Hazard:DURING FIRE IRRITATING DECOMPOSITION PRODUCTS MAY FORM.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB W/INERT MATLS SUCH AS SAND,VERMICULITE,& TRANSFER TO A CONTAINER FOR DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Sto

Precautions:STORE AT AMBIENT TEMPERATURES OUT OF SUNLIGHT AND HEAT.

Other Precautions:KEEP AWAY FROM FOODSTUFFS.KEEP AWAY FROM FLAME & SPARKS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED FOR THE INTENDED USE OF THIS PRODUCT.

Ventilation:LOCAL EXHAUST USING EXPLOSION-PROOF MOTORS IS RECOMMENDED.

Protective Gloves:LATEX OR VINYL

Eye Protection:GOGGLES

Other Protective Equipment:WEAR GLOVES FOR CLEANUP OPERATIONS.

Work H

Hygienic Practices:OBSERVE NORMAL CARE WHEN WORKING W/CHEMICALS.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:NP

Vapor Pres:NE

Vapor Density:NE

Spec Gravity:1.3 G/CM3

pH:NP

Viscosity:NP

Evaporation Rate & Reference:NE

Solubility in Water:INSOLUBLE

Appearance and Odor:CREAMY PASTE W/LIGHT ACRYLIC ODOR

Percent Volatiles by Volume:NP

Corrosion Rate:NP

==

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS.

Stability Condition to Avoid:PROLONGED HEAT ABOVE 50C OR DAYLIGHT.

Hazardous Decomposition Products:CO, CO2.

Conditions to Avoid Polymerization:EXPOSURE TO DAYLIGHT, OPEN FLAME, OR PROLONGED HEAT ABOVE 50C.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

D

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation

.