

CSD, INC -- SOLVENT,350-66 -- 6850-00-274-5421

=====
Product Identification
=====

Product ID:SOLVENT,350-66

MSDS Date:11/30/1992

FSC:6850

NIIN:00-274-5421

MSDS Number: CFYWX

=== Responsible Party ===

Company Name:CSD, INC

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Info Phone Num:409-756-1065/713-797-0395(MEDICAL)

Emergency Phone Num:713-923-6641/800-424-9300(CHEMTREC)

Preparer's Name:SUE B

OTTOM

CAGE:0LWP6

=== Contractor Identification ===

Company Name:CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:4N760

Company Name:CSD, INC

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:800-424-9300

CAGE:0LWP6

=====
Composition/Information on Ingredients
=====

Ingred Name:PARAFFINIC AND NAPHTHENIC HYDROCARBONS/SOLVENT NAPHTHA
(PETROLEUM) MEDIUM ALIPHATIC

CAS:64742-88-7

O

ther REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:NONANE/N-NONANE

CAS:111-84-2

RTECS #:RA6115000

Fraction by Wt: 2 - 6%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM; 9596

Ingred Name:OCTANE/N-OCTANE

CAS:111-65-9

RTECS #:RG8400000

Fraction by Wt: 400F

Lower Limits:0.9%

Upper Limits:6.0%

Extinguishing Media:USE WATER FOG/SPRAY, FOAM, DRY CHEMICAL, CARBON DIOXIDE. PRODUCT MAY FLOAT AND CAN BE REIGNITED.

Fire Fighting

Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITIO

N. VENTILATE AREA. CONTAIN SPILL. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH/PUMP (EXPLOSION PROOF). GROUND ALL HANDLING EQUI PMENTS. PREVENT LIQUID FROM ENTERING SEWERS.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, WELL VENTILATED AREA AWAY FROM HEAT, SPARKS, OTHER SOURCES OF IGNITION & INCOMPATIBLE MATERIALS. KEEP OUT OF REACH OF CHILDREN.

Other Preca

utions:EMPTY CONTAINERS RETAIN RESIDUE. DO NOT WELD, SOLDER,
DRILL OR EXPOSE SUCH CONTAINERS TO FLAME, SPARKS. AVOID REPEATED OR
PROLONGED SKIN CONTACT. DO NOT GET IN EYES. DO NOT BREATHE VAPOR OR
MIST. WASH THOROUGHLY AFTER HANDLING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF WORKING IN CONFINED AREAS, IF EXCESSIVE
MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES EXCEED RECOMMENDED
PERMISSIBLE EXPOSURE LIMITS (PEL), WEAR NIOSH-APPROVED RESPIRATORY

PROTECTION FOR ORGANIC VAPORS (REFER TO 29 CFR 1910.134).

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF)
VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NEOPRENE IF REPEATED CONTACT POSSIBLE

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING, APRON, AND BOOTS IF SPILLS OR
SPLASHING CAN OCCUR.

Work Hygienic Practices:OBSERVE

GOOD INDUSTRIAL HYGIENE PRACTICES AND

RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING,
DRINKING/SMOKING.

Supplemental Safety and Health

FORMULA CHANGED. SEE PNI A&B. NOTE TO PHYSICIAN:IN CASE OF INGESTION,
GASTRIC LAVAGE WITH ACTIVATED CHARCOAL CAN BE USED. USE OF AN
INTRATRACHEAL TUBE PREVENTS ASPIRATION. INDIVIDUALS INTOXICATED
SHOULD BE HOSPITALIZED FOR OBSERVATION (DELAYED EFFECTS ON BLOOD,
HEART & LUNGS). HEART MAY BE SENSITIZED TO CATECHOLAMINES.

=====

===== Physical/Chemical Properties =====

HCC:F4

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:350F - 400F

Vapor Pres:81 @ 100F

Vapor Density:>1

Spec Gravity:0.79

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WATER-WHITE LIQUID; MILD HYDROCARBON ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS, CAUSTICS, HALOGENS

Stability Condition to Avoid:HEAT, SPARKS, FLA

MES, STATIC ELECTRICITY
AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE,
REACTIVE HYDROCARBONS (ALDEHYDES, AROMATICS, ETC.) MAY BE FORMED.

===== Disposal Considerations =====

Waste Disposal Methods: RECLAIM BY DISTILLATION OR INCINERATE ABSORBED
MATERIALS IN A LICENSED HAZARDOUS WASTE FACILITY. DISPOSAL SHOULD
BE IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with
this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.