

ROHM & HAAS CO -- ACRYLOID B-72 50% RESIN, 66753 -- 8040-00-887-1450

=====  
Product Identification  
=====

Product ID:ACRYLOID B-72 50% RESIN, 66753

MSDS Date:05/17/1989

FSC:8040

NIIN:00-887-1450

MSDS Number: CGDSZ

=== Responsible Party ===

Company Name:ROHM & HAAS CO

Address:INDEPENDENCE MALL WEST

City:PHILADELPHIA

State:PA

ZIP:19105

Country:US

Info Phone Num:215-592-3000

Emergency Phone Num:215

-592-3000;800-424-9300(CHEMTREC)

CAGE:GO264

=== Contractor Identification ===

Company Name:ROHM & HAAS CO

Address:100 INDEPENDENCE MALL WEST

City:PHILADELPHIA

State:PA

ZIP:19106-2399

Country:US

Phone:215-592-3000

CAGE:GO264

Company Name:ROHM AND HAAS CO

Address:100 INDEPENDENCE MALL WEST

Box:City:PHILADELPHIA

State:PA

ZIP:19106-2399

Country:US

Phone:215-592-2521/215-592-3000

CAGE:77902

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ACRYLIC COPOLYMER

Fraction b

y Wt: 49-51%  
OSHA PEL:N/K  
ACGIH TLV:N/K

Ingred Name:RESIDUAL MONOMER  
Fraction by Wt: 0.6%  
OSHA PEL:N/K  
ACGIH TLV:N/K

Ingred Name:TOLUENE (SARA 313) (CERCLA)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 49-51%  
OSHA PEL:200 PPM  
ACGIH TLV:50 PPM, S  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:SPILL PROC: FOR RECOVERY OR DISPOSAL AND SOLID DIKING  
MATERIAL TO SEPARATE CONTAINERS FOR DISPOSAL. KEEP SPILLS (ING 5)  
RTECS #:9999999ZZ

Ingred Name:ING 4: AND CLEANING RUNOFFS OUT OF M  
UNICIPAL SEWERS AND  
OPEN BODIES OF WATER. NOTE: SPILLS ON POROUS SURFACES (ING 6)  
RTECS #:9999999ZZ

Ingred Name:ING 5: CAN CONTAMINATE GROUNDWATER.  
RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHAL: SOLVENT VAPOR OR MIST CAN CAUSE  
HEADACHE, DIZZINESS, N  
AUSEA, LOSS OF CONSCIOUSNESS & IRRIT OF NOSE,  
THROAT & LUNGS. SKIN CONTACT: IRRITATING TO SKIN UPON RPTD/PRLNGD  
CONTACT. LIQUID SUBSTANCE C AN BE ABSORBED THRU INTACT SKIN IN  
HARMFUL AMOUNTS. EYE CONTACT: SUBSTANCE CAN CAUSE IRRIT & TRANSIENT  
(EFTS OF OVEREXP)  
Explanation of Carcinogenicity:NOT RELEVANT  
Effects of Overexposure:HLTH HAZ: CORNEAL INJURY. CHRONIC: TOLUENE  
APPEARS ON THE NAVY LIST OF OCCUPATIONAL CHEMICAL REPRODUCTIVE  
HAZARDS. SEEK CONSULTATION FROM APPROP HE

ALTH PROFESSIONALS

CONCERNING LATEST HAZ LIST INFO & SAFE HANDLING & EXPOSURE INFO .  
RPTD OVEREXP TO TOLUENE CAN CAUSE CNS EFTS. EFTS OF OVEREXP ARE  
BASED ON (SUPDAT)

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
First Aid Measures  
=====

First Aid:INHAL: MOVE TO FRESH AIR. GIVE ARTF RESP IF BRTHG HAS  
STOPPED. SEE MD. EYES: FLUSH EYES W/LARGE AMT OF WATER FOR AT LEAST  
15 MIN. SEE MD IF IRRIT PERSISTS. WASH AF  
FECTED SKIN AREAS W/SOAP &  
WATER. ING EST: IF SWALLOWED GIVE TWO GLASSES OF WATER TO DRINK.  
SEE MD. NEVER GIVE ANYTHING BY MOUTH TO AN UNCON PERSON. NOTE TO  
MD: PROD CONTAINS TOLUENE, A PETRO DISTIL HAVING CNS EFTS. CAREFUL  
(SUPDAT)

=====  
Fire Fighting Measures  
=====

Flash Point Method:PMCC  
Flash Point:44.6F,7.0C  
Lower Limits:1.2%  
Upper Limits:7.1%  
Extinguishing Media:ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER  
SPRAY.  
Fire Fighting Pr  
ocedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE  
EQUIPMENT . USE WATER SPRAY TO COOL CONTAINERS.  
Unusual Fire/Explosion Hazard:VAPORS CAN TRAVEL TO A SOURCE OF IGNITION  
AND FLASH BACK. MATERIAL CAN FORM EXPLOSIVE VAPOR WITH AIR.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE IGNITION  
SOURCES. WEAR NIOSH APPROVED RESP (PRESSURE-DEMAND, SCBA OR  
EQUIVALENT) OR AIR MASK FOR LARGE SPILLS IN CONFINED AR  
EA. DIKE &  
CONTAIN SPILL W/INERT MATL (EG, S AND, EARTH). TRANSFER LIQUID TO  
CONTAINERS (ING 4)  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORAGE TEMPERATURE: -18C/0F TO  
60C/140F. LIMIT STORAGE OF FLAMMABLE MATERIAL TO APPROVED AREAS.  
GROUND ALL CONTAINERS WHEN TRANSFERRING MATERIAL.  
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====  
Exposure Controls/Per  
=====

sonal Protection =====

Respiratory Protection:NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED.  
WEAR NIOSH APPROVED RESPIRATOR SUITABLE FOR CONCENTRATIONS AND  
TYPES OF AIR CONTAMINANTS ENCOUNTERED.

Ventilation:EXPLOSION-PROOF LOCAL EXHAUST VENTILATION AT POINT OF  
CONTAMINANT RELEASE.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPROVED EYE WASH & DELUGE SHOWER .

Work Hygienic Practices:NONE SPECIFIED  
BY MANUFACTURER.

Supplemental Safety and Health

% VOLAT: 50-52 (WT). EFTS OF OVEREXP: INFO ABOUT SIMILAR MATLS & ON  
TOXICITY PROFILES FOR SOLVENTS USED IN THIS PROD. NOTE: OVEREXP TO  
TOLUENE HAS CAUSED EMBRYOFETOTOXIC EFTS IN LAB ANIMALS. FIRST AID  
PROC: GASTRIC LAVAGE MAY BE INDICATED BECAUSE OF RISK OF ASPIRATION  
POSED BY PETROLEUM DISTILLATES.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:230F,110C

Melt/Freeze Pt:M.P/F.P Text:-139

F,-95C

Vapor Pres:22 @ 20C

Vapor Density:>1

Spec Gravity:1.0 (H\*2O=1)

Evaporation Rate & Reference:>1 (BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, VISCOUS LIQUID; SOUR, BURNT ODOR.

Percent Volatiles by Volume:SUPDAT

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS.

Stability Condition to Avoid:NOT APPLICABLE.

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

=====

===== Disposal Considerations =====

Waste Disposal Methods:WHEN DISCARDED THIS MATERIAL IS A HAZARDOUS WASTE. RCRA #U-220, RQ 2000 LBS (40 CFR 302, SUPERFUND). INCINERATE LIQUID AND CONTAMINATED MIXING MATERIAL AT A PERMITTED FACILITY IN ACCORDANCE WITH LOCAL , STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.