

PRAXAIR INC -- OXYGEN -- 6830-01-431-0681

=====
Product Identification
=====

Product ID:OXYGEN

MSDS Date:12/01/1992

FSC:6830

NIIN:01-431-0681

MSDS Number: CGDZK

=== Responsible Party ===

Company Name:PRAXAIR INC

Address:39 OLD RIDGEBURY RD

City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Info Phone Num:203-794-5782

Emergency Phone Num:203-794-5782/800-424-9300(CHEMTREC)

CAGE:0LV01

=== Contractor I

dentification ===

Company Name:PRAXAIR, INC.

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06810-5113

Country:US

Phone:800-772-9247; 800-PRAXAIR

CAGE:0LV01

=====
Composition/Information on Ingredients
=====

Ingred Name:OXYGEN

CAS:7782-44-7

RTECS #:RS2060000

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV:NONE CURRENTLY ESTABLISHED

Routes of Entry: Inhalation:YES Sk

in:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN/EYE/INGEST/SKIN ABSORPTION:NO

EVIDENCE OF ADVERSE EFFECTS FRM AVAI INFO.INHAL:BREATH 80% OR MORE OXY @ATMS PRESSURE FOR MORE THAN FEW HRS MAY CAUSE NASAL STUFFINESS,COUGH,SORE THROAT,CHEST PAIN,B REATH DIFFI.BREATH OXY @HI PRESSURE INCR LIKELIHOOD OF ADVERSE EFFECTS W/IN SHORTER TIME PER.BREATH PURE OXY UNDER(SUP)

Effects of Overexposure:NO EVIDENCE OF ADVERSE EFFEC TS FROM AVAILABLE INFORMATION.

Medical Cond Aggravated by Exposure:INDIVIDUALS WHOSE RETINAL CIRCULATION HAS BEEN PREVEIOUSLY COMPROMISED.

=====
===== First Aid Measures =====

First Aid:INGEST:THIS PRODUCT IS GAS @NORMAL TEMP/PRESSURE.SKIN:NO EMERGENCY CARE ANTICIPATED.INHAL:REMOVE TO FRESH AIR.GIVE ARTIFICIAL RESPRIATION IF NOT BREATHING.KEEP VICTIM WARM & @REST.CALL PHYSICIAN.EYE:N O EMERGENCY CARE ANTICIPATED.

=====
===== Fire Fighting Measures =====

Flash Point:NA

Autoignition Temp:Autoignition Temp Text:NA

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:VIGOROUSLY ACCELERATES COMBUSTION.USE MEDIA APPROP FOR SURROUNDING FIRE.WATER(SAF SHOWER)PREFER EXT MEDIA FOR CLOTH FIRE

Fire Fighting Procedures:EVACUATE ALL PERSONNEL FROM DANGER AREA.IMMED COOL CNTNRS W/WATER SPRAY FROM MAX DISTANCE TIL COOL,THEN MOVE CNTNRS AWAY FRM FIRE AREA IF W/O RISK.

Unusual Fire/Explosion Hazard:OXIDIZI

NG AGENT,VIGOROUSLY ACCELERATES

COMBUSTION.CONTACT W/FLAMM MATL MAY CAUSE FIRE/EXPLO.CNTNR MAY RUPTURE DUE TO FIRE HEAT. DONT SUBJ TO >52C.(NEUTRALIZ)

=====
===== Accidental Release Measures =====

Spill Release Procedures:SHUT OFF LEAK W/O RISK.VENTI AREA/MOVE LEAK CNTNRN TO WELL VENTI AREA.REMOVE ALL FLAMM MATLS FROM VICINITY.OXY MUST NEVER BE PERMITTED TO STRIKE OILY SURF,GREASY CLOTHES,OTHER COMBUST MATL.

Neutralizing Agent:FIRE/EXPLO:MOST CNTNR PRO

VIDE W/PRESS RELIEF
DEVICE-VENT WHEN EXPO HI TEMP.

===== Handling and Storage =====

Handling and Storage Precautions:READ/UNDERSTAND MFG
INSTRUCTIONS/PRECAUT LABEL ON PROD.SEE AMER STD Z49.1 & OSHA
PUBLICATION 2206(29CFR1910).REFER PRAXAIR L-52-529,L-2035-FREE
COPIES

Other Precautions:ALL EXPO FOR LONG PER OT OXY @HI PRESSURE & ALL WHO
EXHIBIT OVERT OXY TOXICITY SHOULD HAVE OPHTHALMOLOGIC EXAMS.NEVER
USE MANIFOLDS FOR OXY CYL UNLESS SP
EC DESGND FOR SUCH USE.PROTECT
CNTNR AGAINST P HYS DMG/OVERHEAT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED UNDER NORMAL USE.HOWEVER
AIR-SUPPLIED RESPIRATORS ARE REQUIRED WHILE WORKING IN CONFINED
SPACES W/THIS PRODUCT.THE RESP PROTECTION USE MSUT CONFORM W/OSHA
RULES AS SPECIFIED IN 29CFR1910 .134.

Ventilation:USE LOCAL EXHAUST SYST IF NECESSARY TO PREVENT BUILD UP OF
OXY CONCEN.MECH(GEN):ACCEPTABLE.

Protective

Gloves:PREFERRED FOR CYLINDER HNDLG

Eye Protection:SELECT IAW OSHA 29CFR1910.133

Other Protective Equipment:METATARSAL SHOES FOR CYL HNDLG.SELECT IAW
OSHA 29CFR1910.132,10910.133.

Work Hygienic Practices:NEVER WORK ON PRESSUR SYS.IF LEAK CLOSE CYL
VALVE BLOW DOWN SYS(VENTI),REPAIR LEAK.NEVER LUB OXY VALV,REG,ETC
W/COMB MAT

Supplemental Safety and Health

HEALTH:PRESSURE MAY CAUSE LUNG DMG & ALSO CNS EFFECES RESULTING IN
DIZZ,POOR COORDINATION,TINGLING SENS,VISUAL/HEARING
DISTU

RBANCES,MUSCULAR TWITCHING,UNCONSC,CONVUL.BREATH OXY UNDER
PRESSURE MAY CAUSE PROLONGATION OF ADAPTION TO DARKNESS &RED
PERIPHERAL VISION.

===== Physical/Chemical Properties =====

HCC:D1

Boiling Pt:B.P. Text:-297F,-183C

Melt/Freeze Pt:M.P/F.P Text:-361F,-218C

Decomp Temp:Decomp Text:NP

Vapor Pres:GAS

Vapor Density:1.10

Spec Gravity:GAS

pH:NP

Viscosity:NP

Evaporation Rate & Reference:NA

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORLESS, ODORLES

S GAS AT NORMAL TEMPERATURE AND
PRESSURE.

Percent Volatiles by Volume:100

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

COMBUSTIBLE MATLS,ASPHALT,FLAMM MATLS,ESPECIALLY OILS & GREASES.

Stability Condition to Avoid:SMOKING,FLAMES,ELECTRIC SPARKS IN PRESENCE
OF ENRICHED OXY ATMS ARE POTENTIAL EXPLO HAZ.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

==

Waste Disposal Methods:SLOWLY RELEASE INTO ATM IN OPN OUTDOORS
AREA.REMOVE ALL FLAMM MATLS FROM VICINITY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent profession
al advice to verify and
assume responsibility for the suitability of this information to their
particular situation.