

THE GREEN PAINT COMPANY INC. -- YELLOW FAST DRY TRAFFIC PAINT -- 8010-01-019-1776

=====
Product Identification
=====

Product ID:YELLOW FAST DRY TRAFFIC PAINT

MSDS Date:12/07/1994

FSC:8010

NIIN:01-019-1776

MSDS Number: CGFCX

=== Responsible Party ===

Company Name:THE GREEN PAINT COMPANY INC.

Address:9 MAIN STREET

City:MANCHAUG,

State:MA

ZIP:01526

Country:US

Info Phone Num:508-476-1992

Emergency Ph

one Num:508-476-1992

Preparer's Name:M. S. HERBERT

CAGE:THEGR

=== Contractor Identification ===

Company Name:THE GREEN PAINT COMPANY, INC

Box:430

City:MANCHAUG

State:MA

ZIP:01526

Country:US

Phone:800-424-9300 (CHEMTREC)

CAGE:THEGR

=====
Composition/Information on Ingredients
=====

Ingred Name:2,2,4-TRIMETHYL-3,3,-PENTANEDIOL MONOISOBUTYRATE

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: 1.68%

Other REC Limits:NONE RECOMMENDED

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA 313

) (CERCLA)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 2.12%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGEST: TOXIC & DIZZINESS. MAY CAUSE
MENTAL SLUGGISHNESS.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR >15 MINUTES, CALL DR IMMED. SKIN: WASH
W/LARGE AMOUNTS OF WATER. INHAL: REMOVE TO FRESH AIR, CALL DR
IMMED. INGEST: INDUCE VOMIT IF CONSCIOUS, CALL DR IMMED.

=====
===== Fire Fighting Measures =====

Flash Point:130 TO 140F
Autoignition Temp:Autoignition Temp Text:NA
Lower Limits:5.5
Upper Limits:36.5
Extinguishing Media:CO2, DRY CHEMICAL, FOAM & WATER FOG.
Fire Fighting Procedures:USE SCBA.
Unusual Fire/Ex
plosion Hazard:VAPORS >AIR. MAY TRAVEL TO SOURCES OF
IGNITION & FLASH BACK. CLOSED CONTAINER MAY BURST IN HEAT OF FIRE &
EMIT TOXIC GASES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITS. AVOID EYE CONTACT. ASSURE
ADEQUATE VENT. USE ABSORBENT TO CONTAIN.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DONT STORE AT >80F OR AIR
Spec Gravity:1.69
Evaporation Rate &

Reference:NA

Solubility in Water:100%

Appearance and Odor:OPAQUE LIQUID, W/CHARACTERISTIC ALCOHOL ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER REACTIVE MATERIALS.

Hazardous Decomposition Products:CARBON DIOXIDE, & CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL/STATE/LOAL REGULATIONS.
INCINERATION PREFERRED.

Disclaimer (provi

ded with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.