View NSN Online: https://aerobasegroup.com/nsn/6810-00-543-7915

Product ID: IPA 99% MSDS Date:11/22/1996 FSC:6810 NIIN:00-543-7915 **MSDS Number: CGFNQ** === Responsible Party === Company Name: SOLVENTS AND CHEMICALS, INC. Address:4704 SHANK ROAD Box:490 City:PEARLAND State:TX ZIP:77581 Country:US Info Phone Num:713-485-5377/FAX-6129 Emergency Phone Num:713-485-5377/800-4 24-9300 CAGE:4W432 === Contractor Identification === Company Name: SOLVENTS AND CHEMICALS, INC. Address:4704 SHANK ROAD Box:City:PEARLAND State:TX ZIP:77588-0490 Country:US Phone:281-485-5377 CAGE:4W432 Ingred Name: ISOPROPYL ALCOHOL (SARA 313) CAS:67-63-0 RTECS #:NT8050000 Other REC Limits:NONE RECOMMENDED **OSHA PEL:400 PPM** ACGIH TLV:400 PPM/500STEL;9596

LD5

0 LC50 Mixture:TLV: 200 PPM Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE & SKIN-PRIMARY IRRITATION TO SKIN, DEFATTING, DERMATITIS. PRIMARY IRRITATION TO EYES. LIQUID CAN CAUSE EYE IRRITATION. INHALATION-ANESTHETIC. IRRITATES RESPIRATORY TRACT. ACUTE OVEREXPOSURE CAN CA USE SERIOUS NERVOUS SYSTEM DEPRESSION. VAPOR HARMFUL. SWALLOWING-HRAMFUL OR FATAL IF SWALLOWED. Explanation of C arcinogenicity:THIS PRODUCT HAS NO CARCINOGENS LISTED BY IARC, NTP, NIOSH, OSHA OR ACGIH, AS OF THIS DATE, GREATER OR EQUAL TO 0.1%.

Effects of Overexposure:EYES-REDNESS, TERAING, BLURRED VISION. SWALLOWING-CAN CAUSE ABDOMINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.

Medical Cond Aggravated by Exposure:PERSONS WITH SEVERE SKIN, LIVER OR KIDNEY PROBLEMS SHOULD AVOID USE.

First Aid:EYE:FLUSH W/WATER 15 MIN

& GET MEDICAL ATTENTION.

SKIN:IMMEDIATELY REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY WITH SOAP & WATER. INHALATION:REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYG EN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. SWALLOWING:CALL A PHYSICIAN IMMEDIATELY. INDUCE VOMITING PROMPTLY USING PHYSICIAN'S INSTRUCTIONS.

Flash Point Method:TCC Flash Point:51.8F,11.0C Autoignition Temp:Autoignitio n Temp Text:371C Lower Limits:2 Extinguishing Media:NFPA CLASS B EXTINGUISHERS (CARBON DIOXIDE OR FOAM) FOR CLASS II LIQUID FIRES. Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE ON FIRE BUT CAN PROTECT FIRE-FIGHTERS. USE FOG NOZZLES. USE NIOSH APPROVED POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:COMBUSTIBLE! KEEP CONTAINER TIGHTLY CLOSED. ISOLATE FROM OXIDIZERS, HEAT & OPEN FLAMES. CLOSED CONTAINER MAY EXPLODE IF EXPOSED TO EXT REME HEAT.

Spill Release Procedures:STOP SPILL AT SOURCE. DIKE AREA AND CONTAIN. CLEANUP REMAINDER WITH ABSORBENT MATERIAL. MOP UP AND DISPOSE OF. PERSONS WITHOUT PROPER PROTECTION SHOULD BE KEPT FROM AREA UNTIL CLEANED UP.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: ISOLATE FROM OXIDIZERS, HEAT AND OPEN

FLAMES. DO NOT STORE ABOVE 49C/120F. STORE LARGE AMOUNTS IN STRUCTURES MADE FROM OSHA CLASS II LIQUIDS.

Other Precautions: KEEP CONTAINER TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE TO PREVENT LEAKAGE. USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING OF VAPOR OR SPRAY MIST. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection: USE NIOSH APPROVED POSITIVE PRESSURE SELF-CONTAINED BREATHING

APPARATUS. CONSULT SAFETY EQUIPMENT SUPPLIER.

USE EXPLOSION PROOF EQUIPMENT.

Ventilation:LOCAL EXHAUST-NECESSARY. MECHANICAL (GENERAL)-ACCEPTABLE. Protective Gloves:WEAR GLOVES.

Eye Protection: OSHA STANDARD GOGGLES OR FACE SHIELD.

Other Protective Equipment: WEAR APRON & FOOT WARE IMPERVIOUS TO THIS MATERIAL.

Work Hygienic Practices:WASH CLOTHING BEFORE REUSE. Supplemental Safety and Health

EMPTY CONTAINERS VERY HAZARDOUS!

HCC:F2

NRC/State Lic Num:NONE Boiling Pt:=80.C, 176.F Vapor Pres:33 MMHG Vapor Density:2.1 Spec Gravity:0.787 Solubility in Water:COMPLETE Appearance and Odor:LIQUID, WATER-WHITE, ALCOHOL ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS SUCH AS PERMANGANATES, CHROMATES AND PEROXIDES. Stability Condition to Avoid:ISOLATE FROM OXIDIZERS, HEAT, SPARKS, ELECTRICAL EQUIPMEN

T AND OPEN FLAMES.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE FROM BURNING.

Waste Disposal Methods:RECYCLE OR DISPOSE OF OBSERVING LOCAL, STATE AND FEDERAL HEALTH, SAFETY AND POLLUTION LAWS. IF QUESTIONS EXXIST, CONTACT THE APPROPIATE AGENCIES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defe

nse. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.