OF Е Е Μ SCIENCE DIV Μ **INDUSTRIES** INC 1,2-DICHLOROETHANE,DX0794,DX0796,DX0797,DX0800,DX0805 -- 6810-00-838-5932 Product ID:1,2-DICHLOROETHANE, DX0794, DX0796, DX0797, DX0800, DX0805 MSDS Date:02/12/1997 FSC:6810 NIIN:00-838-5932 MSDS Number: CGLSS === Responsible Party === Company Name: E M SCIENCE DIV OF E M INDUSTRIES INC Address:400 DEMOCRAT RDD **Box:70** City:GIBB STOWN State:NJ ZIP:08027-0070 Country:US Info Phone Num:609-423-6300 Emergency Phone Num:609-423-6300/800-424-9300(CHEMTREC) CAGE:63612 === Contractor Identification === Company Name: E M SCIENCE DIV OF E M INDUSTRIES INC Address:480 DEMOCRAT ROAD Box:70 City:GIBBSTOWN State:NJ ZIP:08027 Country:US Phone:800-222-0342/609-423-6300 CAGE:63612 Company Name: VWR SCIENTIFIC - DIV OF UNIVAR Address:200 CENTER SQUARE RD Box:626 City:BRIDGEPORT State:NJ ZIP:08014 Country:US Phone:609-467-2600 CAGE:2E624

View NSN Online: https://aerobasegroup.com/nsn/6810-00-838-5932

Ingred Name:1,2-DICHLOROETHANE/ETHYLENE DICHLORIDE (SARA 313) (CERCLA) CAS:107-06-2 RTECS #:KI0525000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED OSHA PEL:50 PPM; Z-2 ACGIH TLV:10 PPM; 9596 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS LD50 LC50 Mixture: LC50 (INHL, RAT) 1000 PPM/7 HRS Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of C arcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYES, SKIN, CNS, LIVER, KIDNEY, BLOOD. ACUTE & CHRONIC- MAY CAUSE SEVERE EYE IRRITATION & POSSIBLY BURNS. MAY CAUSE SKIN IRRITATION. MAY BE TOXIC IF INHALED/INGESTED/ABSORBED THROUGH SKI N. REPEATED/PROLONGED EXPOSURE MAY CAUSE DAMGE TO LIVER, KIDNEYS, LUNGS & BLOOD. MAY CAUSE CNS DEPRESSION & COMA. Explanation of Carcinogenicity:NONE Effects of Overexposure: SEVERE IRRITATION, HEADACHE , DIZZINESS, NAUSEA, VOMITING, DROWSINESS, FATIGUE, BLURRED VISION, DIARRHEA, CHEST PAIN, COUGHING, COMA Medical Cond Aggravated by Exposure: ALCOHOLICS, DIABETES AND INDIVIDUALS WITH PRE-EXISTING DISEASES OF THE EYE, SKIN, RESPIRATORY TRACT, CNS, HEART, BLOOD MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES. First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES:IMMEDIATELY F LUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN: WASH WITH SOAP & WATER. INHALED: MOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NECESSARY. ORAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, WASH OUT MOUTH WITH WATER. CALL PHYSICIAN AT ONCE.

Flash Point Method:TCC Flash Point:56.0F,13.3C Lower Limits:6.20 Upper Limits:15.90 Extinguishing Media:USE DRY CHEMICAL, CARBON DIOXIDE, FOAM. USE WATER SPRAY TO COOL FIRE-EXPOS ED CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED.

Unusual Fire/Explosion Hazard: VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINA TE SOURCES

OF IGNITION. VENTILATE AREA. CONTAIN AND PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH, VERMICULITE. GROUND ALL HANDLING EQUIPMENTS. PREVE NT LIQUID FROM ENTERING SEWERS OR WATERWAYS.

Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE IN COOL, DRY, VENTILATED AREA, AWAY FROM FLAMES, SPARKS & INCOMPATIBLES. CONTAINERS SHOULD BE GROUNDED WHEN CONTENTS ARE BE

ING TRANSFERRED.

Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT WELD, SOLDER OR DRILL SUCH CONTAINERS. THEY MAY EXPLODE AND CAUSE INJURY/DEATH. KEEP OUT OF REACH OF CHILDREN. DO NOT INGEST. DO NOT GET IN EYES OR ON SKIN. DO NOT BREATHE VAPOR

Respiratory Protection: IF TLV IS EXCEEDED OR FOR SYMPTOMS OF OVER EXPOSURE, WEAR NIOSH-APPROVED AIR-SUPPLIED RESPIRATOR. IN EMERGENCY

, WEAR A NIOSH-APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS. WORK UNDER T HE HOOD.

Ventilation: MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NEOPRENE, BUTYL

Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:WEAR PROTECTIVE CLOTHING IN CASE OF REPEATED OR PROLONGED CONTACT. PROVIDE EYE WASH & SAFETY SHOWER.

Work Hygienic Practices: OBSERVE GOOD INDUSTRIAL HYGIEN

E PRACTICES AND RECOMMENDED PROCEDURES. WASH AFTER HANDLING AND BEFORE EATING OR DRINKING. Supplemental Safety and Health

HCC:F5 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:182F,84C Melt/Freeze Pt:M.P/F.P Text:-32F,-36C Vapor Pres:67 @ 68F Vapor Density:3.42 Spec Gravity:1.256 Evaporation Rate & amp; Reference:6.46 (N-BUTYL ACETATE=1) Solubility in Water:0.81% Appearance and Odor:COLORLESS LIQUID - CHLOROFORM L IKE ODOR Percent Volatiles by Volume:>99

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS, ALKALIES, ALUMINUM, NITROGEN TETROXIDE, AMINES
Stability Condition to Avoid:HEAT, SPARKS, FLAMES, OTHER IGNITION
SOURCES
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
OXIDES OF NITROGEN, OTHER UNKNOWN COMPOUNDS, TRACE AMOUNTS OF
HYDROGEN CYANIDE

======= Disposal Considerations ==

\_\_\_\_\_

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. RECOMMENDED PROCEDURE IS BY INCINERATION. EPA HAZARDOUS WASTE NUMBER: U077, D001, D028

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.