View NSN Online: https://aerobasegroup.com/nsn/9150-01-178-1221

SHELL OIL COMPANY -- ALVANIA EP GREASE 00,A 12377-1 -- 9150-01-178-1221

Product ID: ALVANIA EP GREASE 00, A 12377-1 MSDS Date:08/04/1994 FSC:9150 NIIN:01-178-1221 MSDS Number: CGLVG === Responsible Party === Company Name: SHELL OIL COMPANY Address: HEALTH, SAFETY AND ENVIRONMENT Box:4320 **City:HOUSTON** State:TX ZIP:77210 Country:US Info Phone Num:713-241-4819/4141/225 2 FAX -6511 Emergency Phone Num:713-473-9461/800-424-9300(CHEMTREC) CAGE:54527 === Contractor Identification === Company Name: COMPTECH CORP Address:15944 DERWOOD RD Box:City:ROCKVILLE State:MD ZIP:20855 Country:US Phone:800-284-5279; 301-519-3401 CAGE:0BR38 **Company Name: COOPER POWER TOOLS** Address:670 INDUSTRIAL DRIVE Box:1410 City:COLUMBIA State:SC ZIP:29071-1410 Country:US Phone:803-359-1200 CAGE:24047 Company Name: SHELL OIL COMPANY Address:Box:2463 **City:HOUSTON** State:TX ZIP:77210 Country:US Ph

one:800-231-6950 CAGE:54527

Ingred Name:MINERAL OIL, HYDROTREATED (MILD), HEAVY NAPHTHENIC DISTILLATE, PETROLEUM CAS:64742-52-5 RTECS #:PY8035000 Fraction by Wt: 80 - 82% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:SOLVENT REFINED HYDROTREATED RESIDUAL OIL CAS:64742-57-0 Fraction by Wt: 5 - 8% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:SULFURIZED FATTY MATERIAL CAS:61790-49-6 Fraction by Wt: 4% Other REC Limits:NONE RECOMMENDED

Ingred Name:LITHIUM 12-HYDROXYSTEARATE CAS:7620-77-1 Fraction by Wt: 2 - 3% Other REC Limits:NONE RECOMMENDED

Ingred Name:ZINC NAPHTHANATE CAS:12001-85-3 RTECS #:QK9275000 Fraction by Wt: 1 - 2% Other REC Limits:NONE RECOMMENDED

Ingred Name:OTHER ADDITIVES Fraction by Wt: 5000 MG/KG(64742-52-5) Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carci nogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYE, SKIN. ACUTE- MILDLY **IRRITATING TO EYES. PROLONGED/REPEATED SKIN CONTACT CAUSES** DERMATITIS, FOLLICULITIS/OIL ACNE. INJECTION UNDER SKIN CAUSES LOCAL NECROSIS. INHALATION OF VAPORS (G ENERATED AT HIGH TEMPERATURES ONLY) MAYCAUSE IRRITATION. SLIGHTLY TOXIC IF INGESTED. CHRONIC- DERMATITIS. Explanation of Carcinogenicity:NONE Effects of Overexposure: IRRITATION, NAUSEA, VOMITING, TISSUE DAMAGE А FEW HOURS AFTER HIGH PRESSURE INJECTION Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT. First Aid:CALL A DOCTOR IF SYMPTOMS OCCUR. EYE:FLUSH WITH WATER. HOLD EYELIDS OPEN. SKIN: WIPE EXCESS OFF. WASH SKIN WITH SOAP & WATER OR A WATERLESS HAND CLEANER FOLLOWED BY SOAP & WATER. IF MATERIAL IS INJECTE D UNDER SKIN, GET MEDI CAL ATTENTION PROMPTLY. DO NOT WAIT FOR SYMPTOMS TO DEVELOP. INHALED: MOVE TO FRESH AIR. PROVIDE OXYGEN IF NEEDED. ORAL:DO NOT INDUCE VOMITING. GET MEDICAL ADVICE. Flash Point Method: PMCC Flash Point:415F,213C Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL/CARBON DIOXIDE. DON'T USE DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED. Fire Fighting Procedures: DO NOT ENTER ANY ENCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard: CONTAINER MAY RUPTURE. COOL CONTAINERS WITH WATER SPRAY.

Spill Release Procedures:SCOOP UP EXCESS GREASE, WIPE UP WITH RAGS, PICK-UP RESIDUE WITH NON-FLAMMABLE ABSORBENT MATERIAL SUCH AS DIATOMACEOUS EARTH, SAND OR VERMICULITE. SWEEP UP AND TRANSFER TO A CONTAINER FOR PROPER DISP OS AL. CLEAN AREA WITH APPROPRIATE CLEANER. Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE IN A DRY PLACE AWAY FROM OPEN FLAMES AND STRONG OXIDIZING AGENTS. KEEP CONTAINER CLOSED.

Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE. ALL PRECAUTIONS SHOULD BE OBSERVED. WASH THOROUGHLY AFTER HANDLING. KEEP OUT OF REACH OF CHILDREN. AVOID REPEATED SKIN CONTACT. DO NOT GET IN EYES. LAUND

ER CONTAMINA TED CLOTHING BEFORE REUSE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE SHOULD BE NEEDED. Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S). Protective Gloves:NITRILE IF FREQUENT CONTACT EXPECTED Eye Protection:SAFETY GOGGLES/GLASSES RECOMMENDED Other Protective Equipment:EYE BATH, WASHING FACILITIES Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND REC

OMMENDED PROCEDURES. WASH BEFORE EATING OR DRINKING.

Supplemental Safety and Health

PREVIOUS NAME: SHELL ALVANIA EP LF GREASE R00

HCC:V6 NRC/State Lic Num:NOT RELEVANT Melt/Freeze Pt:M.P/F.P Text:401F,205C Solubility in Water:INSOLUBLE Appearance and Odor:BROWN SMOOTH GREASE - SLIGHT HYDROCARBON ODOR

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZI

NG AGENTS Stability Condition to Avoid:EXTREME HEAT, OPEN FLAMES Hazardous Decomposition Products:A COMPLEX MIXTURE OF AIRBORNE SOLID, LIQUID, PARTICULATES & GASES WILL EVOVLE. CARBON MONOXIDE & OTHER COMPD. MAY FORM.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL STATE AND FEDERAL LAWS. REUSING OR RECYCLING IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies): This i

nformation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.