

TEXACO LUBRICANTS COMPANY -- CAPELLA WF 68,01582 -- 9150-01-434-8780

=====
Product Identification
=====

Product ID:CAPELLA WF 68,01582

MSDS Date:12/19/1996

FSC:9150

NIIN:01-434-8780

MSDS Number: CGMNJ

=== Responsible Party ===

Company Name:TEXACO LUBRICANTS COMPANY

Box:4427

City:HOUSTON

State:TX

ZIP:77210-4427

Country:US

Info Phone Num:800-782-7852/914-838-7204 (#4;MSDS)

Emergency Phone Num:914-8

31-3400/800-424-9300(CHEMTREC)

CAGE:OTTJ3

=== Contractor Identification ===

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

Company Name:TEXACO LUBRICANTS

Address:4164 E INNSLAKE DR

Box:4427

City:GLEN ALLEN

State:VA

ZIP:23060

Country:US

Phone:804-527-4311

CAGE:OTTJ3

Company Name:TEXACO REFINING AND MARKETING INC

Address:1111 RUSK ST

Box:City:HOUSTON

State:TX

ZIP:77002-3310

Country:US

Phone:713-650-5206

CAGE:2R503

=====
Composition/Information on Ingredients
=====

Ingred Name:DISTILLATES, ACID-TREATED HEAVY NAPHTHENIC

CAS:64742-18-3

RTECS #:PY8032000

Fraction by Wt: 80 - 90%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:LIGHT NAPHTHENIC HYDROTREATED PETROLEUM DISTILLATE/MINERAL
OIL

CAS:64742-53-6

RTECS #:PY8036000

Fraction by Wt: 10 - 20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

=====

==== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS >5000 MG/KG.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, REPIRATORY &
GI TRACTS. ACUTE- EYE:DIRECT CONTACT IRRITATES SLIGHTLY.

SKIN:PROLONGED/REPEATED CONTACT MAY CAUSE DEFATTING.

INHALE:MIST/VAPOR IRRITATES RESPIRATORY TRACT & MAY CAUSE CNS
EFFECTS. ORAL:IF MORE THAN S

EVERAL MOUTHFULS ARE SWALLOWED, NAUSEA,
DIARRHEA MAY OCCUR. CHRONIC- NONE.

Explanation of Carcinogenicity:NONE.

Effects of Overexposure:IRRITATION, REDNESS, NAUSEA, VOMITING,
DIARRHEA, DISCOMFORT, COUGHING, HEADACHE, DIZZINESS, WEAKNESS

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING SKIN
DISORDERS MAY BE MORE SUCCEPTIBLE TO THE EFFECTS FROM EXPOSURE TO
THIS PRODUCT.

=====
First Aid Measures
=====

First Aid:GET MEDICAL HEL

P IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH AIR. EYES:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WIPE OFF EXCESS & WASH SKIN WITH SOAP & WATER. ORAL:IF MORE THAN SEVERAL MOUTHFULS ARE SWALLOWED, DRINK 2 GLASSES OF WATER. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:355F,179C
Extinguishing Media:WATER FOG/SPRAY, CARBON DIOXIDE, FOAM/DRY CHEMICAL. DIRECTLY SPRAYING WATER/FOAM ONTO BURNING OIL MAY CAUSE FROTHING.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. PROVIDE ADEQUATE VENTILATION. REMOVE SPILL WITH INERT ABORBENT SUCH AS SAND, CLAY, EARTH. TRANSFER TO PROPER CONTAINERS FOR DISPOSAL. PREVENT RUN-OFF TO ENTER SEWERS OR WATE RWAYS
. REPORT SPILLS AS REQUIRED TO AUTHORITIES.
Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM STRONG OXIDIZING AGENTS. KEEP CONTAINERS TIGHTLY CLOSED. KEEP OUT OF REACH OF CHILDREN. AVOID WATER CONTAMINATION.
Other Precautions:DO NOT GET IN EYES. MINIMIZE SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES INCLUDING SHOES THAT CANNOT BE DECONTAMINATED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED. IF WORKING IN CONFINED AREAS, IF EXCESSIVE MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS, WEAR NIOSH-APPROVED ORGANIC VAPOR AND MI ST RESPIRATOR (REFER TO 29 CFR 1910.134)
Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW AP

PLICABLE STANDARD(S).

Protective Gloves:WASH AT MEALTIME AND END OF SHIFT.

Eye Protection:CHEMICAL GOGGLES RECOMMENDED

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

NRC/S

tate Lic Num:NOT RELEVANT

Spec Gravity:0.885

Viscosity:65 CST @ 104F

Appearance and Odor:CLEAR, YELLOW LIQUID - BLAND ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:SMOKE, CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES, KETONES MAY BE FORMED.

===== Disposal Considerations =====

Waste Disposal Methods:DI

SPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. THIS PRODUCT HAS BEEN EVALUATED FOR RCRA CHARACTERISTICS AND DOES NOT MEET THE CRITERIA OF A HAZARDOUS WASTE IF DISCARDED IN ITS PUR CHASED FORM.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.