

TEXACO LUBRICANTS CO,DIV TEXACO REFINING & MARKET -- 01537 AIRCRAFT HYDRAULIC OIL 15  
-- 9150-00-223-4134

===== Product Identification =====

Product ID:01537 AIRCRAFT HYDRAULIC OIL 15

MSDS Date:12/19/1996

FSC:9150

NIIN:00-223-4134

MSDS Number: CGMTN

=== Responsible Party ===

Company Name:TEXACO LUBRICANTS CO,DIV TEXACO REFINING & MARKET

Box:4427

City:HOUSTON

State:TX

ZIP:77210-4427

Country:US

Info

Phone Num:800-782-7052/914-838-7204

Emergency Phone Num:914-831-3400/ CHEMTREC 800-424-9300

Preparer's Name:MANAGER, PRODUCT SAFETY

CAGE:OTTJ3

=== Contractor Identification ===

Company Name:TEXACO LUBRICANTS

Address:4164 E INNSLAKE DR

Box:4427

City:GLEN ALLEN

State:VA

ZIP:23060

Country:US

Phone:804-527-4311

CAGE:OTTJ3

Company Name:TEXACO REFINING AND MARKETING INC

Address:1111 RUSK ST

Box:City:HOUSTON

State:TX

ZIP:77002-3310

Country:US

Phone:713-650-5206

CAGE:2R503

===== Composition/I

Information on Ingredients =====

Ingred Name:HYDROTREATED MIDDLE PETROLEUM DISTILLATE;(SOLVENT REFINED  
HYDROTREATED MIDDLE DISTILLATE)

CAS:64742-46-7

RTECS #:JN9379645

Fraction by Wt: 95-100%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50(RAT):>5G/KG,PRACTICALLY NONTOX

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute a

nd Chronic:EYE:MINIMAL IRRIT,EXPERIENCED AS TEMP

DISCOMFORT.SKIN:PROL/WIDESPREAD CONTACT RESULT IN ABSORPTION OF POT  
HARMFUL AMTS OF MATL.PROLONG CONTACT W/WET

CLOTH-DEFATTING,IRRIT.INHAL:VAP/MIST IN EXCESS CONCE N IRRIT

NOSE/THROAT.PROL/REPEAT OVEREXPO-ABSORPTION OF HARMFUL

AMTS.INGEST:ABD DISCOMFORT,NAU,ASPIRATION HAZ (SIGN/SYM)

Explanation of Carcinogenicity:PER MSDS:MIDDLE DISTILLATED HAVE CAUSE

SKIN CANCER IN LAB ANIMALS APPLIED REPEATED/LEFT IN PLACE BETWEEN  
APPL

ICATIONS.

Effects of Overexposure:HEALTH HAZ:RESULTING IN LUNG DMG.INTERFERE W/N

&/OR MUSCULAR FUNCTIONS BY INHIBITION OF ESTERASE.DISFIGUREMENT,

FUNCTION LOSS IF INJECTED. EYE IRRIT-TEMP DISCOMFORT.SKIN

DEFAT/IRRIT,LOC REDNESS W/POSS IBLE MILD DISCOMFORT.IRRIT

NOSE/THROAT,HEAD,NAU,DROWS.ABD DISCOMFORT,NAU,DIARR,ASPIRATION INTO

LUNGS RESULT IN LUNG DMG.

Medical Cond Aggravated by Exposure:REP OVEREXPO MAY AGGRAVATE/ENHANCE

EXISTING CNS DYSFUNCTION PROD BY DISORDERS KNOWN

TO CAUSE CNS

EFFECTS/DMG(DIABETES, ALCOHOL/DRUG ABUSE,PARKINSON'S

DISEASE)DEFATTING PROPERT AGGRAVATE EXISTING DERM.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/LOTS OF H2O FOR SEVERAL MINS. IRRIT PERSISTS GET

MED ATTN.SKIN:WASH W/LOTS OF SOAP/WATER TIL ALL TRACES OF MATL

REMOVED.REMOVE CONTAMIN CLOTH.IRRIT PERSISTS/CONTACT PROLONG GET

MED ATTN.IN GEST:GET IMMED MED ATTN.ONLY INDUCE VOMIT AS DIRECTED

BY DR. NEVER GIVE ANYTH

ING BY MOUTH IF

UNCONSC/CONVULSING.INHAL:IRRIT/HEAD/NAU/ DROWS OCCURS MOVE TO FRESH AIR.BREATH DIFF GET MED ATTN.(OTHER PRE

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>200F,>93C

Lower Limits:N/D

Upper Limits:N/D

Extinguishing Media:WATERSPRAY, DRY CHEM, FOAM, CO2.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND POSITIVE PRESSURE BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA.AVOID BREATH VAP.USE SCBA/SUPPLIED AIR FOR LG SPILLS/CONFINED AREAS.CONTAIN IF POSSIBLE.WIPE UP/ ABSORB ON SUITABLE MATL.SHOVEL UP.PREVENT ENTRY INTO SEWERS/WATERWAYS.AVOID CONTACT W/S KIN/EYE/CLOTHING.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FRM HEAT/OPN FLAME.TRANSP/HNDLG

/ STORE IAW OSHA REG 1910.106/DOT

REGS.READ/UNDERSTAND MSDS BEF HNDLG/DISPO PROD.

Other Precautions:DR:HIGH PRESSURE INJECTION OF MATL INTO SKIN CAN CAUSE SEVERE INJURY IF NOT TREATED.USE X-RAY.ASPIRATION OF PROD DURING INDUCED EMESIS CAN RESULT IN LUNG INJURY.USE METHOD LEAST LIKELY TO CAUSE ASPIRATION.PROD HAS ARYLPHOSPHATE-(SUPPLEMEM)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIRBORNE CONCEN SHOULD BE KEPT LOWEST LEVELS POSSIBLE

IF VAP/MIST/DUST GENERATED USE NIOSH/MSHA APPROVED RESP AS APPROPRIATE.SUPPLIED AIR RESP PROT SHOULD BE USED FOR CLEAN LG SPILLS/UPON ENTRY INTO TK S/VESS/CONF SPACES.

Ventilation:ADEQUATE TO MEET COMPONENT OCCUPATIONAL EXPO LIMITS.

Protective Gloves:RESISTANT TO CHEM & PETRO DISTILLATES.

Eye Protection:CHEM-TYP GOGG,FACESHIELDS.

Other Protective Equipment:PROT CLOTH:UNIFORMS,COVERALLS,LAB COATS,BOOTS RESISTANT TO CHEM/PETRO DISTILLATES.

Work Hygienic Practices:CLEAN (LAUNDRAY

MORE EFFECTIVE-INFORM LAUNDRY  
OF CONTAMIN)CONTAMIN CLOTH BEF REUSE;DESTROY NON-RESIST FOOTWEAR.  
Supplemental Safety and Health  
NONE

===== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:>400F,>204C  
Spec Gravity:0.88  
Appearance and Odor:RED LIQUID WITH A PETROLEUM OIL ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
REACTS VIOLENTLY W/STRONG OXIDIZERS.  
Stability Condition to Avo  
id:NONE SPECIFIED BY MANUFACTURER.  
Hazardous Decomposition Products:TOX LEVELS CO,CO2,IRRIT ALDEHYDES &  
KETONES & COMBUSTION PRODS/CMPDS OF PHOSPHORUS.

===== Disposal Considerations =====

Waste Disposal Methods:PROD DOES NOT MEET CRITERIA OF HAZ WASTE IF  
DISCARDED IN PURCHASED FORM.PER RCRA USER RESPONSABILITY TO DERMINE  
@DISPO TIME WHETHER PROD MEETS RCRA CRITERIAL FOR HAZ WASTE.

Disclaimer (provided with this information by the compiling agencies  
):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.