View NSN Online: https://aerobasegroup.com/nsn/9150-00-868-0134

FISKE BROTHERS REFINING CO -- LUBRICATE 105 MOTOR ASSEMBLY GREASE,765-2651 - 9150-00-868-0134

Product ID:LUBRICATE 105 MOTOR ASSEMBLY GREASE,765-2651 MSDS Date:11/16/1992 FSC:9150 NIIN:00-868-0134 MSDS Number: CGMWM === Responsible Party === Company Name: FISKE BROTHERS REFINING CO Address:1500 OAKDALE AVE City:TOLEDO State:OH ZIP:43605 Country:US Info Phone Num :419-691-2491 / FAX 419-693-3806 Emergency Phone Num:419-691-2491/800-424-9300(CHEMTREC) CAGE:9N579 === Contractor Identification === **Company Name: BALKAMP INC** Address:2601 S HOLT ROAD Box:City:INDIANAPOLIS State:IN ZIP:46241 Country:US Phone:317-244-7241 CAGE:70842 Company Name: FISKE BROTHERS REFINING CO Address:1500 OAKDALE AVE Box:City:TOLEDO State:OH ZIP:43605 Country:US Phone:419-691-2491 CAGE:9N579 Company Name:NAPA Box:UNKNOW CAGE:0NBN5

======= Composition/Information on Ingredient

S ==============

Ingred Name:ZINC OXIDE (SARA 313) (CERCLA) CAS:1314-13-2 RTECS #:ZH4810000 Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:MINERAL OIL,HYDROTREATED (SEVERE), HEAVY NAPHTHENIC DISTILLATE CAS:64742-52-5 RTECS #:PY8035001 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:CALCIUM THICKENER CAS:68309-87-5 Other REC Limits:NONE RECOMMENDED

====== Hazards

Identification ======================

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3.
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY
TRACT. ACUTE- MAY CAUSE EYE IRRITATION. PROLONGED/REPEATED SKIN
CONTACT CAUSES IRRITATION. INJECTION UNDER SKIN CAUSES LOCAL
NECROSIS. INHALATION OF VAPORS/OIL MIS T MAY CAUSE IRRITATION. THIS
PRODUCT HAS A LOW ORDER OF AC
UTE ORAL TOXICITY, BUT ASPIRATION
HAZARD. CHRONIC- UNKNOWN.
Explanation of Carcinogenicity:NONE.
Effects of Overexposure:IRRITATION, REDNESS, SWELLING, TISSUE DAMAGE, NAUSEA, VOMITING

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH AIR. EYES:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WIPE OFF EXCESS & WASH SKIN WITH MILD SOAP & WATER OR WATERLESS CLEANER. IF INJECTED UND ER SKIN, REGARDLESS OF ITS SIZE, CONTACT A PHYSICIAN IMMEDIATELY. DELAY MAY CAUSE LOSS OF AFFECTED PART OF BODY. ORAL:DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.

Flash Point Method:COC Flash Point:360F,182C Lower Limits:0.9% Upper Limits:7.0% Extinguishing Media:WATER FOG/SPRAY, FOAM, DRY CHEMICAL/CARBON DIOXIDE. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY. Fire Fighting Procedures:DO NOT ENTER ANY E NCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:SCOOP UP EXCESS GREASE. PICK-UP RESIDUE WITH NON-FLAMMABLE ABSORBENT MATERIAL SUCH AS DIATOMACEOUS EARTH, SAND OR VERMICULITE. SWEEP UP AND TRANSFER TO A CONTAINER FOR PROPER DISPOSAL. CLEAN AREA WITH MILD DETERGENT. Neutralizing Age nt:NOT RELEVANT

Handling and Storage Precautions:STORE IN COOL, DRY, VENTILATED PLACE AWAY FROM STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.
Other Precautions:DO NOT GET IN EYES. MINIMIZE SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES INCLUDING SHOES THAT CANNOT BE DECONTAMINATED.

Respiratory Protection:NONE SHOULD BE NEEDED. Ventilation:ADEQUATE Protective Gloves:NITRILES Eye Protection:CHEMICAL GOGGLES/SAFETY GLASSES Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED. Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR. Suppl emental Safety and Health

HCC:V6 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:>550F,>288C Vapor Pres:5 Spec Gravity:0.89 - 0.93 Evaporation Rate & amp; Reference: