

COURTAULDS AEROSPACE INC -- 159211 POLYURETHANE POLYMER PR-1592 AMBER,BASE
COMPOUND -- 5970-01-222-5575

===== Product Identification =====

Product ID:159211 POLYURETHANE POLYMER PR-1592 AMBER,BASE COMPOUND

MSDS Date:12/05/1996

FSC:5970

NIIN:01-222-5575

MSDS Number: CGMYB

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE INC

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-549-7586

Emergency Phone Num:818-549-7586

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

===== Composition/Information on Ingredients =====

Ingred Name:POLYURETHANE POLYMER (CONTAINS 1/2% TOLUENE DIISOCYANATE)

CAS:65636-36-4

Fraction by Wt: 100%

Other REC Limit

s:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:TOLUENE

DIISOCYANATE-CANC.EYE:ISOCYANATES ARE VERY IRRIT.LEGAL WORKPLACE

EXPO LIMITS MUCH LOWER THAN LEVELS WHICH TYPICALLY CAUSE IRRIT.SO

EYE IRRIT STRONG INDICATION THAT ONE IS BEING EXPO.SKIN:LOC I

RRIT,DISCOLORATION.MAY CAUSE ALLERGIC RASH IN SENS
INDIVIDUALS.INHAL:IRRIT NOSE/THROAT/LUNGS/EYES.MAY PRODUCE(SUPPLEM)

Explanation of Carcinogenicity:PER MSDS:CONTAINS 1/2% TOLUENE
DIISOCYANATE-IARC(HUMAN SUFFICIENT EVIDENCE),NTP(HUMAN
SUSPECT),STATE OF CALIFORNIA.

Effects of Overexposure:VERY EYE IRRIT,LOCAL SKIN
IRRIT,DISCOLORATION,ALLERGIC RASH,IRRIT
NOSE/THROAT/LUNGS/EYES,ASTHMA-LIKE SYMPTOMS,IRRIT/CORRO
MOUTH/STOMACH TISSUE/DIGESTIVE TRACT.

Medical Cond Aggravated

by Exposure:INDIVIDUALS SUFFERING FROM ASTHMA
OR OTHER CHRONIC RESPIRATORY CONDITIONS MAY EXHIBIT HEIGHTENED
SENSITIVITY TO ISOCYANATES.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH W/LUKE WARM WATER FOR 15MINS.CONSULT
PHYSICIAN.SKIN:WASH W/SOAP/WATER.CONSULT PHYSICIAN.INHAL:REMOVE TO
FRESH AIR.OBTAIN MED ATTN.INGEST:GIVE MILK OR WATER TO
DRINK.CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====

==

Flash Point:>200F,>93C

Autoignition Temp:Autoignition Temp Text:NP

Extinguishing Media:CARBON DIOXIDE,DRY CHEMCIAL,FOAM,WATER FOG.

Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR.USE WATER TO COOL
HEAT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:HIGH TEMPERATURE MAY CAUSE PRESSURE
BUILDUP IN CLOSED CONTAINER.NOT FLAMMABLE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:COVER W/ABSORBANT MATL.ADD DECONTAMINATION
SOLN(5%CON
C AMMONIA,2%DETERGENT,93%WATER).ALLOW TO REACT FOR
10MINS.COLLECT IN CONTAINERS.ADD ADDN DECONTAM SOLN.KEEP LOOSELY
COVERED FOR 48HRS.CLEANUP RESID UE W/SUITABLE SOLVT.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID MOISTURE CONTAMINATION WHICH
WILL CAUSE CARBON DIOXIDE PRESUSRE.DONT RESEAL CONTAINERS IF
MOISTURE CONTAMINATION IS SUSPECTED.

Other Precautions:NONE KNOWN

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING/APPLYING IN ANY CIRCUMSTANCES
LIKELY TO PRODUCE AIRBORNE LEVEL OF HAZ INGREDIENTS IN EXCESS OF TLV
USE ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL.

Protective Gloves:SOLVENT RESISTANT GLOVES

Eye Protection:CHEM GOGG OR FULL FACE SHIELD.

Other Protective Equipment:NONE KNOWN

Work Hygienic Practices:NONE SPECIFIED BY M
ANUFACTURER.

Supplemental Safety and Health

HEALTH:ASTHMA-LIKE SYMPTOMS IN SENS INDIVIDUALS.INGEST:IRRIT,POSSIBLE
CORRO ACTION IN MOUTH/STOMACH TISSUE,DIGESTIVE TRACT.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:0

Melt/Freeze Pt:M.P/F.P Text:NP

Decomp Temp:Decomp Text:NP

Vapor Pres:NP

Vapor Density:>AIR

Spec Gravity:1.06

pH:NP

Viscosity:NP

Evaporation Rate & Reference:UNAVAI

Solubility in Water:NP

Appearance and Odor:CLEAR LIGHT YELL
OW LIQUID

Percent Volatiles by Volume:NONE

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, ALCOHOL, AMINES, STRONG BASES.

Stability Condition to Avoid:NOT KNOWN.

Hazardous Decomposition Products:OXIDES OF CARBON AND NITROGEN,
POSSIBLE TRACES OF HCN.

===== Disposal Considerations =====

Waste Disposal Methods:NOT HAZ WASTE ACCORDING TO EPA
REGULATIONS.CONSULT STATE RE

GS PRIOR TO DISPOSAL OF SPILLAGE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.