View NSN Online: https://aerobasegroup.com/nsn/5970-01-222-5575

COURTAULDS AEROSPACE INC -- 159211 POLYURETHANE POLYMER PR-1592 AMBER,BASE COMPOUND -- 5970-01-222-5575

============= Product Identification ==================

Product ID:159211 POLYURETHANE POLYMER PR-1592 AMBER, BASE COMPOUND

MSDS Date:12/05/1996

FSC:5970

NIIN:01-222-5575

MSDS Number: CGMYB === Responsible Party ===

Company Name: COURTAULDS AEROSPACE INC

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Info Phone Num:818-549-7586

Emergency Phone Num:818-549-7586

CAGE:83574

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

======= Composition/Information on Ingredients ========

Ingred Name: POLYURETHANE POLYMER (CONTAINS 1/2% TOLUENE DIISOCYANATE)

CAS:65636-36-4 Fraction by Wt: 100% Other REC Limit

s:NONE RECOMMENDED

============= Hazards Identification ========================

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:TOLUENE

DIISOCYANATE-CANC.EYE:ISOCYANATES ARE VERY IRRIT.LEGAL WORKPLACE EXPO LIMITS MUCH LOWER THAN LEVELS WHICH TYPICALLY CAUSE IRRIT.SO EYE IRRIT STRONG INDICATION THAT ONE IS BEING EXPO.SKIN:LOC I

RRIT, DISCOLORATION. MAY CAUSE ALLERGIC RASH IN SENS INDIVIDUALS.INHAL:IRRIT NOSE/THROAT/LUNGS/EYES.MAY PRODUCE(SUPPLEM) Explanation of Carcinogenicity: PER MSDS: CONTAINS 1/2% TOLUENE DIISOCYANATE-IARC(HUMAN SUFFICIENT EVIDENCE),NTP(HUMAN SUSPECT), STATE OF CALIFORNIA. Effects of Overexposure: VERY EYE IRRIT, LOCAL SKIN IRRIT, DISCOLORATION, ALLERGIC RASH, IRRIT NOSE/THROAT/LUNGS/EYES, ASTHMA-LIKE SYMPTOMS, IRRIT/CORRO MOUTH/STOMACH TISSUE/DIGESTIVE TRACT. Medical Cond Aggravated by Exposure: INDIVIDUALS SUFFERING FROM ASTHMA OR OTHER CHRONIC RESPIRATORY CONDITIONS MAY EXHIBIT HEIGHTENED SENSITIVITY TO ISOCYANATES. First Aid:EYE:FLUSH W/LUKE WARM WATER FOR 15MINS.CONSULT PHYSICIAN.SKIN:WASH W/SOAP/WATER.CONSULT PHYSICIAN.INHAL:REMOVE TO FRESH AIR.OBTAIN MED ATTN.INGEST:GIVE MILK OR WATER TO DRINK.CONSULT PHYSICIAN. Flash Point:>200F,>93C Autoignition Temp: Autoignition Temp Text: NP Extinguishing Media: CARBON DIOXIDE, DRY CHEMCIAL, FOAM, WATER FOG. Fire Fighting Procedures: USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard: HIGH TEMPERATURE MAY CAUSE PRESSURE BUILDUP IN CLOSED CONTAINER.NOT FLAMMABLE. ======== Accidental Release Measures ============ Spill Release Procedures: COVER W/ABSORBANT MATL. ADD DECONTAMINATION SOLN(5%CON C AMMONIA,2%DETERGENT,93%WATER).ALLOW TO REACT FOR 10MINS.COLLECT IN CONTAINERS.ADD ADDN DECONTAM SOLN.KEEP LOOSELY COVERED FOR 48HRS.CLEANUP RESID UE W/SUITABLE SOLVT. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. ========== Handling and Storage =============== Handling and Storage Precautions: AVOID MOISTURE CONTAMINATION WHICH

WILL CAUSE CARBON DIOXIDE PRESUSRE. DONT RESEAL CONTAINERS IF

MOISTURE CONTAMINATION IS SUSPECTED.

Other Precautions: NONE KNOWN

====== Exposure Controls/Personal Protection ========
Respiratory Protection:WHEN SPRAYING/APPLYING IN ANY CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVEL OF HAZ INGREDS IN EXCESS OF TLV USE ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR. Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL. Protective Gloves:SOLVENT RESISTANT GLOVES Eye Protection:CHEM GOGG OR FULL FACE SHIELD. Other Protective Equipment:NONE KNOWN Work Hygienic Practices:NONE SPECIFIED BY M ANUFACTURER. Supplemental Safety and Health HEALTH:ASTHMA-LIKE SYMPTOMS IN SENS INDIVIDUALS.INGEST:IRRIT,POSSIBLE CORRO ACTION IN MOUTH/STOMACH TISSUE,DIGESTIVE TRACT.
========= Physical/Chemical Properties ============
HCC:N1 Boiling Pt:B.P. Text:0 Melt/Freeze Pt:M.P/F.P Text:NP Decomp Temp:Decomp Text:NP Vapor Pres:NP Vapor Density:>AIR Spec Gravity:1.06 oH:NP Viscosity:NP Evaporation Rate & Deference:UNAVAI Solubility in Water:NP Appearance and Odor:CLEAR LIGHT YELL OW LIQUID Percent Volatiles by Volume:NONE Corrosion Rate:NP
======================================
Stability Indicator/Materials to Avoid:YES WATER, ALCOHOL, AMINES, STRONG BASES. Stability Condition to Avoid:NOT KNOWN. Hazardous Decomposition Products:OXIDES OF CARBON AND NITROGEN, POSSIBLE TRACES OF HCN. ===================================
Waste Disposal Methods:NOT HAZ WASTE ACCORDING TO EPA REGULATIONS.CONSULT STATE RE

GS PRIOR TO DISPOSAL OF SPILLAGE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.