View NSN Online: https://aerobasegroup.com/nsn/7930-00-205-2871

Product ID:WAX FLOOR, WATER EMULSION TYPE MSDS Date:08/21/1996 FSC:7930 NIIN:00-205-2871 MSDS Number: CGNDB === Responsible Party === Company Name: STARCO CHEMICAL DIVISION DIAMOND CHEMICAL CO. INC. Address: UNION AVE. & DUBOIS ST. City:EAST RUTHERFORD State:NJ ZIP:07073 Country:US Info Phone Num:201-935-4300 Emergency Phone Num:800-535-5053 (INFOTRAC) CAGE: JO451 === Contractor Identification === Company Name: DIAMOND CHEMICAL COMPANY, INC Address: UNION AVENUE AND DUBOIS STREET Box:City:EAST RUTHERFORD State:NJ ZIP:07073 Country:US Phone:201-935-4300 CAGE:3R223 Company Name:STARCO CHEMICAL Address: PAGE & SCHUYLER AVES Box:City:LYNDHURST State:NJ ZIP:07071

CAGE:JO451 ========= Composition/Information on Ingredients =

Country:US

Phone:201-935-4300

Ingred Name:NON AS PER 29 CFR 1910.1200 (NON-HAZARDOUS INGREDIENTS) Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRITATING. SKIN: IRRITATING. Medical Cond Aggravated by Exposure:OPEN WOUNDS AND SORES.

First Aid:EYE: FLUSH WITH WATER FOR 15 MINUTES, LIFTING LIDS APART. GET MEDICAL AID. SKIN: FLUSH WITH WATER. THEN WASH WITH SOAP AND WATER. INHAL: GET FRESH AIR. GET MEDICAL AID.

Flash Point:NONFLAMMABLE Autoignition Temp:Autoignition Temp Text:NA Lower Limits:NA Upper Limits:NA Extinguishing Media:MATERIAL IS NONFLAMMABLE. Fire Fighting Procedures:USE SCBA. Unusual Fire/Explosi on Hazard:TOXIC GASES MAY BE EMITTED UNDER FIRE CONDITIONS. SCBA MAY BE REQUIRED.

Spill Release Procedures: MOP UP OR VACUUM. WASH AREA WITH WATER. Neutralizing Agent: MILD ACID SUCH AS CITRIC.

Handling and Storage Precautions:STORE IN A WELL VENTILATED, CLEAN, DRY AREA AWAY FROM BLEACH AND STRONG ACIDS. KEEP COVERED WHEN NOT BEING USED. Other Prec autions: HAVE RUNNING WATER AVAILABLE IN CASE OF MISHAP.

====== Exposure Controls/Personal Protection ==========

Ventilation:LOCAL EXHAUST IS NORMALLY SATISFACTORY. IN DUSTY AREAS, MECHANICAL EXHAUST IS NEEDED. Protective Gloves:RUBBER OR PLASTIC Eye Protection:SPLASH PROOF GOGGLES Other Protective Equipment:RUBBER OR PLASTIC APRON. Supplemental Safety and Health NK

Boiling Pt:B.P. Text:ABOUT 100C Melt/Freeze Pt:M.P/F.P Text:NA Decomp Temp:Decomp Text:NA Vapor Pres:NA Vapor Density:NA Spec Gravity:0.99-1.01 pH: