

ABATEMENT TECHNOLOGIES, INC. -- SPRAY ADHESIVE 101 -- 8040-01-413-8291

=====
Product Identification
=====

Product ID:SPRAY ADHESIVE 101

MSDS Date:01/10/1996

FSC:8040

NIIN:01-413-8291

MSDS Number: CGNMY

=== Responsible Party ===

Company Name:ABATEMENT TECHNOLOGIES, INC.

Address:1705 BELLE MEADE COURT # 160

City:LAWRENCEVILLE

State:GA

ZIP:30243

Country:US

Info Phone Num:770-339-2600 FAX 770-339-26

01

Emergency Phone Num:770-339-2600

CAGE:49294

=== Contractor Identification ===

Company Name:ABATEMENT TECHNOLOGIES INC

Address:2220 NORTHMONT PKY SUITE 100

Box:City:DULUTH

State:GA

ZIP:30096

Country:US

Phone:404-339-2600

CAGE:49294

=====
Composition/Information on Ingredients
=====

Ingred Name:HEXANE

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 30-40%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ACETONE

(SARA 313) (CERCLA)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 10-20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:750 PPM

ACGIH TLV:750 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE/ISOBUTANE

CAS:68476-86-8

Fraction by Wt: 20-40%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:850 PPM

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazard

s Acute and Chronic:EYE: IRRIT, REDNESS. MAY GLUE EYELIDS

SHUT IF SPRAYED IN EYES. SKIN: REDNESS, IRRIT, DEFATTING,

DERMATITIS. INGEST: NASAL/RESPIRATORY IRRIT, DIZZY, WEAKNESS,

FATIGUE.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER, LIFTING LIDS. SKIN: WASH W/SOAP & WATER.

REMOVE CONTAM CLOTHES. INHAL: REMOVE TO FRESH AIR. OXYGEN IF

NEEDED. KEEP WARM/QUIET. IN ALL CASES, GET IMMED MED AID.

=====
===== Fire Fig

hting Measures =====

Flash Point:156F,69C

Extinguishing Media:CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:USE SCBA. KEEP CONTAINERS COOL W/WATER FOG TO PREVENT BURSTING.

Unusual Fire/Explosion Hazard:RUPTURED CONTAINERS MAY ROCKET OUT OF LOCALIZED AREA CAUSING POSSIBLE INJURY AND SPREAD FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITS. VENT AREA. USE NIOSH

APPROVED SCBA. SOAK UP W/OIL ABSORBE

NT MATERIAL AND PLACE IN A
CONTAINER FOR DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:DONT PUNCTURE OR INCINERATE. STORE IN
A WELL VENTED AREA. AVOID TEMPS >120F. KEEP AWAY FROM IGNIT
SOURCES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH APPROVED AIR SUPPLIED RESPIRATOR IF TLV IS
EXCEEDED.

Ventilation:LOCAL EXHAUST OR MECHANICAL IS SUFFICIENT TO MAINTAIN BELOW
TLV.

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:SUITABLE TO PROTECT BEAR SKIN.

Supplemental Safety and Health

NK

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:133F,56C

Vapor Pres:30-45

Vapor Density:>1 AIR = 1

Spec Gravity:0.70 WATER = 1

Evaporation Rate & Reference: