View NSN Online: https://aerobasegroup.com/nsn/1377-01-198-7481

OEA AEROSPACE INC. -- 51281-727 DTA TYPE SET -- 1377-01-198-7481

Product ID:51281-727 DTA TYPE SET MSDS Date:01/11/1996 FSC:1377 NIIN:01-198-7481 MSDS Number: CGWVL === Responsible Party === Company Name: OEA AEROSPACE INC. Address: HWY 12 AND ET RD Box:KK City:FAIRFIELD State:CA ZIP:94533-0659 Country:US Info Phone Num:707-422-1880 Emergency Phone Num:707-422-188 0 Preparer's Name:S SCHOOLFIELD CAGE:17610 === Contractor Identification === Company Name: OEA AEROSPACE INC Address:3530 BRANSCOMBE RD Box:KK City:FAIRFIELD State:CA ZIP:94533-0659 Country:US Phone:707-422-1880 CAGE:17610

Ingred Name:ALUMINUM \*96-4\* CAS:7429-90-5 RTECS #:BD0330000 OSHA PEL:15 MG/CUM ACGIH TLV:10 MG/CUM (DUST)

Ingred Name: HETEROCYCLIC AMINE

Ingred Name:LEAD AZIDE CAS:13424-46-9 RTECS #:OF8650000

Ingred Name

## :HEXANITROSTILBENE I

Ingred Name: IGNITION STRAND

Ingred Name: POTASSIUM PICRATE CAS: 573-83-1

Ingred Name:POTASSIUM PERCHLORATE CAS:7778-74-7 RTECS #:SC9700000

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:INHALATION: IRRITATION TO THE NOSE, THROAT & MUCOUS MEMBRANE. LEAD ALSO CAUSES CNS DISORDERS. SKIN: MAY RESULT IN LEAD POISONING/IRRITATION. ABSORPTION MAY RESULT IN

ALLERGIC REACTION & INHALATION HAZ ARDS. EYES: IRRITATION. INGESTION: IRRITATION. TOXIC EFFECTS ARE POSSIBLE. Effects of Overexposure:IRRITATION, NAUSEA, HEADACHE, WEAKNESS, LOSS OF APPETITE &/COLLAPSE

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH IMMEDIATELY W/SOAP & WATER. INHALATION: MOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

========

Fire Fighting Procedures:DON'T ATTEMPT TO EXTINGUISH. EVACUATE AREA. USE FULL-FACE SCBA TO CONTAIN RESULTING FIRE. Unusual Fire/Explosion Hazard:IF EXPOSED TO FIRE, UNIT MAY ACTUATE/EXPLODE.

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. MOISTEN W/FINE WATER SPRAY. USE FLAME RETARDENT CLOTHING, SAFETY GLASSES & NON-SPARKING TOOLS.

Handling and Storage Precautions: DON'T STORE AT TEMPS AT/ABOVE 350F. EXTREMELY SENSATIVE TO SHOCK & FRICTION. Other Precautions: ANTI-STATIC BAG SHALL BE USED FOR PACKAGING & STORAGE. Respiratory Protection: NIOSH APPROVED HEPA RESPIRATOR IF PEL/TLV IS EXCEEDED. Ventilation:LOCAL EXHAUST: REQUIRED FOR TEST FIRING. Protective Gloves: SPILL: LEATHER GLOVERS/EQUIVALENT Eye Protection: SAFETY GLASSES AS MINIMUM Oth er Protective Equipment: SPILL: EQUIVALENT FLAME RETARDENT CLOTHI NG & CONDUCTIVE SHOES. Supplemental Safety and Health Boiling Pt:B.P. Text:>300F Solubility in Water:LOW Stability Indicator/Materials to Avoid:YES ALKALIS, ACIDS, COPPER, BRONZE, CORROSIVES & OXIDIZERS Stability Condition to Avoid: MECHANICAL SHOCK, STATIC ELECTRICITY, HEAT, FLAME/ **SPARKS** Hazardous Decomposition Products:CO, CO2, HYDROGEN CHLORIDE, NITROGEN, NITROUS OXIDES, LEAD OXIDES/SULFIDE, POTASSIUM CARBONATES, PICRIC ACID. (SUPP) Waste Disposal Methods: DISPOSE AS HAZARDOUS & TOXIC WASTES IAW/FEDERAL, STATE & LOCAL REGULATIONS, UN 0367

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defens e. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.