

DOW CORNING CORPORATION -- 44 HIGH TEMP, BEARING GREASE, MEDIUM -- 9150-00-257-5358
===== Product Identification =====

Product ID:44 HIGH TEMP, BEARING GREASE, MEDIUM

MSDS Date:10/26/1993

FSC:9150

NIIN:00-257-5358

MSDS Number: CGWZY

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-600

0

Emergency Phone Num:517-496-5900/800-424-9300(CHEMTREC)

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

===== Composition/Information on Ingredients =====

Ingred Name:AMINOAZOTOLUENE

CAS:97-56-3

RTECS #:YU8800000

Fraction by Wt: 0.1%

Other REC Limits:NONE RECOMMENDED

Ingred Name:LITHIUM STEARATE

CAS:4485-12-5

RTECS #:WI4370

000

Fraction by Wt: 19%

Other REC Limits:NONE RECOMMENDED

Ingred Name:2,6-CIS-DIPHENYLHEXAMETHYLCYCLOTETRASILOXANE

CAS:33204-76-1

RTECS #:GZ4390000

Fraction by Wt: 300F.PROVIDE VENTI TO CNTRL VAP EXPO W/IN INHAL GIUDELIN
WHEN(SUP)

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO RESPIRATORY PROTECTION SHOULD BE NEEDED.

Ventilation:LOCAL EXHAU:NONE SHOULD BE NEEDED.GENERAL
VENTI:RECOMMENDED.

Protective Gloves:NO SPECIAL PROTECTION NEEDED

E
Eye Protection:SAFETY GLASSES AS MINIMUM

Other Protective Equipment:PRECAUT ARE FOR RT HNDLG.USE @ELEVATED
TEMP/AEROSOL/SPRAY APPLIC MAY REQUIRE ADDED PRECAUTIONS.

Work Hygienic Practices:WASHING @MEALTIME & END OF SHIFT IS
ADEQUATE.AVOID EYE CONTACT DURING SPILLS.

Supplemental Safety and Health

SPILL:OBSERVE ANY SAF PRECAUT APPLIC TO CLEANING MATL BEING USED.SCRAPE
UP/CONTAIN FOR SALVAGE/DISPO.OBSERVE ALL PPE RECOMMENDATIONS IN
MSDS.LOC/STATE/FED REPORT REQMTS MAY APPLY TO SPILLS

/RELEASE OF

MATL INTO ENVIR. OTH PREC:HNDLG @ELEV TEMPS.REVIEW OSHA BENZENE
REGS FOR DETAIL INFO ON SAFE HNDL REQMTS.

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:NA

Melt/Freeze Pt:M.P/F.P Text:N/DETERMINE

Decomp Temp:Decomp Text:NP

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:1.10

pH:NA

Viscosity:NA

Evaporation Rate & Reference:NP

Solubility in Water:NONE

Appearance and Odor:GREASE, SANDSTONE COLOR, SLIGHT ODOR

Percent Volatiles

by Volume:NA
Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING MATERIAL CAN CAUSE A REACTION.

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:SILICON DIOXIDE,NITROGEN OXIDES.CARBON
OXIDES & TRACES OF INCOMPLETELY BURNED CARBON COMPOUNDS.METAL
OXIDES.FORMALDEHYDE

===== Disposal Considerations =====

Waste Disposal Methods:COMPLETE INFORMATION NOT Y
ET AVAILABLE.CALL DOW
CORNING ENVIRO MGMT 517-496-6315 IF MORE INFO IS
DESIRED.CERCLA:NONE.SEC 313 TOXIC CHEM:C.I.SOLVENT YELLOW 3.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should
seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.