

CONVOY OIL CORP -- MOLY IN ISOPROPANOL DISPERSION -- 9150-00-424-3224

=====
Product Identification
=====

Product ID:MOLY IN ISOPROPANOL DISPERSION
MSDS Date:06/11/1995
FSC:9150
NIIN:00-424-3224
Kit Part:Y
MSDS Number: CGXBN
==== Responsible Party ====
Company Name:CONVOY OIL CORP
Address:1412 N FRONT STREET
City:PHILADELPHIA
State:PA
ZIP:19122-3902
Country:US
Info Phone Num:215-739-5281
Emergency P
hone Num:215-739-5281/800-424-9300(CHEMTREC)
Preparer's Name:STANLEY JAKUBOWSKI
CAGE:6A438

==== Contractor Identification ====
Company Name:CONVOY OIL CORP
Address:1410 N FRONT STREET
Box:29366
City:PHILADELPHIA
State:PA
ZIP:19125
Country:US
Phone:215-739-5281
CAGE:6A438

=====
Composition/Information on Ingredients
=====

Ingred Name:MOLYBDENUM DISULFIDE
CAS:1317-33-5
RTECS #:QA4697000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG MO/M3
ACGIH TLV:10 MG MO/M3

Ingred Name:ISOP

ROPYL ALCOHOL (SARA 313)

CAS:67-63-0

RTECS #:NT8050000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM/500STEL;9596

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL:LOW CONCEN MAY CAUSE MILD IRRIT
OF EYES/NOSE/THROAT.SKIN:PROLONGED CONTACT MAY CAUSE DRYI
NG &

CRACKING OF SKIN.SKIN ABSORPT:NON-TOXIC.EYE:CAUSES SLIGHT TO
MODERATE IRRIT W/POSSIBLE CORNEAL INJUR Y.INGEST:SLIGHTLY TOXIC.

Effects of Overexposure:ACUTE:POSSIBLE CORNEAL INJURY W/EYE
CONTACT.POSSIBLE DERM W/SKIN CONTACT.POSSIBLE HEADACHE & DROWSINESS
W/INHAL.INGEST MAY CAUSE DROWSINESS,NAUSEA,VOMITING, &
DIARRHEA.CHRONIC:PRE-EXISTING SKIN AND RE SPIRATORY DISORDERS MAY
BE AGGRAVATED BYEXPOSURE.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN AND RESPIRATORY
DISORDERS MAY BE AGGRAVATED BY EXPOSURE.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH IMMED W/LG QUANT OF H2O.GET MED ATTN.SKIN:REMOVE
CONTAM CLOTH.FLUSH SKIN W/H2O.INHAL:REMOVE TO FRESH AIR.BREATH
STOPS GIVE ART RESP.GET MED ATTN AS SOON AS POSSIBLE.INGEST:GIVE 2
GLASSES OF H2O,INDUCE VOMIT.IF SIGNIFICANT QUANT HAS BEEN
SWALLOWED.GET MED ATTN PROMPTLY.NOTES TO PHSYICIAN:THERES NO SPEC
ANTIDOTE.TREAT OF OVEREXPO SHOULD BE DIRE
CTED @CNTRL OF
SYMPT/CLINICAL CONDITION.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:63.0F,17.2C

Autoignition Temp:Autoignition Temp Text:NA

Lower Limits:2.0

Upper Limits:12.7 @200F

Extinguishing Media:USE WATER SPRAY,CARBON DIOXIDE,DRY
CHEMCIAL,ALCOHOL-TYPE,OR UNIVERSAL-TYPE FOAMS APPLIED BY MFGS
RECOMMENDED.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS &
PROTECTIVE CLOTHING.

Unusual Fire/Explosion

Hazard:VAP FORM FRM PROD&MAY TRAVEL/MOVE BY AIR
CURRENTS,IGN BY PILOT LIGHTS,OTHER
FLAMES,SMOKING,SPARK,HEATERS,STATIC DISCHARGES.

===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH & DONT TURN ON ANY IGN SOURCES TIL
AREA IS DETERMINED TO BE FREE FROM EXPLO OR FIRE HAZ.COLLECT LG
SPILLS FOR DISPOSAL.FLUSH SM SPILLS W/WATER.

Neutralizing Agent:NO AVAI INFO OTHER THAN THAT DESCRIBED ABOVE.

===== Handling and S
torage =====

Handling and Storage Precautions:EYE IRRITANT AND FLAMM LIQUID.

Other Precautions:KEEP AWAY FRM HEAT/SPARKS/FLAME.AVOID CONTACT
W/EYES.KEEP CNTNR CLSD.USE W/ADEQUATE VENTILATION.@VERY LOW CONCEN
IN WATER APPRX 10PPM ISOPROPANOL IS READILY BIODEGRADABLE IN
WASTEWATER TREAT PLANT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS IN HIGH
CONCENTRATIONS.NIOSH APPROVED.

Venti

lation:PROD SHOULD BE CONFINED W/IN CLSD EQPMT IN WHICH CASE
GEN(MECHANICAL)RM VENTI SHOULD BE SAT.SPEC/LOC VENTI NEEDED (SUPPL)

Protective Gloves:BUTYL TYPE RECOMMENDED

Eye Protection:MONOGOGGLES

Other Protective Equipment:EYE BATH & SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HNDLG.

Supplemental Safety and Health

VENTI:@POINTS WHERE VAP CAN BE EXPECTED TO ESCAPE TO WORKPLACE AIR.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. T

ext:180F,82C

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:NP

Vapor Pres:33

Vapor Density:2.07

Spec Gravity:NP

pH:NA

Viscosity:NP

Evaporation Rate & Reference:2.88, BUTYL ACETATE=1

Solubility in Water:90 MIN

Appearance and Odor:GREY LIQUID, ALCOHOL ODOR

Percent Volatiles by Volume:90

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONCENTRATED NITRIC & SULFURIC ACIDS,STRONG
OXIDIZERS,ALDEHYD

ES,HALOGENS,HALOGEN COMPOUNDS.

Stability Condition to Avoid:AVOID HEAT,SPARKS,FLAME.

Hazardous Decomposition Products:BURNING MAY PRODUCE CARBON MONOXIDE
&/OR CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN FURNACE WHERE PERMITTED UNDER
APPROPRIATE LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of th

e Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.