View NSN Online: https://aerobasegroup.com/nsn/9150-00-657-4959

## THIRD COAST PACKAGING INC -- DEXRON III/MERCON ATF 01854 -- 9150-00-657-4959

Product ID:DEXRON III/MERCON ATF 01854

MSDS Date:05/02/1996

FSC:9150

NIIN:00-657-4959

MSDS Number: CGXBT === Responsible Party ===

Company Name: THIRD COAST PACKAGING INC

Address:18410 W CLOVER LN

Box:367

City:FRIENDSWOOD

State:TX ZIP:77546 Country:US

Info Phone Num:800-782-7852

Emergenc

y Phone Num:800-782-7852/800-424-9300(CHEMTREC)

CAGE:0P418

=== Contractor Identification ===

Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX ZIP:77305 Country:US

Phone: 409-756-1065

CAGE:4N760

Company Name: THIRD COAST PACKAGING INC

Address:18410 W CLOVER LN

Box:367

City:FRIENDSWOOD

State:TX ZIP:77549 Country:US

Phone:281-482-9212;914-838-7204

CAGE:0P418

====== Composition/Information on Ingredients ========

Ingred Name:S

OLVENT REFINED LIGHT PARAFFINIC PETROLEUM DISTILLATES/PETROLEUM OIL

CAS:64741-89-5 RTECS #:PY8041500

Fraction by Wt: BALANCE

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED (MILD), HEAVY PARAFFINIC/PETROLEUM LUBE OIL

CAS:64742-65-0 RTECS #:PY8038500 Fraction by Wt: 35 - 50%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name: HY

DROTREATED LIGHT NAPHTHENIC PETROLEUM DISTILLATES/MINERAL

OIL

CAS:64742-53-6

RTECS #:PY8036000 Fraction by Wt: 1 - 3%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:METHACRYLIC ACID,COPOLYMER OF "BUTYL","LAURYL" AND "STEARYL" ESTERS WITH 3-DIMETHYL-AMINOPROPYLMETHACRYLAMIDE

CAS:50867-55-5 Fraction by Wt: 1 - 3%

Other REC Limits: NONE RECOMMENDED

Ingred Name: TOLUENE (SARA 313) (CERCLA)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt:

.01-.09%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2 ACGIH TLV:S, 50 PPM; 9596

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)

CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 0.00875%

Other REC Limits: NONE RECOMMENDED

**OSHA PEL:100 PPM** 

ACGIH TLV:100 PPM/150STEL;9596

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: ETHYL BENZENE (SARA 313)

CAS:100-41-4

RTECS #:DA0700000 Fraction by Wt: 0.00168% D

**OSHA PEL:100 PPM** 

ACGIH TLV:100 PPM/125STEL;9596

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:BENZENEAMINE,N-PHENYL-1,2,4-TRIMETHYLBENZENE

Other REC Limits: NONE RECOMMENDED

=========== Hazards Identification ==========================

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS >5,000 MG/KG. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY & GLTRACTS

. ACUTE- MAY CAUSE MINIMAL EYE IRRITATION.

PROLONGED/REPEATED SKIN CONTACT MAY CAUSE SEVER IRRITATION. INHALATION OF VAPOR (GENERATED AT HIGH TEMPERATUR ES)/MIST MAY CAUSE IRRITATION, DROWSINESS. IF >SEVERAL MOUTHFULS ARE SWALLOWED MAY CAUSE DISCOMFORT. CHRONIC- NONE.

**Explanation of Carcinogenicity:NONE** 

Effects of Overexposure:IRRITATION, NAUSEA, VOMITING, DIARRHEA, HEADACHE, DIZZINESS

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MO

RE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH AIR. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:IF MORE THAN SEVERAL MOUTHFULS OF THIS MA TERIAL ARE SWALLOWED, DRINK TWO GLASSESOF WATER (16 OZ). GET MEDICAL ATTENTION.

========== Fire Fighting Measures ===============

Flas

h Point Method:COC Flash Point:395F,202C


Extinguishing Media: WATER FOG, FOAM, DRY CHEMICAL/CARBON DIOXIDE. WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE

======== Accidental Release Measures ==========

Spill Release Procedures:PICK UP SPILL WITH INERT MATERIAL SUCH AS SAND, CLAY,



STRONG OXIDIZING AGENTS Stability Condition to Avoid: EXCESSIVE HEAT

## **ES AND KETONES**

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE OF IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATION IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.