

CIBA-GEIGY CORP FORMULATED SYSTEMS GROUP -- RP 1250 HARDNER, PART B --
8030-00-830-1821

=====
Product Identification
=====

Product ID:RP 1250 HARDNER, PART B
MSDS Date:11/07/1996
FSC:8030
NIIN:00-830-1821
Kit Part:Y
MSDS Number: CGXCB
=== Responsible Party ===
Company Name:CIBA-GEIGY CORP FORMULATED SYSTEMS GROUP
Address:4917 DAWN AVENUE
City:EAST LANSING
State:MI
ZIP:48823
Info Phone Num:(517) 3
51-5900
Emergency Phone Num:(517) 351-5900
Preparer's Name:MICHAEL L. MUNSELL
CAGE:02684
=== Contractor Identification ===
Company Name:CIBA SPECIALTY CHEMICALS CORPORATION
Address:4917 DAWN AVE
Box:City:EAST LANSING
State:MI
ZIP:48823-5691
Country:US
Phone:517-351-5900
CAGE:02684

=====
Composition/Information on Ingredients
=====

Ingred Name:ALUMINUM (SARA 313)
CAS:7429-90-5
RTECS #:BD0330000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 DUST
ACGIH TLV:10 MG/M3 DUST; 9

Ingred Name:BENTONITE

CAS:1302-78-9

RTECS #:CT9450000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (DUST)

ACGIH TLV:5 MG/M3 (DUST)

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9596

Ingred Name:PARA-TERTIARY BUTYLPHENYL GLYCIDYL ETHER (REACTIVE DILUENT)

CAS:3101-60-8

RTECS #:TX4250000

Other REC Limits:NONE RECOMMENDED

Ingred Name:BISPHENOL A-EPICHLOROHYDRIN COPOL
YMER

CAS:25068-38-6

RTECS #:SL6475000

Other REC Limits:NONE RECOMMENDED

Ingred Name:FIBERGLASS (FIBROUS GLASS)

CAS:65997-17-3

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 RESP DUST

ACGIH TLV:10 MG/M3 (250F,>121C)

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM

Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY
BE TOXIC.

===== Accidental Release Measures =====

Spill

Release Procedures:REMOVE SPILLAGE BY ABSORBING IN ABSORBENT MATERIAL.

Neutralizing Agent:NONE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:NUISANCE DUST MAY BE GENERATED WHEN SAWING OR SANDING CURED MATERIAL.

Other Precautions:CAUSES EYE AND SKIN IRRITATION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED ORGANIC VAPOR CARTRIDGE RESPIRATOR WHEN VAPOR/MIST EXPOSURE IS LIKELY.

Ventilation:GENERAL MECHANICAL AND LOCAL EXHAUST IN ACCORDANCE WITH ACGIH RECOMMENDATIONS.

Protective Gloves:WEAR IMPERMEABLE GLOVES.

Eye Protection:WEAR SPLASH PROOF CHEMICAL GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:REMOVE AND LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY AFTER USING.

Supplemental Safety and Health

THIS IS A KIT THAT CONTAINS 6 QUARTS RESIN AND 6 QUARTS HARDNER. CORROSIVE.

=====
===== Physical/Chemical Properties =====

HCC:N1

Vapor Pres:0.003

Spec Gravity:1.5-1.6

Solubility in Water:NIL

Appearance and Odor:LIGHT GRAY PASTE, ESSENTAILLY ODORLESS.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, ACIDS, BASES.

Stability Condition to Avoid:EXCESSIVE HEAT FOR PROLONGED PERIODS OF TIMES.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE.

=====
===== D

isposal Considerations =====

Waste Disposal Methods:CONSULT QUALIFIED LOCAL OR CORPORATE PERSONNEL FOR METHOD THAT WILL COMPLY WITH LOCAL, STATE AND FEDERAL HEALTH & ENVIRONMENTAL REGULATIONS. NOT A HAZARDOUS WASTE UNDER RCRA.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.