View NSN Online: https://aerobasegroup.com/nsn/6850-01-377-1809

EXXON CHEMICAL AMERICAS -- EXXSOL D 110 SOLVENT -- 6850-01-377-1809

Product ID: EXXSOL D 110 SOLVENT MSDS Date:05/23/1996 FSC:6850 NIIN:01-377-1809 MSDS Number: CGXGH === Responsible Party === Company Name: EXXON CHEMICAL AMERICAS Box:3272 **City:HOUSTON** State:TX ZIP:77001 Country:US Info Phone Num:281-870-6000/6884 (HEALTH) Emergency Phone Num:800-726-2015/800-424-9300(CHEMTREC) CAGE:72190 === Contractor Identification === Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT INC Address:2210 HACKBERRY LN Box:687 City:CONROE State:TX ZIP:77305 Country:US Phone:409-756-1065 CAGE:4N760 Company Name: EXXONMOBIL CHEMICAL CO, DIV OF EXXON MOBILCORP. Address:13501 KATY FWY Box:3272 City:HOUSTON State:TX ZIP:77253-3272 Country:US Phone:281-870-6000 / 800-726-2015 CAGE:72190

Ingred Name:NON-HAZARDO

US INGREDIENTS Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, RESPIRATORY & GI TRACTS. ACUTE- EYE CONTACT MAY CAUSE IRRITATION. PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION. INHALATION MAY CAUSE IRRITATION OF UPPER RESPIRATOR Y TRACT & CNS EFFECTS. LOW ORDER OF ORAL TOXICITY; BUT ASPIRATION HAZARD. CHRONIC- SKIN DERMATITIS. Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION, NAUSEA, VOMITING, ABDOMINAL DISCOMFORT, TEARING, COUGHING, DERMATITIS, DRYNESS OF SKIN, HEADACHE, DIZZINESS Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED CNS OR RESPIRATORY FUNCTION MAY

BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WASH WITH PLENTY OF SOAP & WATE R. ORAL:DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

\_\_\_\_\_

Flash Point Method:PMCC Flash Point:221F,105C Autoignition Temp:Autoignition Temp Text:412F Lower Limits:1.6 Upper Limits:10.2 Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, SAND, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL. Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusua I Fire/Explosion Hazard:CONTAINERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. REMOVE IGNITION SOURCES. RECOVER FREE PRODUCT. REMOVE SPILL WITH INERT ABORBENT SUCH AS SAND, CLAY, EARTH. TRANSFER TO PROPER CONTAINERS FOR DISPOSAL. WASH AREA TO REMOVE RE SIDUAL CONTAMINATION. Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE AWAY FROM OXIDIZING AGENTS. KEEP CONTAINER CLOSED.

Other Precautions: "EMPTY" CONTAINERS RETAIN RESIDUE. ALL PRECAUTIONS SHOULD BE OBSERVED. WASH THOROUGHLY AFTER HANDLING. KEEP OUT OF REACH OF CHILDREN. AVOID BREATHING MISTS/VAPORS. AVOID REPEATED SKIN CONTACT. DO NOT GET IN EYES. DO NOT INGEST.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE. IF

HIGH VAPOR OR MIST CONCENTRATIONS EXPECTED, USE NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR.

Ventilation:ADEQUATE

Protective Gloves:NITRILE IF FREQUENT CONTACT EXPECTED

Eye Protection: SAFETY GOGGLES IF SPLASHING ANTICIPATED

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices: OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH BEFORE EATING OR DRINKING.

Supplemen

tal Safety and Health

HCC:N1 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:480F - 514F Melt/Freeze Pt:M.P/F.P Text:3F,-16C Vapor Pres:6.30 Spec Gravity:0.81 Viscosity:3.5 CST@ 77F Evaporation Rate & amp; Reference: