

PRO-LINE PAINT CO -- F-150-EPOXY-POLYAMIDE PAINT, GREEN #24272 PRIMER --
8010-01-350-4742

===== Product Identification =====

Product ID:F-150-EPOXY-POLYAMIDE PAINT, GREEN #24272 PRIMER

MSDS Date:02/05/1996

FSC:8010

NIIN:01-350-4742

Kit Part:Y

MSDS Number: CGXSX

=== Responsible Party ===

Company Name:PRO-LINE PAINT CO

Address:2646 MAIN STREET

City:SAN DIEGO

State:CA

ZIP:92113-3613

Country:US

Info

Phone Num:619-231-2313 OR 232-8968

Emergency Phone Num:800-535-5053

Preparer's Name:E. SOETERIK

CAGE:9D157

=== Contractor Identification ===

Company Name:PRO-LINE PAINT CO

Address:2646 MAIN STREET

Box:City:SAN DIEGO

State:CA

ZIP:92113-3697

Country:US

Phone:619-231-2313; 619-232-8968

CAGE:9D157

===== Composition/Information on Ingredients =====

Ingred Name:HARDENER-AMIDO AMIDE

CAS:112-57-2

RTECS #:KH8585000

Fraction by Wt: .25-1.0%

Other REC Limits:NONE RECOMMENDED

Ingred Nam

e:RESIN HARDENER-POLYAMIDE
Other REC Limits:NONE RECOMMENDED

Ingred Name:RESIN SOLUTION (SARA 313) (CERCLA)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 10-14.0%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:RHEOLOGICAL ADDITIVE
Fraction by Wt: 0.1-1.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:MAGNESIUM SILICATE HYDRATE
CAS:1480-19-6
Fraction by Wt: 20-25%
Other REC Limits:NONE RECOMMENDED

Ingred Name:N-BUTYL ALCOHOL (SARA 313) (CERCLA)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 12-14.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 3-6.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:YELLOW IRON OXIDE
CAS:1317-61-9
Fraction by Wt: 1-3.0%
Other REC Limits:NONE RECOMMENDED

==== Hazards Identification =====

Routes of En

try: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: REDNESS. SKIN: BURNING SENSATION,
RASH, INFLAMMATION, PINKISH. INHAL: COUGHING, SHORTNESS OF BREATH,
DIZZY, HEADACHE, CONVULSIONS. INGEST: DIARRHEA, STOMACH CRAMPS.
Medical Cond Aggravated by Exposure:ASTHMA, EMPHYSEMA & OTHER
RESPIRATORY DISEASES.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH W/WATER. SK
IN: WASH W/WATER, THEN W/SOAP & WATER.
INHAL: REMOVE TO FRESH AIR. ARTIF RESP IF NEEDED. INGEST: CALL A
DR. IN ALL CASES, GET IMMED MED AID.

=====
Fire Fighting Measures
=====

Flash Point Method:SCC
Flash Point:101F,38C
Lower Limits:1.4
Upper Limits:11.2
Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM, DRY CHEMICAL.
Fire Fighting Procedures:BLANKET FLAME W/EXTINGUISHING MEDIA. USE
PROPER PROTECTION & EQUIPMENT INCLUDING SCBA.
Unusual Fire/Exp
losion Hazard:KEEP MATERIAL AWAY FROM IGNIT SOURCES.
EXPLOSIVE WHEN HEATED. STAY A SAFE DISTANCE FROM FIRE WHEN
EXTINGUISHING.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL IGNIT SOURCES. VENT AREA. PROTECT
CLEAN-UP MAN W/A540 3M CORP. NIOSH APPROVED RESPIRATOR, GOGGLES,
RUBBER GLOVES. (NOTE RESPIRATORY PROTECTION SECTION).

=====
Handling and Storage
=====

Handling and Storage Precaut
ions:PROTECT AGAINST PHYSICAL DAMAGE TO
CONTAINER & SPILLAGE. STORE IN A COOL, WELL VENTED AREA W/SPRINKLER
SYSTEM. KEEP FROM HEAT. POST NO SMOKING SIGNS.
Other Precautions:TRAIN EMPLOYEE ON ALL SPECIAL HANDLING PROCEDURES
BEFORE THEY WORK WITH THIS PRODUCT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE DUST/MIST RESPIRATOR (HIGH EFFICIENCY
CARTRIDGE ADVISED). IF SPRAYING/SANDING, USE ORGANIC VAPOR
CARTRIDGE RESP IF TLV FOR S

SOLVENT COMPONENTS EXCEEDED E.G. 8540 3M
CORP. RESPIRATOR NIOSH APPROVED, IN CONFINED AREAS, WEAR AIR-FED
HOOD.

Ventilation:USE LOCAL EXHAUST WHEN APPLYING THIS PAINT IN CONFINED
AREAS.

Protective Gloves:RUBBER

Eye Protection:GOGGLES W/SIDE SHIELDS

Other Protective Equipment:USE PROTECTIVE CLOTHES. PROVIDE EMERGENCY
SHOWERS & EYEWASH STATIONS.

Work Hygienic Practices:CHANGE CONTAM CLOTHES IMMED.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties

Boiling Pt:B.P. Text:244F,118C

Melt/Freeze Pt:M.P/F.P Text:128F,53C

Vapor Pres:4.4 @ 60F

Vapor Density:2.1 AIR =1

Spec Gravity:1.3

VOC Pounds/Gallon:340

Evaporation Rate & Reference:.43 (BUAC = 1)

Solubility in Water:POOR

Appearance and Odor:TYPICAL PAINT APPEARANCE W/STRONG SOLVENT ODOR,
TYPICAL OF BUTANOL.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WHEN A AND B ARE MIXED, KEEP AWAY FROM HEAT. HEAT
WILL CREATE A RAPID

CHEMICAL REACTION. EMITE HEAT.

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME. DONT ALLOW VAPOR
TO ACCUMULATE.

Hazardous Decomposition Products:COMBUSTIBLE FUMES MAY ACCUMULATE IN
CONFINED AREAS, AND SPARKS AND OPEN FLAMES MAY IGNITE IT.

===== Disposal Considerations =====

Waste Disposal Methods:USE ANY KIND OF ABSORBENT TO ABSORB SPILLED
MATERIAL. PUT IN METAL CONTAINER MARKED, DO NOT USE THIS MATERIAL.
DISPOSE OF

LEGALLY IN ACCORDANCE W/FEDERAL, STATE AND LOCAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.