View NSN Online: https://aerobasegroup.com/nsn/8010-01-421-2959

Product ID:WATERBORN POLYURETHANE, GREEN MSDS Date:06/30/1992 FSC:8010 NIIN:01-421-2959 MSDS Number: CGXVY === Responsible Party === Company Name: COURTAULDS Address:5430 SAN FERNANDO ROAD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Info Phone Num:818-240-2060 Emergency Phone Num:800-228-563 5/818-240-2060 CAGE:83574 === Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574

Ingred Name:METHYL PYRROLIDONE (VP = .3) CAS:872-50-4 RTECS #:UY5790000 Fraction by Wt: 5.0% Other REC Limits:NONE RECOMMENDED

Ingred Name:WATER (VP = 23) CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 50.0% Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-HAZARDOUS ADDITIVES, RESIN & PIGMENTS TRADESECRET Fraction by Wt: 20.0% Other REC Limits:NONE RECOMMENDED Ingred Name: TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 15.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3 Ingred Name: PROPANOIC ACID, 2-METHYL-MONOESTER WITH 2,2,4-TRIMETHYL-1,3-PENTANEDIOUL,TRIMETHYL-3,3,-PENTANEDIOL MONOISOBUTYRATE CAS:25265-77-4 RTECS #:UF6 000000 Fraction by Wt: 93C Lower Limits:NE **Upper Limits:NE** Extinguishing Media: USE NFPA CLASS B EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL OR FOAM). Fire Fighting Procedures: COOL CONTAINERS W/WATER. USE NIOSH/MSHA APPROVED SCBA & PROTECTIVE CLOTHES. Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY RUPTURE OR EXPLODE IN EXTREME HEAT. Spill Release Procedures: USE PERSONAL PROTECTIVE EQUIPMENT. SM SP: DIKE & AB SORBENT W/INERT MATERIAL. CALL EMERGENCY RESPONSE PROFESSIONALS IF MANAGING A RELEASE IS BEYOND THE CAPACITY OF IN HOUSE PERSONNEL. DISPOSAL: PRECAUTI ONS TO PREVENT CONTAM OF GROUND OR SURFACE WATERS. Handling and Storage Precautions: KEEP CONTAINERS TIGHTLY CLOSED. Other Precautions: DONT TAKE INTERNALLY. FOLLOW ALL LABEL WARNINGS.

Respiratory Pr

otection: AREAS WHERE TLVS MAY BE EXCEEDED OR IF SPRAY MIST IS PRESENT, USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTION/OSHA REGULATIONS FOR **RESPIRATOR USE.** Ventilation: ADEQUATE GENERAL LOCAL DILUTION OR LOCAL EXHAUST VENT TO MAINTAIN EMPLOYEE EXPOSURE. Protective Gloves: CHEMICAL RESISTANT Eye Protection: SAFETY GLASSES W/SIDE SHIELES OR GOGGLES Other Protective Equipment: AVOID SKIN CONTACT BY USING PROTECTIVE CLOTHES. SAFETY SHOWER. EYE BATH AND WASHING FACILITIES SHOULD BE AVAILABLE. Work Hygienic Practices: WASH CONTAM CLOTHES BEFORE REUSE. Supplemental Safety and Health WHERE EMPLOYEES WILL NOT BE EXPOSED, KEEP LEVEL BELOW 25% OF LEL.

Boiling Pt:B.P. Text:212 TO 396F Vapor Density:>AIR Spec Gravity:1.18 Evaporation Rate & amp; Reference:SLOWER THAN BUAC Appearance and Odor:GREEN LIQUID Percent Volatiles by Volume:73.2

Stability Indicator/Materials to Avoid:YES NON-RECOGNIZED Stability Condition to Avoid:FIRE & EXCESSIVE HEAT. Hazardous Decomposition Products:CARBON, CARBON MONOXIDE AND CARBON DIOXIDE.

Waste Disposal Methods:MATERIAL IS NOT A IGNITABLE HAZARDOUS WASTE IN ACCORDANCE W/FEDERAL REGULATIONS. CHECK W/STATE ENVIRONMENTAL AGENCIES TO DETERMINE IF MATERIAL IS REGULATED. NO DISPOSAL METHOD

SHOULD BE USED THAT WOUL D PRESENT ENVIRONMENTAL OR HUMAN HEALTHTREAT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and ass ume responsibility for the suitability of this information to their particular situation.