View NSN Online: https://aerobasegroup.com/nsn/8030-01-437-5222

CORROSION TECHNOLOGIES CORP. -- CORROSION X MARINE -- 8030-01-437-5222

Product ID:CORROSION X MARINE

MSDS Date:02/15/1997

FSC:8030

NIIN:01-437-5222

MSDS Number: CGXWQ === Responsible Party ===

Company Name: CORROSION TECHNOLOGIES CORP.

Box:551625 City:DALLAS State:TX

ZIP:75355-1625 Country:US

Info Phone Num:972-271-7361 FAX 972-278-9721

Emergency Phone Num:972-2

71-7361 CAGE:0VJ14

=== Contractor Identification ===

Company Name: CORROSION TECHNOLOGIES CORP.

Box:551625 City:DALLAS State:TX

ZIP:75355-1625 Country:US

Phone:972-271-7361 FAX 972-278-9721

CAGE:0VJ14

======= Composition/Information on Ingredients ========

Ingred Name:BASE STOCK

CAS:72623-85-9 Fraction by Wt: 69.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3

Ingred Name: HYDROCARBON SOLVENT

CAS:72623-83-7 Fraction by Wt: 8.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 P

Ingred Name: ZINC DINONYLNAPHTHALENE SULFONATE

CAS:8008-20-6

RTECS #:OA5500000 Fraction by Wt: 1.0%

Other REC Limits: NONE RECOMMENDED

Ingred Name:PROPELLANT (HYDROCARBON A70)

CAS:28016-00-4 Fraction by Wt: 12.0%

Other REC Limits: NONE RECOMMENDED

LD50 LC50 Mixture: (SEE HEALTH HAZARDS)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chron

ic:EYE: IRRIT, RED, WATERY. SKIN: LD50 IS

2000 MG/KG, DEFATTING, DERMATITIS, DRYING, CHAPPED. INHAL: LC50 = 5000 PPM RAT. NOSE/THROAT/UPPER RESPIRATORY TRACT IRRIT, DIZZY, HEADACHE, NAUSEA. INGEST: NON-T OXIC. LD50 1400 MG/KG (RAT ORAL). HARMFUL, FATAL, MOUTH/THROAT/ESOPHAGUS IRRIT, NAUSEA, VOMIT, GI UPSET, DIARRHEA.

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, LIFTING LIDS. SKIN: REMOVE EXCESS BY WIPI

NG, THEN WASH W/SOAP & WATER. WASH SOILED CLOTHES & SHOES W/DETERGENT. INHAL: REMOVE TO FRESH AIR. CPR IF NEEDED. INGEST: DO NT INDUCE VOMIT. DRINK 1/2 PINT OF MILK. CALL DR. IN ALL CASES, GET MED AID.


========= Fire Fighting Measures ===============

Flash Point Method:COC Flash Point:>285F,>141C

Lower Limits:1.0 Upper Limits:6.0

Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER SPRAY.

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT W/SCBA. COVER W/EXTIN



Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS SUCH

AS LIQUIDS, COMPRESSED OXYGEN, PEROXIDES OR CHLORINES.

Hazardous Decomposition Products:BURNING PRODUCTS NORMALLY BI-PRODUCTS OF COMBUSTION INCLUDE: CARBON MONOXIDE, PHENOLS OR PETROLEUM PRODUCTS.

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN APPROVED LANDFILL SITE OR INCINERATE AT A LICENSED WASTE RECLAIMMING FACILITY. LIQUID WASTE MAY BE REMOVED BY MEANS OF LICENSED RECLAIMER UNDER USED OIL CLASSIFICATION. FO

LLOW ALL FEDERA L, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.