View NSN Online: https://aerobasegroup.com/nsn/8030-01-437-5687

CORROSION TECHNOLOGIES CORP. -- CORROSION X MARINE -- 8030-01-437-5687

======== Product Identification ============

Product ID:CORROSION X MARINE

MSDS Date:12/13/1996

FSC:8030

NIIN:01-437-5687

MSDS Number: CGXWY === Responsible Party ===

Company Name: CORROSION TECHNOLOGIES CORP.

Box:551625 City:DALLAS State:TX

ZIP:75355-1625 Country:US

Info Phone Num:972-271-7361 FAX 972-278-9721

Emergency Phone Num:972-2

71-7361 CAGE:0VJ14

=== Contractor Identification ===

Company Name: CORROSION TECHNOLOGIES CORP.

Box:551625 City:DALLAS State:TX

ZIP:75355-1625 Country:US

Phone:972-271-7361 FAX 972-278-9721

CAGE:0VJ14

======= Composition/Information on Ingredients ========

Ingred Name:BASE STOCK

CAS:72623-85-9 Fraction by Wt: 72.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3

Ingred Name: HYDROCARBON SOLVENT

CAS:72623-83-7 Fraction by Wt: 9.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 P

Ingred Name:ZINC DINONYLNAPHTHALENE SULFONATE

CAS:8008-20-6

RTECS #:OA5500000 Fraction by Wt: 1.0%

Other REC Limits: NONE RECOMMENDED

========== Hazards Identification ===========================

LD50 LC50 Mixture:(SEE HEALTH HAZARDS)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: IRRIT, RED, WATERY. SKIN: LD50 IS 2000 MG/KG. DEFATTING, DERMATITIS, DRYING, CHAPPED. INHAL: LC50 =

5000 PPM RAT. NOSE/THROAT/UPPER RESPIRATORY TRACT IRRIT, DIZZY, HEADACHE, NAUSEA. INGEST: LD50 1400 MG/KG (RAT ORAL). SLIGHTLY TOXIC, HARMFUL, FATAL, MOUTH/THROAT/ESPHAGUS IRRIT, NAUSEA, VOMIT, GI UPSET, DIARRHEA.

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, LIFTING LIDS. SKIN: REMOVE EXCESS BY WIPING, THEN WASH W/SOAP & WATER. WASH SOILED CLOTHES & SHOES W/DETERGENT. INHAL: REMOVE TO FRESH AIR. CPR IF NEEDED.

INGEST: DO NT INDUCE VOMIT. DRINK 1/2 PINT OF MILK. CALL DR. IN ALL CASES, GET MED AID.

============ Fire Fighting Measures =========================


Flash Point Method:COC Flash Point:>285F,>141C

Lower Limits: 1.0 Upper Limits: 6.0

Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER SPRAY.

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT W/SCBA. COVER W/EXTINGUISHING AGENT. DONT SPRAY W/WATER USING DIRECT STREAM INTO BURNING LIQIUD, MAY SPREAD FIRE.

Unusual Fire



ts	S:BURNING PRODUCTS NORMALLY BI-PRODUCTS
	OF COMBUSTION INCLUDE: CARBON MONOXIDE, PHENOLS OR PETROLEUM
	PRODUCTS.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE OF IN APPROVED LANDFILL SITE OR INCINERATE AT A LICENSED WASTE RECLAIMMING FACILITY. LIQUID WASTE MAY BE REMOVED BY MEANS OF LICENSED RECLAIMER UNDER USED OIL CLASSIFICATION. FOLLOW ALL FEDERA L, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.