View NSN Online: https://aerobasegroup.com/nsn/4470-00-514-2568

Product ID:31009, IONAC C-267 MSDS Date:09/07/1990 FSC:4470 NIIN:00-514-2568 MSDS Number: CGZLB === Responsible Party === Company Name:SYBRON CHEMICALS INC Address:BIRMINGHAM RD City:BIRMINGHAM State:NJ ZIP:08011 Country:US Info Phone Num:609-893-1100 Emergency Phone Num:609-893-1100 CAGE:76465 === C ontractor Identification === Company Name: SYBRON CHEMICALS INC, SUB OF SYBRON CORP Address: BIRMINGHAM RD Box:66 City:BIRMINGHAM State:NJ ZIP:08011 Country:US Phone:609-893-1100 CAGE:76465 Ingred Name: SULFONATED COPOLYMER OF STYRENE AND DIVINYLBENZENE; (BENZENE, DIETHENYL-, POLYMER WITH ETHENYLBENZENE AND (ING 2) CAS:69011-20-7 Fraction by Wt: 50-60% OSHA PEL:N/K ACGIH TLV:N/K Ingred Name: ING 1: ETHENYLETHYLBENZENE, SULF

ONATED IN HYDROGEN FORM) RTECS #:99999992Z

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 40-50% OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name:SUP DAT: HYDRAULIC (WATER) SLURRY ALL SAFETY PRACTICES ESTABLISHED FOR USE OF WATER IN THE WORK SPACE MUST BE OBSERVED. RTECS #:9999992Z

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenici

ty:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CAN PRODUCE MECHANICAL IRRITATION TO THE EYE. MAY CAUSE SKIN IRRITATION OF HYPERSENSITIVE PERSONNEL. CHRONIC: MECHANICAL IRRITATION TO THE EYE AND SKIN IRRITATION TO HYPERSENSITIVE PERSONNEL.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:RED, IRRITATED EYES, ITCHING AND FEELING THAT A PARTICLE EXISTS BETWEEN THE EYELID AND EYE. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACT URER.

First Aid:EYES/SKIN: FLUSH WITH COPIOUS QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, SEE MD, AMERICAN RED CROSS. INHALATION: REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE OXYGEN OR ARTIFI CIAL RESPIRATION). INGESTION: CALL MD IMMEDIATELY

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE OR WATER FOG. Fire Figh

ting Procedures:WEAR NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . GUARD AGAINST CONTACT OF PRODUCT WITH EYE DURING SALVAGE OPERATION. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER. Spill Release Procedures: SWEEP AREA OF PRODUCT, COLLECTING IN A CONTAINER FOR DISPOSAL. AREAS OF SPILL CAN BECOME EXTREMELY SLIPPERY, ALL NORMAL SAFETY PRECAUTIONS SHOULD BE OBSERVED. Neutralizing Agent:NONE SPECI FIED BY MANUFACTURER. Handling and Storage Precautions: NO SPECIAL HANDLING IS REQUIRED BEYOND THOSE OUTLINED IN THIS MSDS. AVOID PACKING PRODUCT IN AN UNPROTECTED GLASS COLUMN. Other Precautions: EXPANSION OF PROD CAN CAUSE GLASS COLUMN TO SHATTER. AVOID FREEZING/PROLONGED STORAGE ABOVE 50C BECAUSE PROD CONTAINS WATER WHICH WILL FREEZE & DAMAGE PROD/DRY-OUT ALSO DAMAGING PROD. AVOID CONT W/STR ONG OXIDIZERS SUCH AS NITRIC ACID. Respiratory Protection: USE NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN. Ventilation: NONE SPECIFIED BY MANUFACTURER. Protective Gloves: IMPERVIOUS GLOVES. Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES . Other Protective Equipment: ANSI APPRVD EMER EYEWASH & DELUGE SHOWER . LONG SLEEVE SHIRTS & LONG TROUSERS ARE REC TO PREVENT SKIN CONTACT. Work Hygienic Practices: FLUSH PROD FROM H ANDS W/SOAPY WATER. CARE SHOULD BE TAKEN TO AVOID CONT W/EYES UNTIL HANDS HAVE BEEN COMPLETELY(SUP DAT) Supplemental Safety and Health HYGIENE PRACT: CLEANED. PROD HAS TENDENCY TO CLING TO SKIN DUE TO STATIC CHARGE. CARE MUST BE EXERCISED TO REMOVE ALL PROD FROM SKIN. PROD CAUSES AREAS TO BECOME EXTREMELY SLIPPERY WHEN SPILLED, & CAN CAUSE FALLS. SWEEP UP SPILLED MATL & TRANSFER FOR PROPER DISP. WHEN TRANSFERRING PROD TO OTHER CONTRS VIA (ING 4) ====== Phys

Vapor Pres:SEE ING 2 Vapor Density:SEE ING 2 Spec Gravity:1.3 pH:6-9 Evaporation Rate & amp; Reference:1 (H*2O=1) Solubility in Water:INSOLUBLE Appearance and Odor:SPHERICAL BEADS, ODORLESS; SOLID

Stability Indicator/Materials to Avoid:YES EXPLOSIVE REACTIONS CAN OCCUR IN THE PRESENCE OF STRONG OXIDIZING AGENTS, SUCH AS NITRIC ACID. Stability Condition to Avoid:AT TEMPERATURES A BOVE 204C, DECOMPOSITION OCCURS. Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,

STYRENE, DIVINYLBENZENE.

Waste Disposal Methods:NEW, UNUSED PRODUCT CAN BE DISPOSED OF AS ORDINARY TRASH IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. USED PRODUCT MUST BE TESTED FOR CONTAMINATION BY HAZARDOUS MATERIAL AND DISPOSED O F ACCORDINGLY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.