View NSN Online: https://aerobasegroup.com/nsn/9160-00-075-9816

Product ID: AMPROL TYPE II TRANSFORMER OIL, 11104 MSDS Date:03/24/1997 FSC:9160 NIIN:00-075-9816 **MSDS Number: CHHMC** === Responsible Party === Company Name: LYONDALL LUBRICANTS Address:12000 LAWNDALE AVE Box:2451 **City:HOUSTON** State:TX ZIP:77252-2451 Country:US Info Phone Num:800-447-4572 Emergency Phone Num:800-313-7646(800-424-8300 CHEMTREC) CAGE:07G23 === Contractor Identification ===

Company Name:LYONDALL LUBRICANTS Address:12000 LAWNDALE AVE Box:2451 City:HOUSTON State:TX ZIP:77252-2451 Country:US Phone:800-447-4572 CAGE:07G23

Ingred Name:SEVERELY HYDROTREATED LIGHT NAPHTHENIC DISTILLATE, (TYPE II ELECTRICAL TRANSFORMER OIL), (MINERAL OIL) CAS:64742-53-6 RTECS #:PY8036000 Fraction by Wt: 99.5% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ADDITIVE MIXTURE OXIDATION INHIBITORS (PROPRIETARY) Fraction by Wt: 0.5% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5000 MG/KG. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: NO IRRITATION EXPECTED FRO M

SHORT-TERM EXPOSURE. SKIN: MILD IRRITATION FROM SHORT-TERM EXPOSURE. INHALATION: MISTS OR VAPORS MAY IRRITATE THE MUCOUS MEMBRANES OF THE NOSE, THROAT, BRONCHI, AND L UNGS. ASPIRATION INTO LUNGS MAY CAUSE LIPOID PNEUMONIA. INGESTION: NOT LIKELY TO OCCUR. IT MAY CAUSE A LAXATIVE EFFECT.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: MILD IRRITATION FROM SHOT EXPOSURE. PROLONGED AND/OR REPEATED CONTACT MAY PRODUCE MILD TO MODERATE SKIN IRRITATION, I

NFLAMMATION, AND/OR SENSITIZATION. INHALATION:

IRRITATION OF NOSE, THROAT, BR ONCHI, LUNGS. INGESTION: LAXITIVE EFFECT.

Medical Cond Aggravated by Exposure:PERSONNEL WITH PRE-EXISTING SKIN DISORDERS, CHRONIC RESPIRATORY DISEASES, OR BLOOD DISORDERS SHOULD AVOID CONTACT WITH THIS PRODUCT.

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF PAIN OR REDNESS PERSISTS, GET MEDICAL ATTENTION. SKIN: REMOVE CONT AMINATED

CLOTHING. WASH SKIN WITH LARGE AMOUNTS OF MILD SOAP AND WATER. INHALATION: NOT EX PECTED TO BE AN PROBLEM UNDER ANTICIPATED CONDITIONS OF USE. IN CASE OF OVEREXPOSURE, MOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING. IF IRRITATION OCCURS, GET MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point:300F,149C Lower Limits:1.0 % Upper Limits:7.0% Extinguishing Media:SMALL FIRE: DRY CEMICALS,CARBO

N DIOXIDE, FOAM, WATER FOG, INERT GAS(HALON OR NITROGEN).LARGE FIRES:WATER FOG,SPRAY,FOAM. Fire Fighting Procedures:NEVER USE WATER JET,MAY SPREAD FIRE. FOAM/WATER ARE EFFECTIVE,MAY CAUSE FOAMING.WEAR PROTECTIVE CLOTHING/EQUIPMENT.COOL CONTAINERS EXPOSED TO FIRE WITH WATER. Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO FIRE MAY BURST OR LEAK FLAMMABLE VAPORS THAT CAN BURN IN OPEN OR BE EXPLOSIVE IN CONFINED SPACES.MISTS MAY BE FLAMMABLE BELOW FLASH POINT.
======= Accidental Release Measures ====================================
Spill Release Procedures:CONTAIN SPILL AND PREVENT IT FROM ENTERING ALL WATER BODIES.MAXIMIZE RECOVERY FOR REUSE OR RECYCLING.TAKE UP EXCESS WITH SAND OR OTHER INERT NON-COMBUSTIBLE ABSORBENT AND PLACE IN APPROPTIATE CONTAINE RS FOR LATER DISPOSAL.COMPLY WITH ALL REGULATIONS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
 Handling and Storage Preca utions:TO AVOID PRODUCT DEGRADATION, WATER CONTAMINATION SHOULD BE AVOIDED AND MINIMUM HANDLING TEMPERATURES SHOULD BE MAINTAINED.MINIMIZE EXPOSURE TO >200F. Other Precautions:KEEP CONTAINER CLOSED AND IN A DRY, COOL, WELL-VENTILATED PLACE. STORE AWAY FROM EXTREME HEAT, RADIATION SOURCES, AND STRONG OXIDIZING AGENTS. DO NOT PUNCTURE, INCINERATE, OR STORE CONTAINERS AT TEMPE RATURES ABOVE 120F OR IN DRECT SUNLIGHT.
========== Exposure Controls/Personal Protection ===

Respiratory Protection:NONE NORMALLY REQUIRED WITH ADEQUATE VENTILATION. IF TLV/PEL OF 5 MG/M3 IS EXCEEDED WEAR PROPER NIOSH/MSHA APPROVED VAPOR CONTOL RESPIRATORY EQUIPMENT. Ventilation:PROVIDE EXHAUST VENTILATION/ENGINEERING CONTROLS TO KEEP AIRBORNE CONCENTRATIONS OF MISTS/VAPORS BELOW APPROVED LIMITS. Protective Gloves:DISPOSABLE,VINYL,NITRILE,NEOPRENE GLOVES Eye Protection:SAFETY GLASSES,OR GOGGLES,OR FACE SHIELD Other Protective Equipment:AVOID SKIN CONTACT OR WEAR

Boiling Pt:B.P. Text:480F,249C Va por Pres:0.1 MM HG Vapor Density:>10 AIR=1 Spec Gravity:0.88-0.91 pH:UNKNON Solubility in Water:NEGLIGIBLE Appearance and Odor:TRANSPARENT,LILY WHITE TO SLIGHTLY YELLOW LIQUID. HYDROCARBON LUBE OIL ODOR. Percent Volatiles by Volume:NEG

Stability Indicator/Materials to Avoid:YES STRONG ACIDS, ALKALIES, OXIDIZERS SUCH AS OXYGEN AND LIQUID CHLORINE. Stability Condition to Avoid:EXTREME HEAT, OPEN FLAME. Hazardous Decompositio n Products:SMOKE, CARBON MONOXIDE, CARBON DIOXIDE, PHENOL, AMMONIA, OXIDES AND OTHER COMPOUNDS OF NITROGEN.FREE AROMATIC AMINES.

Waste Disposal Methods:USE APPROVED TREATMENT TRANSPORTERS AND DISPOSAL SITES IN COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. SPILL MATERIAL IS BIODEGRADABLE IF GRADUALLY EXPOSED TO MICROORGANISMS. PREFERABLY IN AN AEROBIC ENVIRONMENT.

Disclaimer (provided with this in

formation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.