

ANSUL FIRE PROTECTION, WORMALD U.S.INC. -- HALON 1301,FREON FE 1301 -- 6830-01-275-1637  
===== Product Identification =====

Product ID:HALON 1301,FREON FE 1301  
MSDS Date:05/07/1993  
FSC:6830  
NIIN:01-275-1637  
MSDS Number: CHHSW  
=== Responsible Party ===  
Company Name:ANSUL FIRE PROTECTION, WORMALD U.S.INC.  
Address:ONE STANTON STREET  
City:MARINETTE  
State:WI  
ZIP:54143-2542  
Country:US  
Info Phone Num:715  
-735-7411  
Emergency Phone Num:715-735-7411/800-424-9300(CHEMTREC)  
CAGE:03670  
=== Contractor Identification ===  
Company Name:ANSUL INC  
Address:ONE STANTON STREET  
Box:City:MARINETTE  
State:WI  
ZIP:54143-2542  
Country:US  
Phone:715-735-7411  
CAGE:03670  
Company Name:FIRE-X OF VA (804-266-8844)  
Address:6107 STAPLES MILL RD  
Box:9757  
City:RICHMOND  
State:VA  
ZIP:23225  
Country:US  
Phone:804-266-8844  
CAGE:0FA36

===== Composition/Information on Ingredients =====

Ingred Name:TRIFLUOROBROMOMETHA

NE (HALON 1301) (SARA III)

CAS:75-63-8

RTECS #:PA5425000

Fraction by Wt: >99%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9293

Ozone Depleting Chemical:1

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:(RAT) 2112 MG/L 4 HRS.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-EYES/SKIN:LIQUID CAN CAUSE  
FROSTBITE. INHALATION:VAPOR

IS HEAVIER THAN AIR & CAN CAUSE

SUFFOCATION. VERY HIGH CONCENTRATIONS CAN CAUSE GIDDINESS,  
SHORTNESS OF BREATH, NARCOSIS, CARDIAC IRREGULARITIES,  
UNCONSCIOUSNESS OR EVEN DEATH. ORAL:NOT LIKELY. CHRONIC- NONE  
KNOWN.

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%  
WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of Overexposure:DIZZINESS, IMPAIRED COORDINATION, REDUCED  
MENTAL ACUITY AND CARDIAC EFFECTS CAN OCCUR. UNCONSCIOUSNESS OR  
E

VEN DEATH IN HIGH CONCENTRATIONS WITH LONGER EXPOSURES.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING CARDIAC  
DISEASES MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THE SUBSTANCE.

=====  
===== First Aid Measures =====

First Aid:OBTAIN MEDICAL HELP IF SYMPTOMS PERSIST. INHALATION:REMOVE TO  
FRESH AIR. EYES/SKIN:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES.  
HOLD EYELIDS OPEN. TREAT FOR FROSTBITE IF NECESSARY. INGESTION: NOT  
LIKE LY. NOTE T

O PHYSICIAN:DO NOT GIVE ADRENALINE OR SIMILAR  
SYMPTOMATIC DRUGS. DO NOT ALLOW VICTIM TO EXERCISE UNTIL 24 HOURS  
FOLLOWING SPECIFIC EXPOSURES. FREEZE BURNS OF MUCOSAL TISSUE CAN  
DEVELOP.

=====  
===== Fire Fighting Measures =====

Extinguishing Media:THIS IS A FIRE EXTINGUISHING AGENT. USE WATER TO  
COOL FIRE-EXPOSED CYLINDERS OR OTHER CONTAINERS.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-  
APPROVED SELF-CONTAINED BREATHING APPAR

ATUS WHEN ENTERING

UNVENTILATED FIRE AREAS WHERE PRODUCT HAS BEEN USED.

Unusual Fire/Explosion Hazard:CONTAINERS ARE EQUIPPED WITH PRESSURE AND TEMPERATURE RELIEF DEVICES, BUT RUPTURE MAY OCCUR UNDER FIRE CONDITIONS & MAY PRODUCE TOXIC FUMES IN FIRES OVER 900F.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AREA. VENTILATE HTE AREA. COOL OR REMOVE HOT METAL SURFACES AND OPEN FLAMES.

Neutralizing Agent:NOT APPLICABLE.

=====

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE AS A LIQUIFIED COMPRESSED GAS IN DOT APPROVED PRESSURE VESSELS AWAY FROM HIGH TEMPERATURES. KEEP AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:AVOID BREATHING VAPORS OR MISTS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. KEEP OUT OF REACH OF C HILDREN.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NON REQUIRED UNDER NORMAL CONDITIONS. IF HIGH VAPOR OR MIST CONCENTRATIONS EXPECTED, USE NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS AND MISTS. WEAR SUPPLIED-AIR RESPIRATOR PROTECTION IN CONFINED OR ENCLOSED SPACES, IF NEEDED.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:PLASTIC GLOVE RECOMMENDED

Eye Prot

ection:SAFETY GLASSES

Other Protective Equipment:EYE WASH STATION, EMERGENCY SHOWER, NORMAL WORK CLOTHING COVERING ARMS AND LEGS

Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR DRINKING. DO NOT BREATHE DUSTS. AVOID CONTACT WITH EYES AND SKIN.

Supplemental Safety and Health

USE IN A WELL VENTILATED AREA ONLY. DO NOT RELEASE TO ENVIRONMENT.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-72F,-58C

Decomp Temp:Decomp Text:>900F,>48

2C

Vapor Pres:10292 @70F

Vapor Density:5.2

Spec Gravity:1.57

Evaporation Rate & Reference:GAS AT ROOM TEMPERATURE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORLESS GAS - SWEET ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACTIVE METALS AND FIRES INVOLVING METAL HYDRIDES.

Stability Condition to Avoid:EXCESSIVE HEAT (ABOVE 900F)

Hazardous Decomposition Products:HYDROGEN FLUORIDE

& HYDROGEN

BROMIDE.THEY HAVE A SHARP IRRITATING ODOR & IN EVEN LOW  
CONCENTRATIONS CAUSE INJURY/ DEATH.

===== Disposal Considerations =====

Waste Disposal Methods:RETURN TO DRMO OR MANUFACTURER FOR RECYCLING OR  
REUSE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, war  
rants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.