View NSN Online: https://aerobasegroup.com/nsn/8030-01-252-7963 FLAMEMASTER CORP -- CS5500 CLASS B (PART A) -- 8030-01-252-7963 Product ID:CS5500 CLASS B (PART A) MSDS Date:01/03/1997 FSC:8030 NIIN:01-252-7963 Kit Part:Y MSDS Number: CHKJM === Responsible Party === Company Name: FLAMEMASTER CORP Address:11120 SHERMAN WAY City:SUN VALLEY State:CA ZIP:91352 Country:US Info Phone Num:800-424-9300 CHEMTREC **Emergency Phone Num:818** -982-1650 Preparer's Name: HERBERT MOORE CAGE:14439 === Contractor Identification === Company Name: FLAMEMASTER CORP THE CHEM SEAL DIV Address:11120 SHERMAN WAY Box:City:SUN VALLEY State:CA ZIP:91352-4949 Country:US Phone:818-982-1650 CAGE:14439

======= Composition/Information on Ingredients ========

Ingred Name: POLYSULFIDE POLYMER

CAS:68611-50-7 Fraction by Wt: 50.0%

Other REC Limits: NONE RECOMMENDED

========= Hazards Identification ===============

Routes of E

| ntry: Inhalation:NO Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN: IRRITATION, DERMATITIS. Effects of Overexposure:SKIN: IRRITATION. EYE: IRRITATION. Medical Cond Aggravated by Exposure:NONE |
|--|
| ====================================== |
| First Aid:EYES: FLUSH W/WATER, GET MED AID. SKIN: WASH W/SOAP & WATER. INGEST: INDUCE VOMITING, GET MED AID. |
| ====================================== |
| Flash Point Method:TCC Flash Point:>200F,>93C Extinguishing Media:DRY CHEMICAL, FOAM, WATER, CO2. Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE |
| ========= Accidental Release Measures ========= |
| Spill Release Procedures:SCOOP, TRANSFER TO CONTAINER FOR REACTION W/CURING AGENT. CLEAN RESIDUE W/AEROMATIC NAPHTHA, THEN SOAP & WATER. |
| ====================================== |
| Handling and Storage Precautions:STORE IN COOL, DRY AREA AWAY FROM STRONG ACIDS. Other Precautions:WASH HANDS BEFORE EATING, SMOKING, DRINKING AND AFTER HANDLING THIS PRODUCT. |
| ===== Exposure Controls/Personal Protection ======= |
| Respiratory Protection:NOT REQUIRED. Ventilation:LOCAL EXHAUST, AIR. (MECHANICAL) FAN. Protective Gloves:RUBBER Eye Protection:SAFETY GLASSES Other Protective Equipment:PROTECTIVE CLOTHING APPROPRIATE TO PREVENT SKIN CONTACT. Work Hygienic Practices:TRAIN PERSONNEL IN THE PROPER |

| HANDLING OF THIS PRODUCT. |
|---|
| Supplemental Safety and Health NK |
| ======== Physical/Chemical Properties ========= |
| Boiling Pt:B.P. Text:NA Decomp Temp:Decomp Text:NA Vapor Pres:NIL Vapor Density:8.5 Spec Gravity:1.52 VOC Pounds/Gallon:3 Viscosity:10000 POISES Evaporation Rate & amp; Reference:NIL Solubility in Water:NEGLIGIBLE Appearance and Odor:GRAY PASTE, POLYSULFIDE ODOR. Percent Volatiles by Volume:2.0 Corrosion Rate:NA |
| ====================================== |
| Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG ACIDS. Stability Condition to Avoid:OPEN FLAME Hazardous Decomposition Products:H2S, CO, CO2, SO2, SMOKE. |
| ======= Disposal Considerations ========== |
| Waste Disposal Methods:REACT W/CURING AGENT AND DISPOSE OF AS SOLID WASTE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS, INCINERATION BY LANDFILL METHOD. MIXED OR NOT MIXED W/PART B NON-HAZARDOUS WASTE. |
| ======== Other Information ==================================== |

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the su

