

FLAMEMASTER CORP -- CS3202 PART B -- 8030-01-381-1821

=====  
===== Product Identification =====

Product ID:CS3202 PART B  
MSDS Date:06/24/1996  
FSC:8030  
NIIN:01-381-1821  
Kit Part:Y  
MSDS Number: CHKKL  
=== Responsible Party ===  
Company Name:FLAMEMASTER CORP  
Address:11120 SHERMAN WAY  
City:SUN VALLEY  
State:CA  
ZIP:91352  
Country:US  
Info Phone Num:800-424-9300 CHEMTREC  
Emergency Phone Num:818-982-1650  
Preparer's  
Name:HERBERT MOORE  
CAGE:14439  
=== Contractor Identification ===  
Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV  
Address:11120 SHERMAN WAY  
Box:City:SUN VALLEY  
State:CA  
ZIP:91352-4949  
Country:US  
Phone:818-982-1650  
CAGE:14439

=====  
===== Composition/Information on Ingredients =====

Ingred Name:LEAD DIOXIDE  
CAS:1309-60-0  
RTECS #:OG0700000  
Fraction by Wt: 64.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.05 MG/M3  
ACGIH TLV:0.05 MG/M3

Ingred Name:LEAD OXIDE  
CAS:1317-36-8  
RTECS #:OG175

0000  
Fraction by Wt: 6.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.05 MG/M3  
ACGIH TLV:0.05 MG/M3

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE-WEAKNESS, STUPOR. CHRONIC-KIDNEY  
DAMAGE, ANEMIA, REPRODUCTIVE DEFECTS.  
Effects of Overexposure:HEADACHE, MUSCLE AND JOINT PAIN, NEUROMUSCULAR  
DYSFUNCTION.  
Medical Cond Aggravated by Exposure:ANEMIA, KIDNEY DISEASE, PREGNANCY.

=====  
First Aid Measures  
=====

First Aid:INGEST: INDUCE VOMITING, GET MED AID. EYE: FLUSH W/WATER, GET  
MED AID.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC  
Flash Point:200F,93C  
Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER.  
Fire Fighting Procedures:USE SCBA W/FULL-FACE PIECE IN CONFINED AREAS.  
Unusual Fire/Explosion Hazard:FIRE HAZARD EXISTS. IF CONTACT  
W/OXIDIZABLE MATERIALS AT HIGH TEMP.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SCOOP, TRANSFER TO SAFETY CONTAINER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL, DRY AREA. KEEP  
CONTAINERS CLOSED.  
Other Precautions:WASH HANDS BEFORE EATING, SMOKING, DRINKING AND AFTER  
HANDLING THIS PRODUCT.

=====  
Exposure Controls/Personal Protection  
=====

===

Respiratory Protection:IF SOOT IS FORMED, USE NIOSH APPROVED RESPIRATOR.

Ventilation:LOCAL EXHAUST, AIR HOOD. (MECHANICAL) FAN.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT.

Work Hygienic Practices:TRAIN PERSONNEL FOR SAFE HANDLING PROCEDURES.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:644F,340C

Melt/Freeze Pt:M.P/F.P Text:LIQUID

@ RM

Decomp Temp:Decomp Text:NA

Vapor Pres:NIL

Vapor Density:NA

Spec Gravity:3.0

VOC Pounds/Gallon:1

pH:6.8

Evaporation Rate & Reference:NIL

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BROWN PASTE, OILY ODOR.

Percent Volatiles by Volume:3.0

Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZABLE MATERIALS

Stability Condition to Avoid:HIGH HEAT

Hazardous Decomposition Products:LEAD OXIDE DUST AND ORGA

NICS

===== Disposal Considerations =====

Waste Disposal Methods:RETURN TO SMELTER FOR RECLAMATION OR REACT W/BASE. DISPOSE IN ACCORDANCE W/FEDERAL, STATE AND LOCAL REGULATIONS. DISPOSE AS HAZARDOUS MIXED SOLID WASTE.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United Sta

tes of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.