View NSN Online: https://aerobasegroup.com/nsn/9150-00-250-0933

Product ID:VV-P-236A MSDS Date:08/01/1997 FSC:9150 NIIN:00-250-0933 MSDS Number: CHKWW === Responsible Party === Company Name:SDB CONSULTANTS LTD Address:401 WHITNEY AVE SUITE 206 City:GRETNA State:LA ZIP:70056 Country:US Info Phone Num:504-368-7900 Emergency Phone Num:504-366-9105 CAGE:0PGK2 === Contractor Id entification === Company Name:SDB CONSULTANTS LTD Address:401 WHITNEY AVE SUITE 120 Box:City:GRETNA State:LA ZIP:70056 Country:US Phone:504-366-9105 Contract Num:SP0450-98-Q-9048 CAGE:0PGK2 Company Name:SDB CONSULTANTS LTD Address:401 WHITNEY AVE SUITE 120 Box:City:GRETNA State:LA ZIP:70056 Country:US Phone:504-366-9105 Contract Num:SP0450-99-M-B104 CAGE:0PGK2 Company Name:SDB CONSULTANTS LTD Address:401 WHITNEY AVE SUITE 120 Box:City:GRETNA State:LA ZIP:70056 Country:US Phone:504-366-9105 Contr

act Num:SP0450-99-M-B158 CAGE:0PGK2

Ingred Name:PETROLATUM CAS:8009-03-8 RTECS #:SE6780000 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 OIL MIST

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER Health Hazards Acute and Chronic:NONE LISTED IN MSDS. Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER Effects of Overexposure:NONE. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER

First Aid:EYES: FLUSH IMMEDIATELY WITH COLD WATER, CALL A PHYSICIAN. SKIN: FOR MOLTEN PETROLEUM, FLUSH IMMEDIATELY WITH COLD WATER. CALL A PHYSICIAN. FOR SOLIDIFIED PETROLATUM REMOVE EXCESS WITH PAPER TOWELS, WASH WITH SOAP AND WATER. INHALATION: NO DATA. INGESTION: CALL A PHYSICIAN.

Flash Point Method:COC
Flash Point:>204.4C, 400.F
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE (C02), FOAM, WATERM
FOG OR SAND/EARTH.
Fire Fighting Procedures:WATER SPRAY IS AN UNSUITABLE EXTINGUISHING
AGENT. FIRE FIGHTERS SHOULD USE SELF-CONTAINED BREATHING APPARATUS
TO PROTECT AGAINST SMOKE INHALATION.
Unusual Fire/Explosion Hazard:NONE.

Spill Release Procedures: SHUT OFF LEAK AND DIKE UP LARGE SPILLS. AFTER

COOLING AND SOLIDIFICATION, SCRAP AND/OR SHOVEL UP MATERIAL. FINALLY, CLEAN AREA WITH AN OIL ABSORBENT MATERIAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER

Handling and Storage Precautions:STORE AWAY FROM FLAME, HEAT (200F MAX) AND STRONG OXIDIZING AGENTS. AVOID SKIN AND EYE CONTACT. Other Precautions:NONE

Respiratory Protection:NO DATA A VAILABLE Protective Gloves:WEAR IMPERVIOUS GLVOES. Eye Protection:WEAR A FACE SHIELD OVER SAFETY GLASSES. Other Protective Equipment:WEAR OVERALLS. Work Hygienic Practices:READ ALL LABELS CAREFULLY BEFORE USING. Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER

HCC:V6 Boiling Pt:B.P. Text:NO DATA AVAILABLE Melt/Freeze Pt:M.P/F.P Text:110 TO 180F Vapor Pres:NO DATA AVAILABLE Spec Gravity:NO DATA AVAILABLE Evaporati on Rate & amp; Reference:NO DATA AVAILABLE Solubility in Water:NIL Appearance and Odor:SEMI-SOLID, OIL LIKE, OPAQUE COLOR: YELLOW OR BROWN.

Stability Indicator/Materials to Avoid:YES NONE. Stability Condition to Avoid:NONE.

Hazardous Decomposition Products:NONE.

Toxicological Information:NONE SPECIFIED BY MANUFACTURER

====== Ecological Inf

Ecological:NONE SPECIFIED BY MANUFACTURER

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Transport Information:NONE SPECIFIED BY MANUFACTURER

SARA Title III Information:NONE SPECIFIED BY MANUFACTURER Federa I Regulatory Information:NONE SPECIFIED BY MANUFACTURER State Regulatory Information:NONE SPECIFIED BY MANUFACTURER

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use

. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.