

FISKE BROS REFINING CO -- LUBRIPLATE NO:630-A,630-2,630-AA,630-AAA -- 9150-00-663-1770

=====  
Product Identification  
=====

Product ID:LUBRIPLATE NO:630-A,630-2,630-AA,630-AAA

MSDS Date:01/01/2000

FSC:9150

NIIN:00-663-1770

MSDS Number: CHKXK

=== Responsible Party ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-915

0

Emergency Phone Num:800-255-3924 CHEM-TEL

Preparer's Name:JAMES R. KONTAK

CAGE:73219

=== Contractor Identification ===

Company Name:COMPTECH CORP

Address:15944 DERWOOD RD

Box:City:ROCKVILLE

State:MD

ZIP:20855

Country:US

Phone:800-284-5279; 301-519-3401

Contract Num:SP0450-01-M-LP92

CAGE:0BR38

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AV

E  
Box:City:TOLEDO  
State:OH  
ZIP:43605  
Country:US  
Phone:419-691-2491  
CAGE:9N579  
Company Name:HERMAN YENCIES INC  
Address:577 MAIN STREET  
Box:688  
City:PASSAIC  
State:NJ  
ZIP:07055  
Country:US  
Phone:973-777-7200 /FAX: 973-777-0954  
CAGE:0B260  
Company Name:SDB CONSULTANTS LTD  
Address:401 WHITNEY AVE SUITE 120  
Box:City:GRETNA  
State:LA  
ZIP:70056  
Country:US  
Phone:504-366-9105  
Contract Num:SP0450-99-M-B043  
CAGE:0PGK2

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NON-HAZARD  
OUS  
= Wt:100.  
Other REC Limits:TLV 5MG/M3 OIL MIST

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NO DATA PROVIDED BY MANUFACTURER  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY  
CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE  
IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A  
PRECAUTION, EXPOSURE TO LIQUID, VAPORS, MISTS AND FUMES SHOU

LD BE

MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY .

Explanation of Carcinogenicity:NO DATA PROVIDED BY MANUFACTURER.

Effects of Overexposure:ROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUID, V APORS, MIST

S AND FUMES SHOULD BE

MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH CLEAR WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.  
SKIN: REMOVE CONTAMI

NATED CLOTHING. WASH SKIN AREA WITH SOAP AND WATER. IF INJE CTED UNDER SKIN, GET IMMEDIATE MEDICAL ATTENTION. DELAY MAY CAUSE LOSS OF AFFECTED PART OF THE BODY. INHALATION: VAPOR PRESSURE IS VERY LOW AND INHALATION AT ROOM TEMPERATURE IS NOT A PROBLEM. IF OVER COME BY VAPOR FROM HOT PRODUCT, REMOVE FROM EXPOSURE AN CALL A PHYSICIAN. INGESTION: IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:=204.4C, 400.F

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY (FOG).

Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD AS THEY MAY EXPLODE.

===== Accid

ental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE. WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWER S AND WATER COURSES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE.

DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDER BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.

Ventilation:LOCAL EXHAUST USED TO CAPTURE FUMES AND VAPORS.

Protective Gloves:OIL-RESISTANT GLOVES, IF NEEDED.

Eye Protection:GOGGLES, IF CHANCE OF EYE CONTACT.

Other Protective Equipment:USE OIL-RE

SISTANT APRON, IF NEEDED.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NONE \*\*FORMULA: LITHIUM SOAP, MINERAL OIL AND ADDITIVES.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>287.8C, 550.F

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5(AIR=1)

Spec Gravity:0.94-0.95

Evaporation Rate & Reference: