View NSN Online: https://aerobasegroup.com/nsn/6830-01-394-5461

DU PONT E I DE NEMOURS AND CO INC, CHEM. FLUOROCH. -- SUVA MP 66 (R 401 B),8968 -- 6830-01-394-5461

Product ID:SUVA MP 66 (R 401 B),8968 MSDS Date:10/05/1996 FSC:6830 NIIN:01-394-5461 MSDS Number: CHKZQ === Responsible Party === Company Name: DU PONT E I DE NEMOURS AND CO INC, CHEM. FLUOROCH. Address:1007 NARKET STREET City:WILMINGTON State:DE ZIP:19898 Country:U S Info Phone Num:800-441-9442 Emergency Phone Num:800-441-3637/800-424-9300(CHEMTREC) CAGE:2S827 === Contractor Identification === Company Name: DU PONT FLUOROPRODUCTS Address:1007 MARKET STREET Box:City:WILMINGTON State:DE ZIP:19898 Country:US Phone:1-800-441-7515 CAGE:2S827 Ingred Name: CHLORODIFLUOROMETHANE (SARA 313) (CERCLA) CAS:75-45-6 RTECS #:PA6390000 Fraction by Wt: 61% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 P

PM ACGIH TLV:1000 PPM; 9596 Ozone Depleting Chemical:2

Ingred Name: ETHANE, 1,1-DIFLUORO CAS:75-37-6 RTECS #:KI1410000 Fraction by Wt: 11% Other REC Limits: TWA 1000 PPM 8HR, MFR Ingred Name:2-CHLORO-1,1,1,2-TETRAFLUOROETHANE (SARA 313) CAS:2837-89-0 Fraction by Wt: 28% Other REC Limits: TWA 1000 PPM 8HR, MFR LD50 LC50 Mixture: TLV 1,000 PPM/3540 MG/M3,8H TWA(HCFC-22) Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: CNS, EYE, SKIN, LUNG. ACUTE- HARMFUL IF INHALED. MAY CAUSE HEART IRREGULARITIES, UNCONSCIOUSNESS OR DEATH. INTENTIONAL MISUSE IS FATAL. VAPOR REDUCES OXYGEN & IS HEAVIER THAN AIR. EYE/SK IN CONTACT WITH LIQUID CAN CAUSE FROSTBITE. VAPORS CAN CAUSE EYE IRRITATION. INGESTION IS UNLIKELY. CHRONIC- UNKNOWN. Explanation of Carcinogenicity:NONE Effects of Overexposure: TEMPORARY NERVOUS SYST **EM DEPRESSION WITH** ANAESTHETIC EFFECTS SUCH AS DIZZINESS, HEADACHE, CONFUSION, INCOORDINATION, LOSS OF CONSCIOUSNESS, IRREGULAR PULSE, PALPITATIONS, INADEQUATE CIRCULATION, FROST BITE, IRRITATION, **BLURRED VISION, TEARING** Medical Cond Aggravated by Exposure: INDIVIDUALS WITH PREEXISTING DISEASES OF THE CENTRAL NERVOUS OR CARDIOVASCULAR SYSTEM MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURE.

\_\_\_\_\_

First Aid:GET MEDICAL ATTENTION IF NEEDED. EYE/SKIN:IMMEDIATELY FLUSH WITH PLENTY OF WATER. INHALED:REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED. ORAL:INGESTION IS NOT CONSIDERED A POTENTIAL ROUTE OF EXPO SURE. NOTE TO PHYSICIAN:CATECHOLAMINE DRUGS SHOULD BE USED WITH SPECIAL CAUTION ONLY IN SITUATIONS OF EMERGENCY LIFE SUPPORT.

Flash Point:NONE Autoignition Temp:Autoignition Temp Text:126 5F

Lower Limits:NOT RELEVANT

Upper Limits:NOT RELEVANT

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CYLINDERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. MOVE CYLINDERS FROM FIRE AREA IF POSSIBLE WITHOUT INCREASED PERSONAL RISK.

Unusual Fire/Explosion Hazard:THIS PRODUCT MAY IGNITE WHEN MIXED WITH AIR ABOVE (60 PSIG) OR AT ATMOSPHER

IC PRESSURE. CYLINDERS MAY RUPTURE. DECOMPOSITION PRODUCTS ARE TOXIC AND CORROSIVE.

Spill Release Procedures: VENTILATE AREA, ESPECIALLY LOW PLACES WHERE VAPORS MIGHT COLLECT. REMOVE OPEN FLAMES. USE SELF-CONTAINED BREATHING APPARATUS FOR LARGE SPILLS OR RELEASES. Neutralizing Agent: NOT RELEVANT

Handling and Storage Precautions:STORE IN A COOL, DR

Y, WELL VENTILATED

AREA, AWAY FROM FLAMES & INCOMPATIBLE MATERIALS. DO NOT HEAT ABOVE 52C/126F.

Other Precautions: AVOID BREATHING VAPORS. AVOID EYE OR SKIN CONTACT. WASH WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING OR DRINKING. USE WITH ADEQUATE VENTILATION. NEVER USE IN CONFINED OR CLOSED SPACES WITHOUT PROPER PROTECTIVE EQUIPMENTS.

Respiratory Protection:WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING

APPARATUS OPERATED IN POSITIVE PRESSURE MODE OR SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE IF A LARGE RELEASE OCCURS.

Ventilation:NORMAL VENTILATION IS SUFFICIENT. LOCAL EXHAUST WHEN LARGE AMOUNTS ARE RELEASED, MECHANICAL VENTILATION IN LOW PLACES

Protective Gloves:LINED BUTYL GLOVES

Eye Protection: CHEMICAL SPLASH GOGGLES/FACE SHIELD

Other Protective Equipment: EYEBATH, WASHING FACILITY, SAFETY SHOWER, UNIFOR

Μ

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

HCC:G3 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:-30F,-35C Vapor Pres:6142 @ 77F Vapor Density:3.2 Spec Gravity:1.193 @ 77F LIQ Viscosity:NOT RELEVANT Evaporation Rate & amp; Reference:>1 (CCL4=1) Solubility in Water:0.1% @ 25C/77F Appearance and Odor: CLEAR, COLORLESS LIQUEFIED GAS - SLIGHT **ETHEREAL** ODOR Percent Volatiles by Volume:100 Stability Indicator/Materials to Avoid:YES ALKALI OR ALKALINE EARTH METALS, POWDERED ALUMINUM, ZINC, BERYLLIUM, ETC. Stability Condition to Avoid: OPEN FLAME, GLOWING METAL SURFACES, HIGH TEMPERATURES (52C/126F) Hazardous Decomposition Products: MAY FORM HYDROGEN FLUORIDE, HYDROGEN CHLORIDE AND TRACES OF CARBONYL HALIDES.

====== Disposal Consideration

Waste Disposal Methods:TREATMENT, STORAGE, TRANSPORTATION AND DISPOSAL MUST BE IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS. RECOVER BY DISTILLATION OR REMOVE TO A PERMITTED WASTE DISPOSAL FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.