

EASTMAN KODAK COMPANY -- 175 6337 KODAK FLEXICOLOR SM TANK DEVELOPER/C-41SM,
PART A -- 6750-01-443-3307

===== Product Identification =====

Product ID:175 6337 KODAK FLEXICOLOR SM TANK DEVELOPER/C-41SM, PART A

MSDS Date:11/07/1997

FSC:6750

NIIN:01-443-3307

Kit Part:Y

MSDS Number: CHLBK

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP

:14650

Country:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====

=====
Composition/Information on Ingredients
=====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 55-60%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

Ingred Name:POTASSIUM CARBONATE
CAS:584-08-7
RTECS #:TS7750000
Fraction by Wt: 25-30%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM BICARBONATE
CAS:298-14-6
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM SULFITE
CAS:7757-83-7
RTECS #:WE2150000

Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PENTETIC ACID, PENTA SODIUM SALT
CAS:140-01-2
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SULFITE
CAS:10117-38-1
RTECS #:WT3530000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM BROMIDE
CAS:7647-15-6
RTECS #:VZ3150000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalati

on:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION-EXPECTED TO BE A LOW HAZARD FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL. EYES-CAUSES IRRITATION. SKIN-THIS MATERIAL HAS A LOW POTENTIAL TO CAUSE ALLERGIC SKIN REACTIONS . INGESTION-MAY BE HARMFUL IF SWALLOWED.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:INGESTION-SOME ASTHMATICS OR SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MIN. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER . GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHIN

G.

Unusual Fire/Explosion Hazard:NONE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE TO REMOVE RESIDUAL CONTAMINATION.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and St

orage Precautions:KEEP CONTAINER CLOSED.

Other Precautions:AVOID BREATHING MIST OR VAPOR. AVOID CONTACT WITH EYES AND PROLONGED OR REPEATED CONTACT WITH SKIN. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.

Protective Gloves:IMPERVIOUS GLOVES SHOULD BE WORN.

Eye Protection:WEAR SAFETY GLASSES W/SIDE SHIELDS.

Other Protective Equipment:EYE BATH, SAFETY SHOWER, WASHING FACILITIES.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

KEY1:N1. THIS IS PART "A" OF A THREE PART KIT. THERE IS ALSO A MATERIAL SAFETY DATA SHEET FOR THE WORKING SOLUTION.

=====
===== Physical/Chemical Properties =====

HCC:B3

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18

Vapor Density:0.6

Spec

Gravity:1.408

pH:10.9

Solubility in Water:COMPLETE

Appearance and Odor:LIGHT, COLORLESS, ODORLESS.

Percent Volatiles by Volume:55-60

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE WITH COMMON MATERIALS AND CONTAMINANTS WITH WHICH THE MATERIAL MAY REASONABLY COME INTO CONTACT.

Stability Condition to Avoid:STABLE.

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

=====
===== Disposal Considerations

=====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. A

ny person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.