View NSN Online: https://aerobasegroup.com/nsn/6850-01-304-6416

Product ID:TURCO 4316-L MSDS Date:09/30/1997 FSC:6850 NIIN:01-304-6416 MSDS Number: CHMFS === Responsible Party === Company Name: TURCO PRODUCTS INC Address:2375 STATE RD City:CORNWELLS HEIGHTS (FORMALLY BENSALEM State:PA ZIP:19020 Country:US Info Phone Num:215-245-3128 Emergency Phone Num:215-419-6376 Prepar er's Name: JOHN F. GRAINGER CAGE:0BYL8 === Contractor Identification === Company Name: AMJAY CORP. DBA AMJAY CHEMICALS Address:11200 WESTHEIMER SUITE 310 Box:218786 **City:HOUSTON** State:TX ZIP:77218-8786 Country:US Phone:713-492-2000 CAGE:64184 Company Name: ELF ATOCHEM NORTH AMERICA INC Address:2375 STATE ROAD Box:City:BENSALEM State:PA ZIP:19020 Country:US Phone:215-245-3128 CAGE:02BJ0 Company Name: TURCO PRODUCTS INC Address:7300 BOLSA AVE City:WESTMINSTER State:CA ZIP:92684-3600 Country:US Phone:7

14-890-3600 CAGE:0BYL8 Company Name: TURCO PRODUCTS, INC. Address:7300 BOLSA AVE Box:6200 City:WESTMINSTER State:CA ZIP:92684-3600 Country:US Phone:614-387-6200 CAGE:0BYN5 Company Name: TURCO PRODUCTS, INC. DIVISON OF ELF ATOCHEM NORTH AMERICA Address:2000 MARKET ST Box:City:PHILADELPHIA State:PA ZIP:19103-3222 Country:US Phone:215-419-7890 CAGE:61102 Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT _____ Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic: EYES: CAUSES SEVERE BURNS, POSSIBLE PERMANENT TISSUE DAMAGE ... BLINDNESS.SKIN:SEVERE

IRRITANAT, PERMANENT TISSUE DAMAGE. CHROMATES ARE SKIN SENSITIZERS.INHAL:SEVERE IRRITANT, POSSIBLE DAMAGE TO UPPER RESP IRATORY TRACT.LUNG CANCER RISK.INGEST:SEVERE IRRITATION, TISSUE DAMAGE.POSSIBLY F ATAL(EFFECTS DO NOT APPEAR IMMEDIATELY). Explanation of Carcinogenicity:HEXAVALENT CHROMIUM IS SUSPECTED

CARCINOGEN. Effects of Overexposure:EYES/SKIN/INGEST/INHAL:IRRITATION,BURNS. Medical Cond Aggravated by Exposure:THE CHRONIC EFFECTS OF THIS PRODUCT ARE EXPECTED TO BE THE SAME AS THE ACUTE EFFECTS REPORTED IN THE HEALTH HAZARD SECTION.

First Aid:INHAL:REMOVE TO FRESH AIR. GIVE O2 IF NEEDED.GET MEDICAL ATTE

NTION. EYES: IMMEDIATELY FLUSH WITH WATER FOR 5 MIN; NORMAL SALINE FOR 30-60 MIN. (HOLD LIDS OPENED)GET MEDICAL ATTENTION. SKIN: REMOVE CONTA MINATED CLOTHING, FLUSH WITH WATER UNTILSLIPPERY FEELING IS GONE.GET MEDICAL ATTENTION. INGEST: DO NOT INDUCE VOMITING, UNLESS ADVISED BY QUALIFIED MEDICAL PERSONNEL, DILUTE W/MILK OR WATER, CALL PHYSICIA

Flash Point:NON-FLAMMABLE Extinguishing Media:MEDIA APPROPRIATE FOR S URROUNDING FIRE. Fire Fighting Procedures:FIREFIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:AVOID CONTACT WITH AL,ZN,TIN,ETC.MAY GENERATE HYDROGEN GAS IN EXPLOSIVE AMOUNTS.

Spill Release Procedures:CONTAIN SPILL;STOP LEAK AT SOURCE.VENTILATE AREA.EVACUATE PERSONNEL.PUMP LIQ UID INTO A DOT APPROVED DRUM FOR DISPOSAL. WASH SPILL AREA WITH WATER(PLACE WASH WATER INTO DRUM).AVOID SPILLAGE INTO SEWER OR WATERWAYS. Neutralizing Agent:BORIC ACID, DILUTE ACETIC ACID.

Handling and Storage Precautions:STORE IN A PROTECTED COOL, DRY AREA.
KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN
Other Precautions:HAZARDOUS CARBON MONOXIDE CAN FORM UPON CONTACT WITH FOOD OR BEVERAGES ...THIS CAN COLLECT IN
ENCLOSED SPACES AND BE FATAL.WHEN MIXING ADD WATER SLOWLY!AVOID SPLASHING.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE REQUIRED. ALWAYS USE NIOSH/MSHA APPROVED RESPIRATORS WHEN REQUIRED. Ventilation:USE ADEQUATE MECHANICAL VENTILATION. Protective Gloves:ALKALI RESISTANT(NEOPRENE,VITON) Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. PROTECTIVE CLOTHING(EG. VIT ON,NEOPRENE).
Work Hygienic Practices:WASH HANDS AND FACE BEFORE EATING,SMOKING. SEPERATE WORK CLOTHING;LAUNDER BEFORE REUSE.
Supplemental Safety and Health
BEORE REPAIRING TANK,RELEASE PRESSURE,COVER OPENING TO AVOID BEING SPRAYED BY LIQUID UNDER PRESSURE.WHEN ENTERING TANK USE RESPIRATORY PROTECTION AND A SAFETY LINE;HAVE SOMEONE WATCHING AT A SAFE DIST ANCE.

HCC:B1 Boiling Pt:=143.3C, 290.F Vapor Pres:5 Vap or Density:>1.0 Spec Gravity:1.52 pH:14.0 Evaporation Rate & amp; Reference: