

FLINN SCIENTIFIC INC -- SULFUR HEXAFLUORIDE -- 6830-00-985-7283

=====
Product Identification
=====

Product ID:SULFUR HEXAFLUORIDE

MSDS Date:07/13/1996

FSC:6830

NIIN:00-985-7283

Status Code:A

MSDS Number: CHVWW

=== Responsible Party ===

Company Name:FLINN SCIENTIFIC INC

Address:910 W WILSON ST

Box:219

City:BATAVIA

State:IL

ZIP:60510-1606

Country:US

Info Phone Num:708-879-6900/800-452-1261

Emergenc

y Phone Num:800-452-1261/800-424-9300(CHEMTREC)

CAGE:8U825

=== Contractor Identification ===

Company Name:FLINN SCIENTIFIC INC

Address:770 N RADDANT RD

Box:231

City:BATAVIA

State:IL

ZIP:60510-2471

Country:US

Phone:630-879-6900; 800-452-1261

CAGE:8U825

=====
Composition/Information on Ingredients
=====

Ingred Name:SULFUR HEXAFLUORIDE

CAS:2551-62-4

RTECS #:WS4900000

Fraction by Wt: 99.8%MIN

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9596

=====

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:TLV IS 1000 PPM.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS: CENTRAL NERVOUS SYSTEM,
RESPIRATORY TRACT. ACUTE- ACTS AS AN ASPHYXIANT. INHALATION OF
OXYGEN-DEFICIENT ATMOSPHERE CAN CAUSE HEADACHE, SHORTNESS OF
BREATH, DIZZINESS, RINGING IN EARS. AT HIGH CONCENTRATIONS MAY
CAUSE COMA & DEATH. I

INGESTION/SKIN IS NOT LIKELY. CHRONIC- MAY
CAUSE CNS DEPRESSION.

Explanation of Carcinogenicity:NONE.

Effects of Overexposure:INCREASED BREATHING AND PULSE RATES, MUSCULAR
INCOORDINATION, FAULTY JUDGMENT, DISORIENTATION, EYE IRRITATION,
BREATHING DIFFICULTIES, PAIN, EXCESSIVE TEARING, HEADACHE,
DIZZINESS, NAUSEA, UNCONSCIOUSNESS, DEATH

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING EYE
PROBLEMS OR IMPAIRED CENTRAL NERVOUS SYSTEM OR RESPIRATORY FUNCTION
MAY
BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

=====
===== First Aid Measures =====
=====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: IMMEDIATELY
FLUSH WITH WARM WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. INHALED:
MOVE TO FRESH AIR. PROVIDE OXYGEN/CPR IF NEEDED. SKIN/ORAL UNLIKELY
(GAS) . RESCUERS SHOULD WEAR NIOSH-APPROVED SELF-CONTAINED
BREATHING APPARATUS & PERSONAL PROTECTIVE EQUIPMENT.

=====
===== Fire Fighting Measures =====
=====

Flash Point:NOT RELEVANT

Lower Limits:NOT RELEVANT

Upper Limits:NOT RELEVANT

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL
FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR NIOSH APPROVED SELF-CONTAINED BREATHING
APPARATUS AND PROTECTIVE CLOTHINGS. USE WATER FROM DISTANCE TO COOL
FIRE-EXPOSED CYLINDERS.

Unusual Fire/Explosion Hazard:CYLINDERS MAY EXPLODE IN HEAT OF FIRE.
FIRE MAY PRODUCE IRRITATING AND POISONOUS GASES.

=====

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PERSONAL PROTECTIVE EQUIPMENT. EVACUATE ALL PERSONNEL FROM RELEASE AREA. STOP LEAK IF POSSIBLE. VENTILATE AREA ESPECIALLY LOW PLACES. PRODUCT WILL DISPERSE ITSELF. SPILLS MAY HAVE TO BE REPORTED TO FEDERAL AND/OR LOCAL AUTHORITIES.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE CYLINDERS UPRIGHT AND SECURE IN

WELL VENTILATED AREA. DO NOT STORE ABOVE 125F/52C. KEEP AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:DO NOT DEFACE CYLINDERS OR LABELS. HANDLE CYLINDERS WITH PROPER CAUTION. USE A SUITABLE HAND TRUCK FOR CYLINDER MOVEMENT. USE A FIRST-IN FIRST-OUT SYSTEM. AVOID BREATHING GAS. WASH HANDS AFTER HANDLING CYLINDERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH-APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS OR AIR-SUPPLIED RESPIRATOR IF ABOVE TLV.

Ventilation:USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV REQUIREMENTS.

Protective Gloves:LEATHER FOR HANDLING CYLINDERS

Eye Protection:SAFETY GLASSES WITH SIDE SHIELD/GOGGLES

Other Protective Equipment:SAFETY SHOES, COVERALLS, EYE WASH STATION MAY BE NECESSARY.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:G3

NRC/State Lic Num:NOT RELEVANT

Vapor Density:5.11

Spec Gravity:NOT RELEVANT

Viscosity:NOT RELEVANT

Evaporation Rate & Reference:NOT RELEVANT

Solubility in Water:5.4 ML/KG 1 ATM, 77F

Appearance and Odor:COLORLESS, ODORLESS GAS

Percent Volatiles by Volume:99.8

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS, ORGANOMETALLICS, CHEMICALLY ACTIVE METALS (SODIUM,

POTASSIUM, BARIUM, POWDERED MAGNESIUM AND ALUMINUM)

Stability Condition to Avoid: EXCESSIVE HEAT, OPEN FLAMES, MOISTURE

Hazardous Decomposition Products: MAY FORM SF₄, S₂F₂, S₂F₁₀ WITH SULFUR

TETRAFLUORIDE PREDOMINATING. IF MOISTURE PRESENT, MAY FORM HYDROGEN SULFIDE & HF.

===== Disposal Considerations =====

Waste Disposal Methods: MOVE LEAKY CYLINDER TO OUTDOORS OR VENTILATED HOOD. ALLOW GAS TO DISCHARGE AT MODERATE RATE. DISPOSAL SHOULD BE MADE I

N ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. CYLINDERS CAN BE RETURNED TO SUPPLIER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.