

CARIBIAN PAIT -- SYNTHETIC WOOD STAIN TT-S-711C SEMI-TRANS LIGHT OAK --
8010-00-597-8226

===== Product Identification =====

Product ID:SYNTHETIC WOOD STAIN TT-S-711C SEMI-TRANS LIGHT OAK

MSDS Date:01/02/1996

FSC:8010

NIIN:00-597-8226

Status Code:A

MSDS Number: CHWQR

=== Responsible Party ===

Company Name:CARIBIAN PAIT

Address:5295 NW 79TH AVE.

City:MIAMI,

State:FL

Country:US

Info Phone Num:305-

594-4500

Emergency Phone Num:800-242-4100

CAGE:0YF41

=== Contractor Identification ===

Company Name:CARIBIAN PAIT

Address:5295 NW 79TH AVE.

Box:City:MIAMI,

State:FL

Country:US

Phone:305-594-4500

CAGE:0YF41

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:64642-88-7

Other REC Limits:100PPM OCUP EXP LMT

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcino

genicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION, SKIN: IRRITATION,
DERMATITIS, RESPIRATORY: IRRITATION, HEADACHE, DIZZINESS,
UNCONSCIOUSNESS

Explanation of Carcinogenicity:NO

=====
===== First Aid Measures =====

First Aid:INHALATION: MOVE TO FRESH AIR OR WELL-VENTILATED
AREA,RESTORE BREATHING, GET MED AID. SKIN:WIPE W/CLEAN CLOTH,
WASH THOROUGHLY W/SOAP AND WATR. EYES: FLUSH THOROUGHLY W/WATR,
GET
MED AID.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:105F,41C

Lower Limits:1.0

Extinguishing Media:FOAM, CO2 DRY CHEMICAL

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE ON FIRE. WATER SPRAY
MAY BE USED TO COOL CLOSED CONTAINERS EXPOSED TO EXTREME HEAT TO
PREVENT EXPLOSION

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN
EXPOSED TO EXTREME HEAT OR FIRE. VAPORS MAY IGNITE.

=====
===== Accidental
Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VENTILATE
AREA, MOP SPILLS W/INERT ABSORBANT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 100F, KEEP CONTAINERS
CLOSED AND AWAY FROM HEAT AND OPEN FLAME

Other Precautions:AVOID PROLONGED CONTACT W/SKIN AND BREATHING VAPORS
OR SPRAY MIST. DO NOT APPLY TO HOT SURFACES. AVOID CONTAM W/FOREIGN
MATERIALS. DO NOT TAKE INT
ERNALLY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:(SPRAYING APPLICATIONS) OPEN AREAS: PAINT SPRAY
MASK, USE MECHANICAL FILTER RESPIRATOR, RESTRICTED VENT AREAS:
USE PAINT SPRAY MASK AND APPROVED MECHANICAL FILTER. IN CONFINED:
USE AIRLINE RESPIRATORS OR HOODS

Ventilation:PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST

Protective Gloves:SOLVANT RESISTANT GLOVES

Eye Protection:SPLASH-PROOF GOGGLES

Supplemental Safety and Health

=====
=====

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:313F,156C

Vapor Density:HVR/AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:48.2

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN

Hazardous Decomposition Products:CO CO2 POSSIBLE NO(SUB)X POSSIBLE NO
SUB)X FUMES ON IGNITION.

===== Disposal Considerations =====

Waste

Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE
REGULATIONS. DO NOT INSINORATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.