View NSN Online: https://aerobasegroup.com/nsn/8010-01-309-0329

SHERWIN-WILLIAMS CO -- PRIMER EPOXY, LOW VOC, COR. INHIB. L/CF (B) (724737)

8010-01-309-0329

Product ID:PRIMER EPOXY, LOW VOC, COR. INHIB. L/CF (B) (724737)

MSDS Date: 09/24/1997

FSC:8010

NIIN:01-309-0329

Kit Part:Y

MSDS Number: CHWRQ === Responsible Party ===

Company Name: SHERWIN-WILLIAMS CO

Address:101 PROSPECT AVE N W

City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Info Phone Num:216-566-2902

Emergency Phone Num:216-566-2917

CAGE:54636

=== Contractor Identification ===

Company Name: SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

Box:City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Phone:800-251-2486/216-566-2242

CAGE:54636

======= Composition/Information on Ingredients ========

Ingred Name: TOLUENE (SARA 313) (CERCLA)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 21%

Other REC Limits: OSHA STEL 150 PP SKN

**OSHA PEL:100PPM SKIN** 

ACGIH TLV:S, 50 PPM; 9495

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: N-BUTYL ALCOHOL (SARA 313) (CERCLA)

CAS:71-36-3

RTECS #:EO1400000 Fraction by Wt: 2%(C)

Other REC Limits: NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:S, C 50 PPM; 9495

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: PHENYL METHANOL

CAS:100-51-6

RTECS #:DN3150000 Fraction by Wt: 4%

Other REC Limits: NONE RECOMMENDED

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)

CAS:78-93-3 RTECS #:EL6475

000

Fraction by Wt: 12%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200 PPMSTEL 300PPM ACGIH TLV:200 PPM/300STEL;9495

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:METHYL PROPYL KETONE (2-PENTANONE)

CAS:107-87-9

RTECS #:SA7875000 Fraction by Wt: 19%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200PPM/STEL250PPM ACGIH TLV:200 PPM/250STEL;9495

Ingred Name: METHYL ISOBUTYL KETONE (HEXONE) (SARA 313) (CERCLA)

CAS:108-10-1

RTECS #:SA9275000 Fraction by Wt: 1%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:50PPM/STEL75PPM ACGIH TLV:50 PPM/75 STEL; 9495

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:TRI(DIMETHYLAMINOMETHYL)PHENOL

CAS:90-72-2

RTECS #:SN3500000 Fraction by Wt: 1%

Other REC Limits: NONE RECOMMENDED

Ingred Name:4,4'-ISOPROPYLIDENEDIPHENOL (SARA 313)

CAS:80-05-7

RTECS #:SL6300000 Fraction by Wt: 4%

Other REC Limits: NONE RECOMMENDED

**ACGIH TLV:5 PPM** 

Ingred Name: 1-METHOXI-2-PROPENOL ACETATE

CAS:108-65-6

RTECS #:AI8925000 Fraction by Wt: 13%

Other REC Limits: NONE RECOMMEND

ED

Ingred Name: DIETHYLENETRIAMINE

CAS:111-40-0

RTECS #:IE1225000 Fraction by Wt: 4%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:1 PPM SKIN ACGIH TLV:S, 1 PPM; 9495

Ingred Name: EPOXY POLYMER

Fraction by Wt: 3%

Other REC Limits: NONE RECOMMENDED

Ingred Name: POLYAMIDE FIBER, NYLON 6.6 FIBER

Fraction by Wt: 4%

Other REC Limits: NONE RECOMMENDED


Ingred Name: POLYAMINE ADUCT

Fraction by Wt: 10%

Other REC Limits: NONE RECOMMENDED

========= Hazards Identification =============

Rou



======== Handling and Storage ============
Handling and Storage Precautions:CONTNTS FLAMABLE, KEEP AWAY FROM HEAT/IGNITABLES. KEEP VENTED. DO NOT SMOKE,CONSULT NFPA CODE. USE APRVD BNDG/GRDG, KEEP CLOSED WHEN NOT IN USE.  Other Precautions:USE ONLY COMPLETE AND PRROPRIATE LABELING. DO NOT TAKE INTERNALLY, KEEP OUT OF REACH OF CHILDREN.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:WEAR PROPERLY FITTED ORGANIC VAPOR/PA RTICULATE RESPIRATOR APRVD BY NIOSH/MSHA, WHEN SANDING, ABRADING, WEAR MIST/DUST RESPIRATOR APROVD BY NIOSH/MSHA Ventilation:LOCAL EXHAUST PREF, GENERAL EXHAUST ACCEPTABLE IF EXPOSURE BELO EXPSUR LMTS, USE ENOUGH VENT AVOID MST CNTNING PRTIC Protective Gloves:AS RECOM BY GLOVE SUPPLIER Eye Protection:SAFETY SPECS W/ UNPERF SIDE-SHIELDS Other Protective Equipment:BARRIER CREAM Supplemental Safety and Health MUST BE MXD W/OTHER COMPONENTS BEFORE USE. READ AND FOLLOW DIRECTIONS BEF ORE OPENING PACAGES OF ANY COMPONENTS. INTENT MIS-USE, HARMFUL OR FATAL. * MAY CAUSE HLTH HZARD, SYMPRMS MAY BE DELAYED. GET MED AID
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:174F,79C Vapor Pres:30.1@25C Vapor Density:HVR/AIR Spec Gravity:.90 VOC Grams/Liter:5.78 Evaporation Rate & Deference:SLOWER THAN ETHER Appearance and Odor:LIQUID, W/SOLVENT ODOR Percent Volatiles by Volume:80%
=========== Stability and Reactivity Data
Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:CO2 CO OXIDES OF NITROGEN, POSSIBILITY OF HYDROGEN-CYANIDE
======= Disposal Considerations ==========
Waste Disposal Methods:WASTE MAY BE HZRDOUS, MUST BE TESTED FOR IGNITABILITY. INSINORATE IN APRVD FACILITY.DO NOT INSINORATE CLOSD CNTNR. DISPOSEOF PER FED STE AND LOCAL REGS RE: POLUTION
========== Other Information =============

sclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.