

XYMAX COATINGS INC. -- MAX COAT HB SEMI-GLOSS BLACK #27038

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 01-436-7608  
MSDS Date: 06/07/1996  
MSDS Num: CHWSF  
Product ID: MAX COAT HB SEMI-GLOSS BLACK #27038  
MFN: 01  
Responsible Party  
Cage: 0ZP91  
Name: XYMAX COATINGS INC.  
Address: 1004 COBB PARKWAY NORTH, SUITE  
A  
City: MARIETTA GA 30062  
Info Phone Number: 800-332-3136  
Emergency Phone Number: 800-332-3136  
Proprietary Ind: Y  
Review Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: 0ZP91  
Name: XYMAX COATINGS INC.  
Address: 1004 COBB PARKWAY NORTH, SUITE A  
City: MARIETTA GA 30062  
Phone: 800-332-3136

=====  
Item Description Information  
=====

=====  
Item Manager: GSA  
Item Name: POLYURETHANE COATING  
Unit of Issue: GL  
UI Container Qty: 1

=====  
Ingredients  
=====

Name: \*\*\* PROPRIETARY \*\*\*  
-----

=====  
Health Hazards Data  
=====

LD50 LC50 Mixture: \*  
Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

OSHA: NO

Effects of Exposure: EYES: SEVERE/CHRONIC IRRITATION, REDNESS, WTRING, INFLAMATION, ITCHING. SKIN: HARMFUL IF ABSORBED, SENSITIZATION, INFLAMATION, IRRITATION, DESTRUCTION, DERMOTITIS, INGEST: CHEM BURNS IRRITATION, MAY BE FATAL, INJURY MAY BE SEVERE, INHALE:SEVERE/CHRONIC IRRITATION, SENSITIZATION,

Signs And Symptions Of Overexposure: TOXIC TO MUCUOUS MEMBRANES, UPPER RESP TRACT, LUNGS, BLOOD, KIDNEY, LIVER, POSSIBLE ASTHESMA, PULMONARUOEDEMA,

EFFECTS MAY BE DELAYED, POSSIBLE EXEMA. POSSIBLE PERMINANT CNS DAMAGE, NAUSEA, HEADACHE , VOMETING.

Medical Cond Aggravated By Exposure: SKIN/ASTHESMA TYPE CONDTIONS, LIVER/KIDNEY DISORDERS, IF ALLERGIC TO ISOCYANATES, AMINES, SOLVENTS OR HAVE ASTHEMA OR CHRON BRONCHITIS-- AVOID THIS PRODUCT

First Aid: EYES: REMOVE CONTACTS, IMMPLY FLUSH W/RUNNING WTR &gt;15 MIN HOLDING EYELIDS OPEN. DO NOT USE OINTMENT, GET MED AID. SKIN: WASH W/RUNING WTR/NON-ABRASIVE SOAP 15-30 MIN. HAND CREAM AFTE

R WASHING. GET MED AID WASH

CONTAM CLOTHING. INHALE: REMOVE TO FRESH AIR. GET IMMED MED AID, CPR, GET MED AID. INGEST: DO NOT INDUCE VOMET, IF CONSC, DRINK SEV GLASSES WTR/MLK, GET IMMED MED AID, AVOID ASPIRATION

=====  
Handling and Disposal

=====  
Spill Release Procedures: SM: ABSORB W/INERT MATL. PLACE IN CONT. DO NOT SEAL DRUM. LRG: ELIM ALL IGNITBLES WEAR FULL-PROT EQUIP+SCUBA STOP L EAK PREVENT

ENTRY INTO SEWERS/ALL WATRWAYS, DIKE AND COVER W/WET EARTH, SAND, DRY A BSORB, WETTED W/ NUTROLIZER. PLC IN CONTAF 15 MIN

Neutralizing Agent: 5% AMONIA WTR OR 5-10% SODIUM-CARBONATE IN WTR

Waste Disposal Methods: HAZARDOUS WASTE. FILL DRUMS HALFWAY, DO NOT SEAL. KEEP WELL VENTED. PER FED STATE LOCAL REGS, AVOID RESIDUE. DO NOT HEAT/CUT EMPTY CONTS W/ELECT/GAS TORCH

Handling And Storage Precautions: STORE IN SEPARATE SAFETY RM. AVOID ALL IGNITS, KEEP CONT TIGHTLY CLOSED IN

WELL VENTED DRY PLACE, REFRIG PREF. AVOID INCOMPATIBLES

Other Precautions: KEEP OUT OF REACH OF CHILDREN, AVOID ALL CONTACT W/PRODUCT. NO CONTACT LENSES, SHOW LABEL TO MED AID. GROUND AL EQUIP. ISOCYANATES CAN NOT BE SMELLED UNTIL WELL ABV SAFE EXPOSURE LIMIT

=====  
Fire and Explosion Hazard Information

=====  
Flash Point Method: CC

Flash Point Text: 75.2F,24.0C

Autoignition Temp Text: 315C

Lower Limits: .7%

Upper Limits: 25.1%

Extinguishing Media: SM FIRE: DRY CHEM, CO2 ALC FOAM, WTR SPRA, LG FIRE: WTR SPRA OR FOG, NEVER DIRECT WTR JET INSIDE CONTAINER

Fire Fighting Procedures: COOL CONT W/WTR SPRA/FOG, WEAR SCUBA VPR MAY TRAVL LONG DISTANCES TO SOURCE OF IGNTN AND FLASH BACK. EMITS HIGHLY TOXIC FUMES. CONT MAY EXPLD DUE TO HEAT

Unusual Fire/Explosion Hazard: VERY SLIGHTLY TO SLIGHTLY EXPLOSIVE IN PRESENCE OF OXIDIZING MATERIALS VPR FORMS EXPLOSIVE MIXTURE W/AIT BTWN LE L AND UEL

=====  
Control Measures  
=====

Respiratory Protection: NIOSH/MSHA APRVD VPR/DUST RESPIRATOR, (W/ORGANIC VPR CARTRAGES, SCUBA/AIR SUPPLIED RESPIRATOR,

Ventilation: EXHAUST VENTILATION, DO AIR MONITORING IF POSSIBLE

Protective Gloves: IMPERVIOUS

Eye Protection: SPLASH GOGGLES

Other Protective Equipment: EYE WASH STATION, SAFETY SHOWER, FULL SUIT, BOOTS,

Work Hygienic Practices: KEEP PRO

D AWAY FROM FOOD, DRINKS, TOBACCO, EATING,

DRINKING, SMOKING SHD BE PROHIB AROUND PRODUCT. WASH HANDS, FACE

Supplemental Safety and Health: LD50/LC50 INGREDIENTS IN WHICH LD50S HAVE BEEN

DETERMINED: PROPOLENE GLYCOL MONOMETHYL ETHER ACETATE, METHYL N-AMYL KETONE, XYLENES, ISOPHORONE DI-ISOCYANATE(IPDI) PETROLIUM NAPHTHA, DIISOBUTYLKETONE.

MORE INFO AVAILABLE ON FILE

=====  
Physical/Chemical Properties  
=====

B.P. Text: 281F,139C

Vapor Pres: 2.84@20C

Vapor Density: 5.12

Spec Gravity: 1,2848

Evaporation Rate & Reference: 0.3

Solubility in Water: INSOLUABLE

Appearance and Odor: LBLACK LIQUID, AROMATIC

Percent Volatiles by Volume: 37%

=====  
Reactivity Data  
=====

Stability Indicator: YES

Materials To Avoid: ALL IGNITIBLES/COMBUSTABLES, OXIDIZING/REDUCING MATL ACIDS, ALKALIS MOIS

TURE, ORGANIC MATERIALS, METALS

Hazardous Decomposition Products: CARBON OXIDES, NITRO OXIDES, ISOSIONATE  
VPRS, HYDROGEN SIONIDE

=====  
Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====  
Other Information  
=====

=====  
Transportation Information  
=====

Responsible Party Cage: 0ZP91

Trans ID NO: 136

656

Product ID: MAX COAT HB SEMI-GLOSS BLACK #27038

MSDS Prepared Date: 06/07/1996

Review Date: 09/30/1998

MFN: 1

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: GL

Container QTY: 1  
=====

=====  
Detail DOT Information  
=====

DOT PSN Code: LFE

DOT Proper Shipping Name: PAINT

DOT PSN Modifier: INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS,  
VARNISH, POLISH, LIQUID FILLER, AND LIQUID LACQU

ER BASE  
Hazard Class: 3  
UN ID Num: UN1263  
DOT Packaging Group: III  
Label: FLAMMABLE LIQUID  
Special Provision: B1,B52,T7,T30  
Packaging Exception: 150  
Non Bulk Pack: 173  
Bulk Pack: 242  
Max Qty Pass: 60 L  
Max Qty Cargo: 220 L  
Vessel Stow Req: E,B,A

=====  
Detail IMO Information  
=====

IMO PSN Code: LCT  
IMO Proper Shipping Name: PAINT OR PAINT RELATED MATERIAL  
IMO PSN Modifier: (INCLUDING PAINT, LACQUE  
R, ENAMEL, STAIN, SHELLAC SOLUTIONS,  
VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING PAINT  
THINNING OR REDUCING COMPOUND) o  
IMDG Page Number: 3372  
UN Number: 1263  
UN Hazard Class: 3.3  
IMO Packaging Group: III  
Subsidiary Risk Label: -  
EMS Number: 3-05  
MED First Aid Guide NUM: 310

=====  
Detail IATA Information  
=====

IATA PSN Code: SXH  
IATA UN ID Num: 1263  
IATA Proper Shipping Name: PAINT  
IATA PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC, VARNISH,  
POLISH, LIQUID FILLER AND LIQUID LACQUER BASE)  
IATA UN Class: 3  
IATA Label: FLAMMABLE LIQUID  
UN Packing Group: III  
Packing Note Passenger: 309  
Max Quant Pass: 60L  
Max Quant Cargo: 220L  
Packaging Note Cargo: 310

=====  
Detail AFI Information  
=====

AFI PSN Code: SXH  
AFI Proper Shipping Name: PAINT OR PAI

NT RELATED MATERIAL

AFI PSN Modifier: (INCLUDING PAINT, LACQUER, ENAMEL, STAIN, SHELLAC SOLUTIONS, VARNISH, POLISH, LIQUID FILLER AND LIQUID LACQUER BASE) OR (INCLUDING PAINT THINNING OR REDUCING COMPOUNDS)

AFI Hazard Class: 3

AFI UN ID NUM: UN1263

AFI Packing Group: III

Special Provisions: P5

Back Pack Reference: A7.3

=====  
HAZCOM Label  
=====

Product ID: MAX COAT HB SEMI-GLOSS BLACK #27038

Ca

ge: 0ZP91

Company Name: XYMAX COATINGS INC.

Street: 1004 COBB PARKWAY NORTH, SUITE A

City: MARIETTA GA

Zipcode: 30062

Health Emergency Phone: 800-332-3136

Label Required IND: Y

Date Of Label Review: 10/12/1999

Status Code: A

Origination Code: G

Hazard And Precautions: EYES: SEVERE/CHRONIC IRRITATION, REDNESS, WTRING, INFLAMATION, ITCHING. SKIN: HARMFUL IF ABSORBED, SENSITIZATION, INFLAMATION, IRRITATION, DESTRUCTION, DERMOTITIS, INGEST: CHEM BURNS IRRITATION, MAY BE FATAL, INJURY MAY BE SEVERE, INHALE:SEVERE/CHRONIC IRRITATION, SENSITIZATION,

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defe

nse

nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government

t situation.