

GIBSON-HOMANS CO -- BLACK JACK ALL WEATHER RF CMT -- 5610-00-236-4964

=====
Product Identification
=====

Product ID:BLACK JACK ALL WEATHER RF CMT

MSDS Date:10/12/1990

FSC:5610

NIIN:00-236-4964

Status Code:A

MSDS Number: CHXQB

=== Responsible Party ===

Company Name:GIBSON-HOMANS CO

Address:1755 ENTERPRISE PARKWAY

City:TWINSBURG

State:OH

ZIP:44087

Country:US

Info Phone Num:216-467-8128

Emergency Ph

one Num:216-425-3255

CAGE:GIBHO

=== Contractor Identification ===

Company Name:GIBBSON-HOMANS CO

Address:1755 ENTERPRISE PARKWAY

Box:City:TWINSBURG

State:OH

ZIP:44087

Country:US

Phone:216-467-8128

CAGE:0U534

Company Name:GIBSON-HOMANS CO

Address:1755 ENTERPRISE PARKWAY

City:TWINSBURG

State:OH

ZIP:44087

Country:US

Phone:216-425-3255

CAGE:GIBHO

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 10-30%

OSHA PEL:500 PPM
ACGIH TLV:100 PPM

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: SKIN: PROLONGED/REPEATED
CONTACT MAY CAUSE IRRITATION. EYES: MAY CAUSE IRRITATION, BLURRED
VISION. INHALATION: EXCESSIVE BREATHING OF HIGH VAPOR
CONCENTRATIONS CAN CAUSE NASAL AND RE
SPIRATORY IRRITATION,
DIZZINESS, NAUSEA, POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION.
INGESTION: CAN CAUSE (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of Overexposure:HLTH HAZ: GASTROINTESTINAL IRRITATION, NAUSEA,
VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.
Medical Cond Aggravated by Exposure:PRE-EXISTING LUNG AND SKIN
DISORDERS.

===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH LARGE
AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. INHALATION: REMOVE PERSON
FROM AFFECTED AREA. IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. IF
BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. INGESTION: DO
NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:105F,41C
Lower Limits:0.8%
Upper Li
mits:7.0%
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS.
Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT . WATER MAY CAUSE FROTHING, APPLY CAUTIOUSLY.
Unusual Fire/Explosion Hazard:KEEP AWAY FROM SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE SPILL AREA. RECOVER FREE LIQUID, ADD
ABSORBENT TO SPILL AREA. REMOVE SOURCES OF IGNITION. VENTILATE AREA
IF NECESSARY.
Neutralizing

Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM SOURCES OF IGNITION.
USE ONLY WITH ADEQUATE VENTILATION. AVOID PROLONGED/REPEATED
CONTACT WITH SKIN.

Other Precautions:KEEP OUT OF THE REACH OF CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NEEDED IN WELL VENTILATED AREA. IF
TLV IS EXCEEDED, A NIOSH APPROVED BRE
ATHING APPARATUS IS
RECOMMENDED.

Ventilation:AS NECESSARY TO MAINTAIN EXPOSURE BELOW TLV LEVEL.

Protective Gloves:OIL RESISTANT GLOVES.

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPRVD EYE WASH & DELUGE SHOWER . AS
NECESSARY.

Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING, LAUNDER BEFORE
REUSE.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

=====
===== Physical/Chemical Properties =====

Boiling Pt:B

.P. Text:>300F,>149C

Vapor Pres:21 @ 25C

Vapor Density:>1

Spec Gravity:1.1

Evaporation Rate & Reference: