

CASTROL INDUSTRIAL NORTH AMERICA INC -- BRAYCOTE 194, SPD -- 8030-01-340-4866
===== Product Identification =====

Product ID:BRAYCOTE 194, SPD

MSDS Date:04/14/1998

FSC:8030

NIIN:01-340-4866

Status Code:A

MSDS Number: CHXQV

=== Responsible Party ===

Company Name:CASTROL INDUSTRIAL NORTH AMERICA INC

Address:1001 WEST 31ST ST

City:DOWNERS GROVE

State:IL

ZIP:60515-1280

Country:US

Info Phone Num:800-62

1-2661

Emergency Phone Num:800-424-9300(CHEMTREC)

CAGE:CASTI

=== Contractor Identification ===

Company Name:CASTROL INDUSTRIAL INC

Address:1001 W 31ST

City:DOWNERS GROVE

State:IL

ZIP:60515-1280

Country:US

Phone:708-241-4000

CAGE:CASTI

Company Name:CASTROL INDUSTRIAL NORTH AMERICA INC SPECIALTY PRODUCTS
DIV

Address:1001 WEST 31ST STREET

Box:City:DOWNERS GROVE

State:IL

ZIP:60515-1280

Country:US

Phone:800-621-2661/ FAX: 630-241-4140

CAGE:2R128

===== Composition/Information on Ingredie

nts =====

Ingred Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 40-45%
OSHA PEL:500 PPM
ACGIH TLV:100 PPM

Ingred Name:SUPDAT: THE HEAD DOWN. SEEK IMMEDIATE MED ATTENTION. INHALATION: REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING HAS (ING 3)
RTECS #:9999999ZZ

Ingred Name:ING 2: STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP PERSON WARM & AT REST. TREAT SYMPTOMATICALLY & SUPPORTIVELY. GET MEDICAL (ING 4)
RTECS #:9999999ZZ

Ingred Name:ING 3: ATTENTION IMMEDIATELY.
RTECS #:99999
99ZZ

Ingred Name:SPILL PROC: FLUSH AREA WITH WATER. WHERE FEASIBLE & APPROPRIATE, REMOVE CONTAMINATED SOIL. SMALL SPILLS: NEUTRALIZE &/OR SOAK (ING 6)
RTECS #:9999999ZZ

Ingred Name:ING 5: UP SPILL WITH INERT ABSORBENT. STORE IN CLOSED CONTAINER & DISPOSE OF PROPERLY.
RTECS #:9999999ZZ

Ingred Name:OTHER PROTECTIVE EQUIPMENT: ALCOHOL RESISTANT BARRIER HAND CREAM. IMPERMEABLE PROTECTIVE CLOTHING & CHEMICAL RESISTANT SAFETY SHOES (ING 8)
RTECS #:9999999ZZ

Ingred Name:ING 7: SHOULD BE WORN TO MINIMIZE CONTACT.
RTECS #:999999
9ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: MAY CAUSE EYE IRRITATION. SKIN CONTACT: CONCENTRATE MAY CAUSE SKIN IRRITATION. SKIN ABSORPTION: NO ACUTE EFFECTS EXPECTED. INGESTION: THIS PRODUCT MAY CAUSE GASTROINTESTINAL DISTRESS WITH SYMPTOMS OF NAUSEA, VOMITING

G,
DIARRHEA AND ABDOMINAL PAIN. INHALATION: INHALATION OF HIGH CONCENTRATIONS OF (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HLTH HAZ: MISTS MAY PRODUCE IRRITATION AND DAMAGE TO THE RESPIRATORY TRACT. CHRONIC: A REVIEW OF THE LITERATURE DOES NOT SHOW OBVIOUS LONG TERM HAZARD.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYES: IMMEDIATE FLUSH WITH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MIN.
GET MED ATTENTION IMMEDIATE. SKIN: IN CASE OF CONTACT, WASH SKIN WITH PLENTY OF SOAP & WATER. REMOVE CONTAMINATED CLOTHING. GET MED ATTENTION IF IRRITATION PERSISTS. WASH CLOTHING BEFORE REUSE. USE SKIN CREAM FOR DEFATTED AREAS. INGESTION: ASPIRIN HAZARD:DO NOT INDUCE VOMIT OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER LUNGS & CAUSE SEVERE DAMAGE. DO NOT LEAVE (SUPERDAT)

=====
Fire Fighting Measures
=====

Flash Point Method:COO
Flash Point
Temperature: >100F, >38C
Extinguishing Media: DRY CHEMICAL, WATER FOG, CHEMICAL FOAM OR CARBON DIOXIDE. DIRECT WATER-STREAM MAY CAUSE FROTHING.
Fire Fighting Procedures: USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. WATER/FOAM MAY CAUSE FROTHING. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO (SUPERDAT)
Unusual Fire/Explosion Hazard: HAZARDOUS PRODUCTS OF COMBUSTION: IRRITATING OR TOXIC FUMES; CARBON MONOXIDE & CARBON DIOXIDE; OXIDES OF SULFUR.
Properties that could increase fire/explosion hazard: NONE KNOWN.

=====
Accidental Release Measures
=====

Spill Release Procedures: LARGE SPILLS: WEAR APPROPRIATE PROTECTIVE CLOTHING. STOP SOURCE OF LEAK IF POSSIBLE. DIKE, CONTAIN SPILL & RECOVER FREE LIQUID. PREVENT ENTRY INTO WATERWAYS. SOAK UP RESIDUE WITH INERT ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIALS; STORE & DISPOSE OF PROPERLY.
(ING 5)
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handli

ing and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE NEAR HEAT, FLAME, STRONG OXIDANTS. MAINTAIN ADEQUATE VENTILATION.

Other Precautions:MAINTAIN AMBIENT TEMPERATURES. AVOID PROLONGED/REPEATED BREATHING OF VAPORS, MISTS, FUMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE IF VAPOR CONCENTRATIONS EXCEED PERMISSIBLE EXPOSURE LIMIT.

Ventilation:PROVIDE SUFFICIENT MECH, GENERAL &/OR LOCAL EXHAUST TO MAINTAIN EXPOS BELOW TLV. GREATER THAN 60F3/MIN RECOMMENDED.

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPROVED EYE WASH & DELUGE SHOWER IN ALL AREAS IN WHICH THIS PROD IS HANDLED. PETROLEUM SOLVENT & (ING 7)

Work Hygienic Practices:WASH CONTAMINATED CLOTHING WITH SOAP AND WATER AND DRY BEFORE REUSE.

Supplemental Safety and Health

FIRE FIGHT PROC: FLUSH SPILL

S AWAY FROM EXPOS. FOR FIRES IN ENCLSD

AREAS, FIREFIGHTERS MUST USE NIOSH APPROVED SCBA. PVNT RUNOFF FROM FIRE CONTROL OR DILUTION FROM ENTERING STREAMS OF DRINKING WATER SUP PLY. FIRST AID PROC: VICTIM UNATTENDED.IF VOMIT OCCURS, OR IF COMATOSE OR LETHARGIC, PLACE ON LEFT SIDE WITH (ING 2)

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:300F,149C

Vapor Pres:2

Vapor Density:>1

Spec Gravity:0.8700 (H*2O=1)

Evaporation Rate & Reference: